ASSOCIATION CONNECTING ELECTRONICS INDUSTRIES® INCLUSTRIES®	. Bannockb	ourn. Illinois. A	Il rights reserved untions.	under both	This docume level parts, t	ent is a declaration	ion of the s encompasse	ubstances s all lowe	within the r level mat	manufacture erials for wh	er listed iter hich the man	n. Note: nufacture	if the item is an as er has engineering	sembly with low responsibility.
				Form Type Distribute	*	Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Materi					als and Mfg Information			
Supplier Information														
Company name* Co			Company unique ID			Unique ID Authority					Response Date*			
onsemi									2024-04-30					
ntact Name Title - Contact			ct		Phone - Contact*					Email - Contact*				
Product-Env-Stewards Product Er			et Enviro Compliance			NA				Product-Env-Stewards@onsemi.com				
Authorized Representative* Title - Re			- Representative			Phone - Representative*				Email - Representative*				
Product-Env-Stewards Product			oduct Enviro Compliance			NA				Product-Env-Stewards@onsemi.com				
Requester Item Number	equester Item Number Mfr Item		n Number Mfr Item Name			Effective Date	Version Manufacturing Site		ing Site	W	eight*	UOM	Unit Type	
	15GN03	15GN03FA-TL-H BIP NPN		70mA 10V fT=1.5G		2024-04-30		(	CNG		1.8	32	mg	Each
Aanufacturing Proccess Informatio	n													
Terminal Plating / Grid Array Mater	rminal Plating / Grid Array Material Terminal Base Alloy			J-STD-020 MSI	Rating	Peak Pro	Peak Process Body Temperature Max Time at Peak Temperature Number of Reflow Cycles						eles	
contains Bi CU Alloy			1		260		С	30		seconds	3			
omments														
vel 1 - maximum time at peak temperature	during sol	ldering is 10-3	0 seconds											
or more information regarding material co	mposition	please refer to	page 3											

RoHS Material Composition Declaration				Declaration Type *	Detailed							
Directive 2015/863/EU amending RoHS Directive 2011/65/EU	(Pb), Mercury (Hg), Hexavalent Chromium (Cr6+), Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE), and Bis(2-ethylhexyl) phthalate (DEHP), Benzyl-butyl phthalate (BBP), Dibutyl phthalate (DBP), Disobutyl phthalate (DIBP).											
cadmium, hexavalentchromium, polybrominate contains a RoHS restricted substance inexcess encompass all such components. Supplier certif as of the date that Supplier completes this form Company acknowledges that Supplier may hav independently verified information provided by certification in this paragraph. If the Company a	ed biphenyls and/or polybrominated dip of an applicable quantity limit, please ir ies that it gathered the information it pro- .Supplier acknowledges that Company e relied on informationprovided by othe v others, Supplier agrees that, at a minin and the Supplier enter into a written agre pource of the Supplier's liability and the	henyl ethers (each a " ndicate below which, i ovides in this form us will rely on this certifiers in completing this num, itssuppliers have eement with respect to Company's remedies	RoHS restricted substance") in exce if any, RoHS exemption you believe ing appropriate methods to ensure if ication in determining the complian form, and that Supplier may not have e provided certifications regarding the to the identified part, the terms and co for issues that arise regarding inform	ce of its products with European Union membe	ove. If a homogeneous material within the part er level components, the declaration shall l correct to the best of its knowledge and belief, r state laws that implement the RoHS Directive. wever, in situations where Supplier has not tions are at least as comprehensive as the anty rights and/or remedies provided as part of							
RoHS Declaration * 1 - Item(s)	does not contain RoHS restricted substa	on above	Supplier Acceptance	* Accepted								
Exemption: If the declared item does not con applicable exemptions.	ntain RoHS restricted substances per	the definition above	except for defined RoHS exempti	ons, then select the corresponding response i	n the RoHS Declaration above and choose all							
Exemption List Version	EL-2011/534/EU											
Declaration Signature												
Instructions: Complete all of the required fin Requester) and click on Submit Form to have	elds on all pages of this form. Select the form returned to the Requester	he "Accepted" on th	e Supplier Acceptance drop-down	. This will display the signature area. Digital	lly sign the declaration (if required by the							
Supplier Digital Signature Ra	stislav Drska	Le										

## Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

sigma range of distribution unless	otherwise noted).							
Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Die	0.03	mg	Supplier	Silicon (Si)	7440-21-3		0.03	mg
Lead Frame	0.68	mg	Supplier	Silver (Ag)	7440-22-4		0.026	mg
			Supplier	Zinc (Zn)	7440-66-6		0.0096	mg
			Supplier	Silicon (Si)	7440-21-3		0.0019	mg
			В	Nickel (Ni)	7440-02-0		0.0186	mg
			Supplier	Copper (Cu)	7440-50-8		0.6236	mg
			Supplier	Phosphorus (P)	7723-14-0		0.0003	mg
Mold Compound-Black	1.06	mg	Supplier	Carbon Black (C)	1333-86-4		0.0053	mg
			Supplier	Aluminum Hydroxide (Al(OH)3)	21645-51-2		0.159	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		0.7155	mg
			Supplier	Ortho-Cresol Novolac Resin	29690-82-2		0.159	mg
			Supplier	Silica Crystalline (SiO2)	14808-60-7		0.0212	mg
Plating	0.04	mg	В	Bismuth (Bi)	7440-69-9		0.0002	mg
			Supplier	Tin (Sn)	7440-31-5		0.0398	mg
Wire Bond - Au	0.01	mg	Supplier	Gold (Au)	7440-57-5		0.01	mg

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).