IPC  ASSOCIATION CON ELECTRONICS IND	© Copyright 2005.	Material Composition Declaration © Copyright 2005. IPC, Bannockburn, Illinois. All rights reserved under both international and Pan-American copyright conventions.			der both le	This document is a declaration of the substances within the manufacturer listed item. Note: if the item is an assembly with lower level parts, the declaration encompasses all lower level materials for which the manufacturer has engineering responsibility.								
752-21.1		IPC Web Site for Information on IPC-1752 Standard Form Typ http://www.ipc.org/IPC-175x Distribute				* Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Mater					ials and Mfg Information			
upplier In	formation													
Company name*			Company unique ID			U	Unique ID Authority				Response Date*			
nsemi											2024-05-03			
Contact Name	2	Title - Contact			P	Phone - Contact*				Email - Contact*				
Product-Env-	-Stewards		Product Enviro Compliance			1	NA				Product-Env-Stewards@onsemi.com			
uthorized Re	epresentative*	Title - Representative			P	Phone - Representative*			Email - Representative*					
Product-Env-Stewards			Product Enviro Compliance			ı	NA				Product-Env-Stewards@onsemi.com			
Re	equester Item Number	Mfr Item	Number	Mfr Item Name			Effective Date	Version	Ma	Manufacturing Site		Veight*	UOM	Unit Type
		74LCX257MX QUAD 2-1 MUI		QUAD 2-1 MULTI	PLEXER		2024-05-03 PH4		<del></del>	1	47.797	mg	Each	
Ianufactu	ring Proccess Informa	ation									·		·	·
2 2			rminal Base Alloy J-STD-020 MSL Rating			Rating	Peak Process Body Temperature Max Time at Peak T				Temperature Number of Reflow Cycles			
Ma	tte Tin (Sn) - annealed	(	CU Alloy	1			260	C	:	30	second	ls <b>3</b>		
omments														
vel 1 - maxin	num time at peak tempera	ture during sol	dering is 10-3	30 seconds										
or more info	rmation regarding materia	l composition	please refer t	o page 3										

RoHS Material Composition Declaration			Declaration Type *	Detail	ed						
Directive 2015/863/EU amending RoHS Directive 2011/65/EU  RoHS Definition: Quantity limit of 0.01% by mass (100 PPM) in homogeneous material for Cadmium and quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury (Hg), Hexavalent Chromium (Cr6+), Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE), and Bis(2-ethylhexyl) phthalate (DEHP), Benzyl-butyl phthalate (BBP), Dibutyl phthalate (DBP), Diisobutyl phthalate (DIBP).											
Please indicate whether any homogeneous material (as defined by the RoHS Directive, EU 2011/65/EU and implemented by the laws of the European Union member states) of the part identified on this form contains lead, mercury, cadmium, hexavalentchromium, polybrominated biphenyls and/or polybrominated diphenyl ethers (each a "RoHS restricted substance") in excess of the applicable quantity limit identified above. If a homogeneous material within the part contains a RoHS restricted substance inexcess of an applicable quantity limit, please indicate below which, if any, RoHS exemption you believe may apply. If the part is an assembly with lower level components, the declaration shall encompass all such components. Supplier certifies that it gathered the information it provides in this form using appropriate methods to ensure its accuracy and that such information is true and correct to the best of its knowledge and belief, as of the date that Supplier completes this form. Supplier acknowledges that Company will rely on this certification in determining the compliance of its products with European Union member state laws that implement the RoHS Directive. Company acknowledges that Supplier may have relied on information provided by others in completing this form, and that Supplier may not have independently verified such information. However, in situations where Supplier has not independently verified information provided by others, Supplier agrees that, at a minimum, its suppliers have provided certifications regarding their contributions to the part, and those certifications are at least as comprehensive as the certification in this paragraph. If the Company and the Supplier agreement with respect to the identified part, the terms and conditions of that agreement, including any warranty rights and/or remedies provided as part of that agreement, will be the sole and exclusivesource of the Supplier's Standard Terms and Conditions of Sale applicable to such part shall apply.											
RoHS Declaration * 1 - Item	(s) does not contain RoHS restricted substar	nces per the definition above	Supplier A	cceptance *	Accepted						
Exemption: If the declared item does not contain RoHS restricted substances per the definition above except for defined RoHS exemptions, then select the corresponding response in the RoHS Declaration above and choose all applicable exemptions.											
Exemption List Version	EL-2011/534/EU										
Declaration Signature											
		e "Accepted" on the Supplier Acceptance	drop-down. This will display the signature a	rea. Digitally sign t	the declaration (if required by the						

## **Homogeneous Material Composition Declaration for Electronic Products**

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).

<b>Homogeneous Material</b>	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Die	4.35	mg	Supplier	Silicon (Si)	7440-21-3		4.35	mg
Die Attach Epoxy	0.44	mg	Supplier	Silver (Ag)	7440-22-4		0.4048	mg
			Supplier	Phenolic Resin-2	54208-63-8		0.0352	mg
Lead Frame	46.4	mg	Supplier	Silver (Ag)	7440-22-4		0.2042	mg
			Supplier	Zinc (Zn)	7440-66-6		0.0603	mg
			Supplier	Iron (Fe)	7439-89-6		1.1136	mg
			Supplier	Copper (Cu)	7440-50-8		45.0034	mg
			Supplier	Phosphorus (P)	7723-14-0		0.0186	mg
Mold Compound-Black	93.9	mg	Supplier	2,6-dibromo-4-[1-(3-bromo-4-hydroxyphenyl)-1-methylethyl]phenol	6386-73-8		0.939	mg
			Supplier	Ortho Cresol Novolac Resin	29690-82-2		27.231	mg
			В	Antimony Trioxide (Sb2O3)	1309-64-4		1.878	mg
			Supplier	Carbon Black (C)	1333-86-4		0.704	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		63.148	mg
Plating	2.31	mg	Supplier	Tin (Sn)	7440-31-5		2.31	mg
Wire Bond - Au	0.397	mg	Supplier	Gold (Au)	7440-57-5		0.397	mg