ASSOCIATION CONNECTING LECTRONICS INDUSTRIES	PC. Bannockl	burn. Illinois. A	Il rights reserved untions.	under both	This docum level parts, t	ent is a declara he declaration	ion of the s encompasse	ubstances es all lowe	within the man r level materials	ufacturer liste s for which th	ed item. No e manufact	ote: if the turer has	item is an ass engineering r	embly with lowe esponsibility.
	21.1 IPC Web Site for Information on IPC-1752 Standard For http://www.ipc.org/IPC-175x Dis				* Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Materials					Materials and	ls and Mfg Information			
Supplier Information														
Company name*	Company un	Company unique ID			Unique ID Authority					Response Date*				
onsemi						, ,					2024-05-01			
Contact Name Title - Contact			ct			Phone - Contact*					Email - Contact*			
Product-Env-Stewards Product H			et Enviro Compliance			NA				Pro	Product-Env-Stewards@onsemi.com			
Authorized Representative* Title - Re			Representative			Phone - Representative*			Ema	Email - Representative*				
Product-Env-Stewards Product E			t Enviro Compliance			NA				Pro	Product-Env-Stewards@onsemi.com			
Requester Item Number	Mfr Item Numb		umber Mfr Item Name			Effective Date Version Manufacturing S		Site	Weight*	*	UOM	Unit Type		
	EGF1D		UFR DO-214BA GPPN 1A 200V		1	2024-05-01		1	PANJITFG		67.9		mg	Each
Manufacturing Proccess Informa	tion													
Terminal Plating / Grid Array Ma	inal Plating / Grid Array Material Terminal Base .		Alloy	J-STD-020 MSL Rating		Peak Process Body Temperature		e Max Time at Peak Tempera		nperature Number of Reflow Cycles		es		
Matte Tin (Sn) - annealed CU Allo		CU Alloy	1			260	260 C 30		se	seconds 3				
Comments														
evel 1 - maximum time at peak temperatu	ire during so	ldering is 10-3	0 seconds											
or more information regarding material	composition	please refer to	page 3											

RoHS Material Composition Declar	ation			Declaration Type *	Detailed
Directive 2015/863/EU amending Rol Directive 2011/65/EU	(Pb), Mercury (Hg), Hexav		ninated Biphenyls (PBB), Polybror	dmium and quantity limit of 0.1% by mass (100 ninated Diphenyl Ethers (PBDE), and Bis(2-eth	
cadmium, hexavalentchromium, polyb contains a RoHS restricted substance i encompass all such components.Suppl as of the date that Supplier completes Company acknowledges that Supplier independently verified information pro- certification in this paragraph.If the Co	rominated biphenyls and/or polybror nexcess of an applicable quantity lim ier certifies that it gathered the inforr this form.Supplier acknowledges that may have relied on informationprovi ovided by others, Supplier agrees that ompany and the Supplier enter into a clusivesource of the Supplier's liabili	ninated diphenyl ethers (each a "R it, please indicate below which, if nation it provides in this form usin Company will rely on this certifud ded by others in completing this f , at a minimum, itssuppliers have written agreement with respect to ty and the Company's remedies for	toHS restricted substance") in exce any, RoHS exemption you believe ag appropriate methods to ensure it cation in determining the complian orm, and that Supplier may not hav provided certifications regarding th the identified part,the terms and co or issues that arise regarding inform	ropean Union member states) of the part identifies so of the applicable quantity limit identified about may apply. If the part is an assembly with lows a accuracy and that such information is true and ce of its products with European Union member re independently verified such information. How heir contributions to the part, and those certifica motions of that agreement, including any warra nation the Supplier provides in this form. In the	ove. If a homogeneous material within the part er level components, the declaration shall l correct to the best of its knowledge and belief, r state laws that implement the RoHS Directive. wever, in situations where Supplier has not tions are at least as comprehensive as the inty rights and/or remedies provided as part of
<b>RoHS Declaration *</b> 4	- Item(s) does not contain RoHS restr	icted substances per the definition	above except for selected exempti	ons Supplier Acceptance	* Accepted
Exemption: 7a: Lead in high meltin Exemption: 7c-I Electrical and elect	g temperature type solders (i.e. lead ronic components containing lead i	l based solder alloys containing n a glass or ceramic other than	85% by weight or more lead). dielectric ceramic in capacitors, o	e.g. piezoelectronic devices, or in a glass or ce	eramic matrix compound.
Exemption List Version	EL-2011/534/EU				
Declaration Signature					
Instructions: Complete all of the rec Requester) and click on Submit For			Supplier Acceptance drop-down	. This will display the signature area. Digital	ly sign the declaration (if required by the
Supplier Digital Signature	Rastislav Drska	Le			

## Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Die	0.764	mg	А	Lead (Pb)	7439-92-1	7c	0.0367	mg
			Supplier	Silicon (Si)	7440-21-3		0.7166	mg
			В	Nickel (Ni)	7440-02-0		0.0069	mg
			Supplier	Gold (Au)	7440-57-5		0.0038	mg
Die Attach Solder	2.25	mg	Supplier	Silver (Ag)	7440-22-4		0.0563	mg
			А	Lead (Pb)	7439-92-1	7a	2.0812	mg
			Supplier	Tin (Sn)	7440-31-5		0.1125	mg
Lead Frame	27.5903	mg	Supplier	Iron (Fe)	7439-89-6		0.0331	mg
			Supplier	Copper (Cu)	7440-50-8		27.5489	mg
			Supplier	Phosphorus (P)	7723-14-0		0.0083	mg
Mold Compound-Black	36.69	mg		Metal Hydroxide	proprietary data		1.2842	mg
			Supplier	Ortho Cresol Novolac Resin	29690-82-2		2.9352	mg
			Supplier	Carbon Black (C)	1333-86-4		0.1834	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		29.352	mg
			Supplier	Phenolic Resin (Novolac)	9003-35-4		2.9352	mg
Plating	0.6057	mg	Supplier	Tin (Sn)	7440-31-5		0.6057	mg