© Copy	rial Composition right 2005. IPC, Ban tional and Pan-Americ	nockburn, Illinois.	All rights reserved to nations.	under both	This docume level parts, t	ent is a declarat	ion of the su encompasse	ibstances s all lowe	within the manufacture r level materials for w	rer listed i which the r	tem. Note: i nanufacturer	f the item is an as r has engineering	ssembly with lower responsibility.	
	IPC Web Site for Information on IPC-1752 Standard Form Ty http://www.ipc.org/IPC-175x Distribut				* Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Materi				ials and M	als and Mfg Information				
Supplier Information														
Company name*	Company u	Company unique ID			Unique ID Authority				Respon	Response Date*				
onsemi									2024-05	2024-05-05				
Contact Name	Title - Conta	Title - Contact			Phone - Contact*				Email -	Email - Contact*				
Product-Env-Stewards	Product Env	Product Enviro Compliance			NA				Produc	Product-Env-Stewards@onsemi.com				
Authorized Representative* Tit			Title - Representative			Phone - Representative*			Email -	Email - Representative*				
Product-Env-Stewards Pro			Product Enviro Compliance			NA				Produc	Product-Env-Stewards@onsemi.com			
Requester Item Nur	Requester Item Number Mfr Iten		n Number Mfr Item Name			Effective Date	Version	1	Manufacturing Site		Weight*	UOM	Unit Type	
	FA	N23SV56MPX	6A 24V PoL Regulators			2024-05-05		I	РВВ		83.149	mg	Each	
Manufacturing Proccess	s Information													
Terminal Plating / Grid Array Material Terminal			se Alloy J-STD-020 MSL Rating			Peak Process Body Temperature Max Time at Peak			k Tempera	Temperature Number of Reflow Cycles				
Matte Tin (Sn) - annealed CU Alloy				1		260		С	30	secor	nds 3			
Comments														
level 1 - maximum time at pea	ak temperature duri	ng soldering is 10-	30 seconds											
For more information regardi	ing material compos	ition please refer t	o page 3											

RoHS Material Composition Declaration				Declaration Type *	Detailed						
Directive 2015/863/EU amending RoHS Directive 2011/65/EU	(Pb), Mercury (Hg), Hexavalent Chro	toHS Definition: Quantity limit of 0.01% by mass (100 PPM) in homogeneous material for Cadmium and quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead Pb), Mercury (Hg), Hexavalent Chromium (Cr6+), Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE), and Bis(2-ethylhexyl) phthalate (DEHP), Benzyl-butyl hthalate (BBP), Dibutyl phthalate (DBP), Diisobutyl phthalate (DIBP).									
cadmium, hexavalentchromium, polybromina contains a RoHS restricted substance inexces encompass all such components. Supplier cer as of the date that Supplier completes this for Company acknowledges that Supplier may h independently verified information provided certification in this paragraph. If the Company	ated biphenyls and/or polybrominated dip s of an applicable quantity limit, please in iffies that it gathered the information it pr m.Supplier acknowledges that Company ave relied on informationprovided by oth by others, Supplier agrees that, at a minir and the Supplier enter into a written agr esource of the Supplier's liability and the	henyl ethers (each a "RoHS restricted substa ndicate below which, if any, RoHS exemption ovides in this form using appropriate methoo will rely on this certification in determining ers in completing this form, and that Supplie num, itssuppliers have provided certification eement with respect to the identified part, the Company's remedies for issues that arise reg	nce") in exco n you believe ls to ensure i the compliar r may not ha s regarding t terms and co	e may apply. If the part is an assembly with low s accuracy and that such information is true an ce of its products with European Union member de independently verified such information. Ho neir contributions to the part, and those certifica	ove. If a homogeneous material within the part er level components, the declaration shall d correct to the best of its knowledge and belief, er state laws that implement the RoHS Directive. wever, in situations where Supplier has not ations are at least as comprehensive as the anty rights and/or remedies provided as part of						
RoHS Declaration * 4 - Item(s) does not contain RoHS restricted subst	ances per the definition above except for sele	ected exempt	ions Supplier Acceptance	* Accepted						
Exemption: 7a: Lead in high melting temp	erature type solders (i.e. lead based sol	der alloys containing 85% by weight or m	ore lead).								
Exemption List Version	EL-2011/534/EU										
Declaration Signature											
Instructions: Complete all of the required Requester) and click on Submit Form to h			e drop-dowi	a. This will display the signature area. Digita	lly sign the declaration (if required by the						
Supplier Digital Signature	astislav Drska	Le									

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Die	1.14	mg	Supplier	Silicon (Si)	7440-21-3		1.14	mg
Die Attach Solder	1.362	mg	Supplier	Silver (Ag)	7440-22-4		0.034	mg
			А	Lead (Pb)	7439-92-1	7a	1.2599	mg
			Supplier	Tin (Sn)	7440-31-5		0.0681	mg
Lead Frame	30.983	mg	Supplier	Silver (Ag)	7440-22-4		0.282	mg
			Supplier	Zinc (Zn)	7440-66-6		0.04	mg
			Supplier	Iron (Fe)	7439-89-6		0.744	mg
			Supplier	Copper (Cu)	7440-50-8		29.917	mg
Mold Compound-Black	46.6	mg	Supplier	4,4'-Bis(2,3-epoxypropoxy)-3,3',5,5'- tetramethylbiphenyl	85954-11-6		4.194	mg
			Supplier	Carbon Black (C)	1333-86-4		0.466	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		41.008	mg
			Supplier	Phenolic Resin (Novolac)	9003-35-4		0.932	mg
Plating	1.78	mg	Supplier	Tin (Sn)	7440-31-5		1.78	mg
Vire Bond - Au	0.684	mg	Supplier	Gold (Au)	7440-57-5		0.684	mg
Wire Bond - Cu	0.6	mg	Supplier	Palladium (Pd)	7440-05-3		0.012	mg
			Supplier	Copper (Cu)	7440-50-8		0.588	mg