© Copyrig	al Composition De ht 2005. IPC, Bannock hal and Pan-American c	burn, Illinois. A	Il rights reserved untions.	under both	This docume level parts, t	ent is a declarati he declaration e	on of the su	bstances v all lower	vithin the manufactu level materials for w	rer listed it which the m	em. Note:	if the item is an as r has engineering	sembly with low responsibility.	
	IPC Web Site for Information on IPC-1752 Standard Form Type http://www.ipc.org/IPC-175x Distribute				*	<ul> <li>Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Materi</li> </ul>					als and Mfg Information			
Supplier Information														
ompany name*	Company un	Company unique ID			Unique ID Authority				Respons	Response Date*				
nsemi									2024-04	2024-04-30				
Contact Name Title - Co			le - Contact			Phone - Contact*				Email -	Email - Contact*			
Product-Env-Stewards Pro			Product Enviro Compliance			NA				Product-Env-Stewards@onsemi.com				
Authorized Representative* Title			Title - Representative			Phone - Representative*			Email - Representative*					
Product-Env-Stewards	Product Envi	Product Enviro Compliance			NA				Product-Env-Stewards@onsemi.com					
Requester Item Numb	ester Item Number Mfr Item Num		Number Mfr Item Name			Effective Date	e Version Manufacturing Site			Weight*	UOM	Unit Type		
	FSA804	SA8049UCX Audio Jack Detect S		et Switch		2024-04-30 PBI		BB	-		mg	Each		
Ianufacturing Proccess I	nformation		1					<b>I</b>		<b>I</b>				
Terminal Plating / Grid	Terminal Plating / Grid Array Material Terminal Base A			by J-STD-020 MSL Rating Pea			Peak Process Body Temperature Max Time at Peak T			Temperature Number of Reflow Cycles				
SnAgCu CU Allog		CU Alloy	1			<b>260</b> C		С	30 seco		seconds 3			
omments														
vel 1 - maximum time at peak t	temperature during so	oldering is 10-3	0 seconds											
or more information regarding	material composition	please refer to	page 3											

RoHS Material Composition Declaration				Declaration Type *	Detailed					
Directive 2015/863/EU amending RoHS Directive 2011/65/EU	RoHS Definition: Quantity limit of 0.01% by mass (100 PPM) in homogeneous material for Cadmium and quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury (Hg), Hexavalent Chromium (Cr6+), Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE), and Bis(2-ethylhexyl) phthalate (DEHP), Benzyl-butyl phthalate (BBP), Dibutyl phthalate (DBP), Dibutyl phthalate (DIBP).									
cadmium, hexavalentchromium, polybrominate contains a RoHS restricted substance inexcess encompass all such components. Supplier certif as of the date that Supplier completes this form Company acknowledges that Supplier may hav independently verified information provided by certification in this paragraph. If the Company a	ed biphenyls and/or polybrominated dip of an applicable quantity limit, please ir ies that it gathered the information it pro- .Supplier acknowledges that Company e relied on informationprovided by othe y others, Supplier agrees that, at a minin and the Supplier enter into a written agre pource of the Supplier's liability and the	henyl ethers (each a " ndicate below which, i ovides in this form us will rely on this certifiers in completing this num, itssuppliers have eement with respect to Company's remedies	RoHS restricted substance") in exce if any, RoHS exemption you believe ing appropriate methods to ensure if ication in determining the complian form, and that Supplier may not have e provided certifications regarding the to the identified part, the terms and co for issues that arise regarding inform	ce of its products with European Union membe	ove. If a homogeneous material within the part er level components, the declaration shall l correct to the best of its knowledge and belief, r state laws that implement the RoHS Directive. wever, in situations where Supplier has not tions are at least as comprehensive as the anty rights and/or remedies provided as part of					
RoHS Declaration * 1 - Item(s)	does not contain RoHS restricted substa	ances per the definitio	on above	Supplier Acceptance	* Accepted					
Exemption: If the declared item does not contain RoHS restricted substances per the definition above except for defined RoHS exemptions, then select the corresponding response in the RoHS Declaration above and choose all applicable exemptions.										
Exemption List Version	EL-2011/534/EU									
Declaration Signature										
Instructions: Complete all of the required fin Requester) and click on Submit Form to have	elds on all pages of this form. Select the form returned to the Requester	he "Accepted" on th	e Supplier Acceptance drop-down	. This will display the signature area. Digital	lly sign the declaration (if required by the					
Supplier Digital Signature Ra	stislav Drska	Le								

## Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

sigma range of distribution unless otherwise noted).										
Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure		
Die	1.29618	mg	Supplier	Silicon (Si)	7440-21-3		1.2895	mg		
			Supplier	Aluminum (Al)	7429-90-5		0.0067	mg		
Solder Ball	0.547544	mg	Supplier	Silver (Ag)	7440-22-4		0.0309	mg		
			Supplier	Tin (Sn)	7440-31-5		0.5133	mg		
			Supplier	Copper (Cu)	7440-50-8		0.0033	mg		
Under Bump Metal	5.86E-4	mg	Supplier	Titanium (Ti)	7440-32-6		0.0001	mg		
			Supplier	Copper (Cu)	7440-50-8		0.0004	mg		

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 signar range of distribution unless otherwise noted)