ASSOCIATION CONNECTING ELECTRONICS INDUSTRIES® INDUSTRIES® INTERNATIONAL AND	IPC, Bannockt	burn, Illinois. A	Il rights reserved untions.	under both	This docume level parts, t	ent is a declara he declaration	ion of the s encompasse	ubstances es all lowe	within the manufact r level materials for	urer listed which the	item. Note: manufacture	if the item is an a er has engineering	ssembly with low responsibility.	
	IPC Web Site for Information on IPC-1752 Standard Form http://www.ipc.org/IPC-175x Distri				e * Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Mater					erials and l	ials and Mfg Information			
Supplier Information														
Company name* Com			Company unique ID			Unique ID Authority					Response Date*			
nsemi										2024-0	2024-05-05			
Contact Name Title - Contact			itact			Phone - Contact*				Email	Email - Contact*			
Product-Env-Stewards Product Env			Enviro Compliance			NA				Produ	Product-Env-Stewards@onsemi.com			
Authorized Representative* Title - Repre			resentative			Phone - Representative*			Email	Email - Representative*				
Product-Env-Stewards Product En			uct Enviro Compliance			NA				Produ	Product-Env-Stewards@onsemi.com			
Requester Item Number	quester Item Number Mfr Item I		Number Mfr Item Name			Effective Date	e Version]	Manufacturing Site		Weight*	UOM	Unit Type	
	H11N1S	M	6PW SCHM-T SMD			2024-05-05]	LITEONFG		464.903	mg	Each	
Aanufacturing Proccess Informa	ntion													
Terminal Plating / Grid Array M	erminal Plating / Grid Array Material Terminal Base A		Alloy	J-STD-020 MSL Rating		Peak Process Body Temperature Max T		re Max Time at Pea	ak Temperature Number of Reflow Cycles		cles			
Matte Tin (Sn) - annealed CU Alloy		CU Alloy		1		260 C		30	seconds					
omments														
vel 1 - maximum time at peak temperat	ure during so	ldering is 10-3	0 seconds											
or more information regarding materia	l composition	please refer to	page 3											

RoHS Material Composition Declaration				Declaration Type *	Detailed						
Directive 2015/863/EU amending RoHS Directive 2011/65/EU	RoHS Definition: Quantity limit of 0.01% by mass (100 PPM) in homogeneous material for Cadmium and quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead Pb), Mercury (Hg), Hexavalent Chromium (Cr6+), Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE), and Bis(2-ethylhexyl) phthalate (DEHP), Benzyl-butyl hthalate (BBP), Dibutyl phthalate (DBP), Diisobutyl phthalate (DIBP).										
cadmium, hexavalentchromium, polybrominate contains a RoHS restricted substance inexcess encompass all such components. Supplier certif as of the date that Supplier completes this form Company acknowledges that Supplier may hav independently verified information provided by certification in this paragraph. If the Company a	ed biphenyls and/or polybrominated dip of an applicable quantity limit, please ir ies that it gathered the information it pro- .Supplier acknowledges that Company e relied on informationprovided by othe v others, Supplier agrees that, at a minin and the Supplier enter into a written agre pource of the Supplier's liability and the	henyl ethers (each a " ndicate below which, i ovides in this form us will rely on this certifiers in completing this num, itssuppliers have eement with respect to Company's remedies	RoHS restricted substance") in exce if any, RoHS exemption you believe ing appropriate methods to ensure if ication in determining the complian form, and that Supplier may not have e provided certifications regarding the to the identified part, the terms and co for issues that arise regarding inform	ce of its products with European Union membe	ove. If a homogeneous material within the part er level components, the declaration shall l correct to the best of its knowledge and belief, r state laws that implement the RoHS Directive. wever, in situations where Supplier has not tions are at least as comprehensive as the anty rights and/or remedies provided as part of						
RoHS Declaration * 1 - Item(s)	does not contain RoHS restricted substa	on above	Supplier Acceptance	* Accepted							
Exemption: If the declared item does not con applicable exemptions.	ntain RoHS restricted substances per	the definition above	except for defined RoHS exempti	ons, then select the corresponding response i	n the RoHS Declaration above and choose all						
Exemption List Version	EL-2011/534/EU										
Declaration Signature											
Instructions: Complete all of the required fin Requester) and click on Submit Form to have	elds on all pages of this form. Select the form returned to the Requester	he "Accepted" on th	e Supplier Acceptance drop-down	. This will display the signature area. Digital	lly sign the declaration (if required by the						
Supplier Digital Signature Ra	stislav Drska	Le									

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Coupling Gel	0.4	mg	Supplier	Dimethyl Cyclosiloxanes	69430-24-6		0.04	mg
			Supplier	Trimethoxy(methyl)silane (C4H12O3Si)	1185-55-3		0.36	mg
Die	5.13	mg	Supplier	Silicon (Si)	7440-21-3		5.13	mg
Die Attach	0.3	mg	Supplier	Silver (Ag)	7440-22-4		0.225	mg
			Supplier	Phenolic Resin-2	54208-63-8		0.075	mg
Lead Frame	101.703	mg	Supplier	Silver (Ag)	7440-22-4		0.407	mg
			Supplier	Zinc (Zn)	7440-66-6		0.203	mg
			Supplier	Iron (Fe)	7439-89-6		2.64	mg
			Supplier	Copper (Cu)	7440-50-8		98.3	mg
			Supplier	Phosphorus (P)	7723-14-0		0.153	mg
Mold Compound-White	327.22	mg	Supplier	Titanium Dioxide (TiO2)	13463-67-7		81.805	mg
			В	Brominated Bisphenol A Diglycidyl Ether	40039-93-8		9.8166	mg
			Supplier	Ortho Cresol Novolac Resin	29690-82-2		44.1747	mg
			В	Antimony Trioxide (Sb2O3)	1309-64-4		9.8166	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		163.61	mg
			Supplier	Phenolic Resin (Novolac)	9003-35-4		17.9971	mg
Plating	28.5	mg	Supplier	Tin (Sn)	7440-31-5		28.5	mg
Wire Bond - Au	1.65	mg	Supplier	Gold (Au)	7440-57-5		1.65	mg