ABSOCIATION CONNECTING ELECTRONICS INDUSTRIES® International and Pan	C. Bannockl	burn. Illinois. A	ll rights reserved untions.	under both	This docume level parts, t	ent is a declara he declaration	tion of the s encompasse	ubstances s all lowe	within the r r level mate	manufacture rials for wh	er listed iten hich the man	n. Note: if ufacturer	f the item is an as has engineering	sembly with lowe responsibility.
	IPC Web Site for Information on IPC-1752 Standard Form T http://www.ipc.org/IPC-175x Distrib				*	* Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Materi					als and Mfg Information			
Supplier Information														
Company name* Cor			Company unique ID			Unique ID Authority					Response Date*			
nsemi											2024-05-04			
ontact Name Title - Contact			ct	Phone - Con			tact* F			Email - Contact*				
Product-Env-Stewards Product Ex			Enviro Compliance			NA				Product-Env-Stewards@onsemi.com				
Authorized Representative* Title - Representati			ntative		Phone - Representative*				Email - Representative*					
Product-Env-Stewards Product			roduct Enviro Compliance			NA				Product-Env-Stewards@onsemi.com				
Requester Item Number	uester Item Number Mfr Item N		Number Mfr Item Name			Effective Dat	e Version	rsion Manufacturing Site		ng Site	We	ight*	UOM	Unit Type
	MC74H G	C74HCT4052ADR2 IC MUX/DEMUX		X DUAL 4X1		2024-05-04]	PH4		142	2.68	mg	Each
Manufacturing Proccess Informat	ion													
Terminal Plating / Grid Array Ma	erial Terminal Base Alloy		Alloy	J-STD-020 MSI	ASL Rating Pea		k Process Body Temperature Max Time at Peak		ne at Peak T	Temperature Number of Reflow Cycles		les		
Matte Tin (Sn) - annealed CU Alloy			1		260		С	30		seconds	3			
Comments														
evel 1 - maximum time at peak temperatu	re during so	ldering is 10-3	0 seconds											
or more information regarding material (composition	please refer to	page 3											

RoHS Material Composition Declaration				Declaration Type *	Detailed						
Directive 2015/863/EU amending RoHS Directive 2011/65/EU	RoHS Definition: Quantity limit of 0.01% by mass (100 PPM) in homogeneous material for Cadmium and quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury (Hg), Hexavalent Chromium (Cr6+), Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE), and Bis(2-ethylhexyl) phthalate (DEHP), Benzyl-butyl phthalate (BBP), Dibutyl phthalate (DBP), Disobutyl phthalate (DIBP).										
cadmium, hexavalentchromium, polybrominate contains a RoHS restricted substance inexcess encompass all such components. Supplier certif as of the date that Supplier completes this form Company acknowledges that Supplier may hav independently verified information provided by certification in this paragraph. If the Company a	ed biphenyls and/or polybrominated dip of an applicable quantity limit, please ir ies that it gathered the information it pro- .Supplier acknowledges that Company e relied on informationprovided by othe v others, Supplier agrees that, at a minin and the Supplier enter into a written agre pource of the Supplier's liability and the	henyl ethers (each a " ndicate below which, i ovides in this form us will rely on this certifiers in completing this num, itssuppliers have eement with respect to Company's remedies	RoHS restricted substance") in exce if any, RoHS exemption you believe ing appropriate methods to ensure if ication in determining the complian form, and that Supplier may not have e provided certifications regarding the to the identified part, the terms and cc for issues that arise regarding inform	ce of its products with European Union membe	ove. If a homogeneous material within the part er level components, the declaration shall l correct to the best of its knowledge and belief, r state laws that implement the RoHS Directive. wever, in situations where Supplier has not tions are at least as comprehensive as the anty rights and/or remedies provided as part of						
RoHS Declaration * 1 - Item(s)	does not contain RoHS restricted substa	ances per the definitio	on above	Supplier Acceptance	* Accepted						
Exemption: If the declared item does not con applicable exemptions.	ntain RoHS restricted substances per	the definition above	except for defined RoHS exempti	ons, then select the corresponding response i	n the RoHS Declaration above and choose all						
Exemption List Version	EL-2011/534/EU										
Declaration Signature											
Instructions: Complete all of the required fin Requester) and click on Submit Form to have	elds on all pages of this form. Select the form returned to the Requester	he "Accepted" on th	e Supplier Acceptance drop-down	. This will display the signature area. Digital	lly sign the declaration (if required by the						
Supplier Digital Signature Ra	stislav Drska	Le									

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

select a ROHS exemption, if appli sigma range of distribution unless	otherwise noted).	it of the substance of the Pl	PM concentration	[F] Optionally enter the positive (+) and n	legative (-) tolerance in per	cent (Note: percer	it tolerance values are	expected to cover a 3
Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Die	2.73	mg	Supplier	Silicon (Si)	7440-21-3		2.73	mg
Die Attach	4.85	mg	Supplier	Silver (Ag)	7440-22-4		3.6375	mg
			Supplier	Epoxy resins	129915-35-1		1.2125	mg
Lead Frame	75.92	mg	Supplier	Silver (Ag)	7440-22-4		0.7592	mg
			Supplier	Zinc (Zn)	7440-66-6		0.1518	mg
			Supplier	Iron (Fe)	7439-89-6		1.9739	mg
			Supplier	Copper (Cu)	7440-50-8		73.035	mg
Mold Compound-Black	55.11	mg		Epoxy resin	proprietary data		2.7555	mg
			Supplier	Phenolic Resin	Proprietary Data		2.7555	mg
			Supplier	Ortho Cresol Novolac Resin	29690-82-2		1.1022	mg
			Supplier	Carbon Black (C)	1333-86-4		0.2756	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		48.2213	mg
Plating	3.73	mg	Supplier	Tin (Sn)	7440-31-5		3.73	mg
Wire Bond - Cu	0.34	mg	Supplier	Copper (Cu)	7440-50-8		0.34	mg