© Copy	rial Compositi right 2005. IPC, B ional and Pan-Am	Bannockbi	urn, Illinois. A	ll rights reserved untions.	under both	This docume level parts, t	ent is a decla he declaratio	ration of the second	the substances passes all low	s within th er level m	ne manufactur aterials for wl	er listed ite hich the m	em. Not anufactu	te: if the i urer has e	tem is an asse	mbly with lower sponsibility.
	IPC Web Site for Information on IPC-1752 Standard Form Type http://www.ipc.org/IPC-175x Distribute				e *	Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Mater					als and Mfg Information					
Supplier Information																
Company name*			Company unique ID			Unique ID Authority					Response Date*					
onsemi												2024-05-03				
Contact Name			Title - Contact				Phone - Contact*					Email - Contact*				
Product-Env-Stewards			Product Enviro Compliance			NA					Product-Env-Stewards@onsemi.com					
Authorized Representative*			Title - Representative			Phone - Representative*				Email - Representative*						
Product-Env-Stewards			Product Enviro Compliance				NA				Product-Env-Stewards@onsemi.com					
Requester Item Nur	uester Item Number Mfr Item			Number Mfr Item Name			Effective D	ate Ver	rsion	Manufacturing Site		v	Veight*	l	UOM	Unit Type
	MC74LCX158DTG		LOG CMOS LOW VOLTAGE		2024-05-03	;		PH1		4	5.4	1	ng	Each		
Manufacturing Proccess	s Information			<u>.</u>			·									
Terminal Plating / G	Terminal Plating / Grid Array Material		erminal Base A	minal Base Alloy J-ST		L Rating	Peak P	Peak Process Body Temperatu		ure Max Time at Peak Ter		Temperatu	emperature Number of		Reflow Cycle	s
Precious metal (e.g. Ag,Au, NiPdAu) (no Sn)) (no C	U Alloy 1		1		260		С	30 sec		second	econds 3			
Comments																
evel 1 - maximum time at pea	ık temperature dı	uring sole	dering is 10-3	0 seconds												
For more information regardi	ing material comp	position p	please refer to	page 3												

RoHS Material Composition Declaration				Declaration Type *	Detailed
Directive 2015/863/EU amending RoHS Directive 2011/65/EU		nium (Cr6+), Polybro	ominated Biphenyls (PBB), Polybron	dmium and quantity limit of 0.1% by mass (100 minated Diphenyl Ethers (PBDE), and Bis(2-eth	
cadmium, hexavalentchromium, polybrominate contains a RoHS restricted substance inexcess encompass all such components. Supplier certif as of the date that Supplier completes this form Company acknowledges that Supplier may hav independently verified information provided by certification in this paragraph. If the Company a	ed biphenyls and/or polybrominated dip of an applicable quantity limit, please ir ies that it gathered the information it pro- .Supplier acknowledges that Company e relied on informationprovided by othe v others, Supplier agrees that, at a minin and the Supplier enter into a written agre pource of the Supplier's liability and the	henyl ethers (each a " ndicate below which, i ovides in this form us will rely on this certifiers in completing this num, itssuppliers have eement with respect to Company's remedies	RoHS restricted substance") in exce if any, RoHS exemption you believe ing appropriate methods to ensure if ication in determining the complian form, and that Supplier may not have e provided certifications regarding the to the identified part, the terms and co for issues that arise regarding inform	ce of its products with European Union membe	ove. If a homogeneous material within the part er level components, the declaration shall l correct to the best of its knowledge and belief, r state laws that implement the RoHS Directive. wever, in situations where Supplier has not tions are at least as comprehensive as the anty rights and/or remedies provided as part of
RoHS Declaration * 1 - Item(s)	does not contain RoHS restricted substa	ances per the definitio	on above	Supplier Acceptance	* Accepted
Exemption: If the declared item does not con applicable exemptions.	ntain RoHS restricted substances per	the definition above	except for defined RoHS exempti	ons, then select the corresponding response i	n the RoHS Declaration above and choose all
Exemption List Version	EL-2011/534/EU				
Declaration Signature					
Instructions: Complete all of the required fin Requester) and click on Submit Form to have	elds on all pages of this form. Select the form returned to the Requester	he "Accepted" on th	e Supplier Acceptance drop-down	. This will display the signature area. Digital	lly sign the declaration (if required by the
Supplier Digital Signature Ra	stislav Drska	Le			

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

sigma range of distribution unless otherwise noted).									
Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure	
Die	2.0	mg	Supplier	Silicon (Si)	7440-21-3		2	mg	
Die Attach	1.32	mg		Epoxy resin	proprietary data		0.132	mg	
			Supplier	Silver (Ag)	7440-22-4		1.056	mg	
			Supplier	Formaldehyde Polymer	9003-36-5		0.132	mg	
Lead Frame	20.76	mg	Supplier	Iron (Fe)	7439-89-6		0.3944	mg	
			Supplier	Copper (Cu)	7440-50-8		20.3656	mg	
Mold Compound-Black	19.0	mg		Epoxy resin	proprietary data		0.95	mg	
			Supplier	Phenolic Resin	Proprietary Data		0.38	mg	
			Supplier	Ortho Cresol Novolac Resin	29690-82-2		0.475	mg	
			Supplier	Carbon Black (C)	1333-86-4		0.095	mg	
			Supplier	Fused Silica (SiO2)	60676-86-0		17.1	mg	
Plating	2.12	mg	Supplier	Palladium (Pd)	7440-05-3		0.1611	mg	
			В	Nickel (Ni)	7440-02-0		1.9292	mg	
			Supplier	Gold (Au)	7440-57-5		0.0297	mg	
Wire Bond - Au	0.2	mg	Supplier	Gold (Au)	7440-57-5		0.2	mg	

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).