© C	terial Composit opyright 2005. IPC, I national and Pan-Am	Bannockb	urn, Illinois. A	ll rights reserved utions.	under both	This docume level parts, t	ent is a declarat	ion of the su encompasse	ubstances v s all lower	within the manufactu level materials for v	urer listed i which the r	tem. Note: nanufacture	if the item is an as r has engineering	ssembly with low responsibility.	
					Form Type Distribute	e *	 Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Materi 				rials and N	als and Mfg Information			
Supplier Information	L														
Company name* Co			Company uni	Company unique ID			Unique ID Authority				Respon	Response Date*			
onsemi											2024-05	2024-05-10			
Contact Name 7			Title - Contact				Phone - Contact*				Email -	Email - Contact*			
Product-Env-Stewards			Product Enviro Compliance				NA				Produc	Product-Env-Stewards@onsemi.com			
Authorized Representative* Ti			Title - Representative			Phone - Representative*				Email -	Email - Representative*				
Product-Env-Stewards			Product Enviro Compliance				NA				Produ	Product-Env-Stewards@onsemi.com			
Requester Item	ster Item Number Mfr Item		n Number Mfr Item Name				Effective Date Version Manufacturing Site		Ianufacturing Site		Weight*	UOM	Unit Type		
		MC7805ABD2TR4G		ANA 1A 5V VREG			2024-05-10		N	MY1		909.21	mg	Each	
Ianufacturing Proce	ess Information	I													
Terminal Plating / Grid Array Material Termina		erminal Base A	Base Alloy J-STD-020 MSL Ratir		L Rating	Peak Process Body Temperature		Max Time at Peak Tempera		ture Num	ber of Reflow Cy	cles			
Matte Tin (Sn) - annealed C		J Alloy 1			260	260 C		30	secon	nds 3					
omments															
vel 1 - maximum time at	peak temperature d	uring sol	dering is 10-3	0 seconds											
or more information rega	rding material com	position j	please refer to	page 3											

RoHS Material Composition Declaration				Declaration Type *	Detailed						
Directive 2015/863/EU amending RoHS Directive 2011/65/EU	RoHS Definition: Quantity limit of 0.01% by mass (100 PPM) in homogeneous material for Cadmium and quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury (Hg), Hexavalent Chromium (Cr6+), Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE), and Bis(2-ethylhexyl) phthalate (DEHP), Benzyl-butyl phthalate (BBP), Dibutyl phthalate (DBP), Disobutyl phthalate (DIBP).										
cadmium, hexavalentchromium, polybromina contains a RoHS restricted substance inexces encompass all such components. Supplier cer as of the date that Supplier completes this for Company acknowledges that Supplier may h independently verified information provided certification in this paragraph. If the Company	ated biphenyls and/or polybrominated dip s of an applicable quantity limit, please in iffies that it gathered the information it pr m.Supplier acknowledges that Company ave relied on informationprovided by oth by others, Supplier agrees that, at a minir and the Supplier enter into a written agr esource of the Supplier's liability and the	henyl ethers (each a "RoHS restricted substa ndicate below which, if any, RoHS exemption ovides in this form using appropriate methoo will rely on this certification in determining ers in completing this form, and that Supplie num, itssuppliers have provided certification eement with respect to the identified part, the Company's remedies for issues that arise reg	nce") in exco n you believe ls to ensure i the compliar r may not ha s regarding t terms and co	e may apply. If the part is an assembly with low s accuracy and that such information is true an ce of its products with European Union member de independently verified such information. Ho neir contributions to the part, and those certifica	ove. If a homogeneous material within the part er level components, the declaration shall d correct to the best of its knowledge and belief, er state laws that implement the RoHS Directive. wever, in situations where Supplier has not ations are at least as comprehensive as the anty rights and/or remedies provided as part of						
RoHS Declaration * 4 - Item(s) does not contain RoHS restricted subst	ances per the definition above except for sele	ected exempt	ions Supplier Acceptance	* Accepted						
Exemption: 7a: Lead in high melting temp	erature type solders (i.e. lead based sol	der alloys containing 85% by weight or m	ore lead).								
Exemption List Version	EL-2011/534/EU										
Declaration Signature											
Instructions: Complete all of the required Requester) and click on Submit Form to h			e drop-dowi	a. This will display the signature area. Digita	lly sign the declaration (if required by the						
Supplier Digital Signature	astislav Drska	Le									

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Die	0.19	mg	Supplier	Silicon (Si)	7440-21-3		0.19	mg
Die Attach	11.31	mg	А	Lead (Pb)	7439-92-1	7a	10.7445	mg
			Supplier	Tin (Sn)	7440-31-5		0.5655	mg
Lead Frame	340.51	mg	В	Nickel (Ni)	7440-02-0		1.0215	mg
			Supplier	Copper (Cu)	7440-50-8		339.4885	mg
Mold Compound-Black	529.31	mg		Epoxy resin	proprietary data		26.4655	mg
			Supplier	Phenolic Resin	Proprietary Data		26.4655	mg
			Supplier	Ortho Cresol Novolac Resin	29690-82-2		10.5862	mg
			Supplier	Carbon Black (C)	1333-86-4		2.6465	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		463.1462	mg
Plating	27.15	mg	Supplier	Tin (Sn)	7440-31-5		27.15	mg
Wire Bond - Cu	0.74	mg	Supplier	Copper (Cu)	7440-50-8		0.74	mg

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 signar range of distribution unless otherwise noted)