IPC ASSOCIATION CO	© Copyright 2005.	Material Composition Declaration © Copyright 2005. IPC, Bannockburn, Illinois. All rights reserved under both international and Pan-American copyright conventions.			der both le	This document is a declaration of the substances within the manufacturer listed item. Note: if the item is an assembly with lower level parts, the declaration encompasses all lower level materials for which the manufacturer has engineering responsibility.									
752-21.1		IPC Web Site for Information on IPC-1752 Standard Form Typ http://www.ipc.org/IPC-175x Distribute				* Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Mater					ials and Mfg Information				
upplier Ir	nformation														
Company name*			Company un	Company unique ID			Unique ID Authority					Response Date*			
nsemi											2024-04-29				
Contact Nam	e	Title - Contact			P	Phone - Contact*				Email - Contact*					
Product-Env	y-Stewards		Product Enviro Compliance			1	NA				Product-Env-Stewards@onsemi.com				
uthorized R	Representative*	Title - Representative			P	Phone - Representative*			Email - Representative*						
Product-Env	-Stewards	Product Enviro Compliance			1	NA				Product-Env-Stewards@onsemi.com					
Ro	equester Item Number	Mfr Item	Number	Mfr Item Name			Effective Date	Version	N	Manufacturing Site		Veight*	UOM	Unit Type	
		NB3H83905CMNG 1.8V/2.5V/3.3 V		1.8V/2.5V/3.3 V BI	UFFER		2024-04-29 MY1		IY1	3	9.39	mg	Each		
Ianufactu	uring Proccess Inform	ation									·			·	
Terminal Plating / Grid Array Material Ter			erminal Base Alloy J-STD-020 MSL Ra		Rating				e Max Time at Peak	k Temperature Number of Reflow Cycles					
Ma	atte Tin (Sn) - annealed	(CU Alloy	1			260		C	30	second	ls 3			
omments															
vel 1 - maxi	mum time at peak tempera	ture during sol	ldering is 10-3	30 seconds											
or more info	ormation regarding materia	al composition	please refer to	page 3											

RoHS Material Composition Declaration			Declaration Type *	Detail	ed						
Directive 2015/863/EU amending RoHS Directive 2011/65/EU RoHS Definition: Quantity limit of 0.01% by mass (100 PPM) in homogeneous material for Cadmium and quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury (Hg), Hexavalent Chromium (Cr6+), Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE), and Bis(2-ethylhexyl) phthalate (DEHP), Benzyl-butyl phthalate (BBP), Dibutyl phthalate (DBP), Diisobutyl phthalate (DIBP).											
cadmium, hexavalentchromium, polybromin contains a RoHS restricted substance inexce encompass all such components. Supplier cet as of the date that Supplier completes this Company acknowledges that Supplier may hindependently verified information provided certification in this paragraph. If the Compan	nated biphenyls and/or polybrominated diphess of an applicable quantity limit, please indriffes that it gathered the information it provom. Supplier acknowledges that Company wave relied on informationprovided by others of the supplier agrees that, at a minimusy and the Supplier enter into a written agree yesource of the Supplier's liability and the C	enyl ethers (each a "RoHS restricted substan licate below which, if any, RoHS exemption vides in this form using appropriate methods vill rely on this certification in determining the s in completing this form, and that Supplier um, itssuppliers have provided certifications ement with respect to the identified part, the tompany's remedies for issues that arise rega	s of the European Union member states) of the ce") in excess of the applicable quantity limit is you believe may apply. If the part is an assemb to ensure its accuracy and that such informatio e compliance of its products with European Ur may not have independently verified such infor regarding their contributions to the part, and the erms and conditions of that agreement, including information the Supplier provides in this	dentified above. If a ally with lower level in is true and correct tion member state la mation. However, in ose certifications are ag any warranty righ	homogeneous material within the part components, the declaration shall to the best of its knowledge and belief, was that implement the RoHS Directive. In situations where Supplier has not the at least as comprehensive as the lats and/or remedies provided as part of						
RoHS Declaration * 1 - Item	(s) does not contain RoHS restricted substar	nces per the definition above	Supplier A	cceptance *	Accepted						
Exemption: If the declared item does not contain RoHS restricted substances per the definition above except for defined RoHS exemptions, then select the corresponding response in the RoHS Declaration above and choose all applicable exemptions.											
Exemption List Version	EL-2011/534/EU										
Declaration Signature											
		e "Accepted" on the Supplier Acceptance	drop-down. This will display the signature a	rea. Digitally sign t	the declaration (if required by the						

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).

Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Die	2.73	mg	Supplier	Silicon (Si)	7440-21-3		2.73	mg
Die Attach	0.26	mg		Resin	proprietary data		0.0208	mg
			Supplier	Silver (Ag)	7440-22-4		0.2197	mg
			Supplier	Formaldehyde Polymer	9003-36-5		0.0195	mg
Lead Frame	18.25	mg	Supplier	Tin (Sn)	7440-31-5		0.0456	mg
			Supplier	Zinc (Zn)	7440-66-6		0.0402	mg
			Supplier	Chromium (Cr)	7440-47-3		0.0456	mg
			Supplier	Copper (Cu)	7440-50-8		18.1186	mg
Lead Frame plating	0.2	mg	Supplier	Silver (Ag)	7440-22-4		0.2	mg
Mold Compound-Black	17.47	mg	Supplier	Epoxy and Phenolic Resin	40216-08-8		1.3976	mg
			Supplier	Carbon Black (C)	1333-86-4		0.0873	mg
			Supplier	Aluminum Hydroxide (Al(OH)3)	21645-51-2		0.3494	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		15.1115	mg
			Supplier	Phenolic Resin (Novolac)	9003-35-4		0.5241	mg
Plating	0.26	mg	Supplier	Tin (Sn)	7440-31-5		0.26	mg
Wire Bond - Au	0.22	mg	Supplier	Gold (Au)	7440-57-5		0.22	mg