000	aterial Composit Copyright 2005. IPC, H rnational and Pan-Am	Bannockbu	irn, Illinois. A	ll rights reserved utions.	under both	This docume level parts, t	ent is a decla he declaratio	aration of the second s	of the substa ompasses all	ances w lower	within the relevel mate	nanufactur rials for w	er listed i hich the n	tem. N nanufao	ote: if th cturer ha	e item is an as s engineering	sembly with lowe responsibility.
					Form Type Distribute	 Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Mate 					ous Materi	ials and Mfg Information					
Supplier Information	1																
Company name*			Company unique ID			1	Unique ID Authority						Response Date*				
onsemi										2024-05-11							
Contact Name			Title - Contact]	Phone - Contact*					Email - Contact*					
Product-Env-Stewards			Product Enviro Compliance				NA					Product-Env-Stewards@onsemi.com					
Authorized Representative*			Title - Representative]	Phone - Representative*					Email - Representative*					
Product-Env-Stewards			Product Enviro Compliance				NA					Product-Env-Stewards@onsemi.com					
Requester Item	Requester Item Number Mfr Item N NCP103AN		n Number Mfr Item Name				Effective D	Date V	Version	M	Manufacturing Site		Weight*		t*	UOM	Unit Type
			MX250TCG	IX250TCG 150 mA CMOS Low Dropout Regulator, Vout=2.5V, Act discharge			2024-05-11 MY1			1.74			mg	Each			
Manufacturing Proc	cess Information																
Terminal Plating / Grid Array Material		1 Te	rminal Base Alloy J-STD-02		J-STD-020 MSI	L Rating	Peak P	Process Body Temperature Max Time at 1		ne at Peak	ak Temperature Nu		Number o	of Reflow Cyc	les		
Precious metal (e.g. Ag,Au, NiPdAu) (no Sn)) (no C	CU Alloy 1		1		260	C			30		seconds 3		3		
Comments																	
evel 1 - maximum time at	peak temperature d	uring solo	lering is 10-3	0 seconds													
or more information reg	arding material com	position p	lease refer to	page 3													

RoHS Material Composition Declaration				Declaration Type *	Detailed
Directive 2015/863/EU amending RoHS Directive 2011/65/EU		nium (Cr6+), Polybro	ominated Biphenyls (PBB), Polybron	dmium and quantity limit of 0.1% by mass (100 minated Diphenyl Ethers (PBDE), and Bis(2-eth	
cadmium, hexavalentchromium, polybrominate contains a RoHS restricted substance inexcess encompass all such components. Supplier certif as of the date that Supplier completes this form Company acknowledges that Supplier may hav independently verified information provided by certification in this paragraph. If the Company a	ed biphenyls and/or polybrominated dip of an applicable quantity limit, please ir ies that it gathered the information it pro- .Supplier acknowledges that Company e relied on informationprovided by othe y others, Supplier agrees that, at a minin and the Supplier enter into a written agre pource of the Supplier's liability and the	henyl ethers (each a " ndicate below which, i ovides in this form us will rely on this certifiers in completing this num, itssuppliers have eement with respect to Company's remedies	RoHS restricted substance") in exce if any, RoHS exemption you believe ing appropriate methods to ensure if ication in determining the complian form, and that Supplier may not have e provided certifications regarding the to the identified part, the terms and cc for issues that arise regarding inform	ce of its products with European Union membe	ove. If a homogeneous material within the part er level components, the declaration shall l correct to the best of its knowledge and belief, r state laws that implement the RoHS Directive. wever, in situations where Supplier has not tions are at least as comprehensive as the anty rights and/or remedies provided as part of
RoHS Declaration * 1 - Item(s)	does not contain RoHS restricted substa	ances per the definitio	on above	Supplier Acceptance	* Accepted
Exemption: If the declared item does not con applicable exemptions.	ntain RoHS restricted substances per	the definition above	except for defined RoHS exempti	ons, then select the corresponding response i	n the RoHS Declaration above and choose all
Exemption List Version	EL-2011/534/EU				
Declaration Signature					
Instructions: Complete all of the required fin Requester) and click on Submit Form to have	elds on all pages of this form. Select the form returned to the Requester	he "Accepted" on th	e Supplier Acceptance drop-down	. This will display the signature area. Digital	lly sign the declaration (if required by the
Supplier Digital Signature Ra	stislav Drska	Le			

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Die	0.06	mg	Supplier	Silicon (Si)	7440-21-3		0.06	mg
Die Attach	0.02	mg	Supplier	Silver (Ag)	7440-22-4		0.015	mg
			Supplier	Epoxy resins	129915-35-1		0.005	mg
Lead Frame	0.76	mg	Supplier	Tin (Sn)	7440-31-5		0.0019	mg
			Supplier	Zinc (Zn)	7440-66-6		0.0017	mg
			Supplier	Chromium (Cr)	7440-47-3		0.0019	mg
			Supplier	Copper (Cu)	7440-50-8		0.7545	mg
Mold Compound-Black	0.87	mg	Supplier	Epoxy and Phenolic Resin	40216-08-8		0.0696	mg
			Supplier	Carbon Black (C)	1333-86-4		0.0044	mg
			Supplier	Aluminum Hydroxide (Al(OH)3)	21645-51-2		0.0174	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		0.7526	mg
			Supplier	Phenolic Resin (Novolac)	9003-35-4		0.0261	mg
Plating	0.01	mg	Supplier	Palladium (Pd)	7440-05-3		0.0002	mg
			В	Nickel (Ni)	7440-02-0		0.0088	mg
			Supplier	Gold (Au)	7440-57-5		0.001	mg
Vire Bond - Au	0.02	mg	Supplier	Gold (Au)	7440-57-5		0.02	mg

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).