ABSOCIATION CONNECTING ELECTROMICS INDUSTRIES® INDUSTRIES®	PC, Bannockt	urn, Illinois. A	Ill rights reserved untions.	under both leve	is docume el parts, tl	ent is a declaration e	on of the su	ibstances s all lowe	within the manufactu r level materials for w	rer listed	item. Note: nanufacture	if the item is an as r has engineering	sembly with lower responsibility.	
				Form Type * Distribute					ials and Mfg Information					
Supplier Information														
Company name* Co			Company unique ID			Unique ID Authority					Response Date*			
onsemi										2024-05-18				
Contact Name Title - Cont			Contact			Phone - Contact*				Email -	Email - Contact*			
Product-Env-Stewards Product E			duct Enviro Compliance			NA				Product-Env-Stewards@onsemi.com				
Authorized Representative* Title - Representative			presentative		1	Phone - Representative*			Email - Representative*					
Product-Env-Stewards Produ			Product Enviro Compliance			NA				Product-Env-Stewards@onsemi.com				
Requester Item Number	Requester Item Number Mfr Item I		Number Mfr Item Name			Effective Date	Version	N	Manufacturing Site		Weight*	UOM	Unit Type	
	NCP812	NCP81241MNTXG Industrial Te		perature range Single Phase		2024-05-18		F	PH1		45.91	mg	Each	
Manufacturing Proccess Informa	tion					-		·						
Terminal Plating / Grid Array Ma	Terminal Plating / Grid Array Material Terminal Base A		Alloy	J-STD-020 MSL Ra	ating	Peak Proc	ess Body Te	emperatu	re Max Time at Peak	Tempera	ture Num	ber of Reflow Cyc	eles	
Matte Tin (Sn) - annealed CU Alloy			1		260		С	30	secon	nds 3				
Comments														
level 1 - maximum time at peak temperatu	re during so	dering is 10-3	0 seconds											
For more information regarding material	composition	please refer to	page 3											

RoHS Material Composition Declaration				Declaration Type *	Detailed						
Directive 2015/863/EU amending RoHS Directive 2011/65/EU	RoHS Definition: Quantity limit of 0.01% by mass (100 PPM) in homogeneous material for Cadmium and quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury (Hg), Hexavalent Chromium (Cr6+), Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE), and Bis(2-ethylhexyl) phthalate (DEHP), Benzyl-butyl phthalate (BBP), Dibutyl phthalate (DBP), Diisobutyl phthalate (DIBP).										
cadmium, hexavalentchromium, polybrominate contains a RoHS restricted substance inexcess encompass all such components. Supplier certif as of the date that Supplier completes this form Company acknowledges that Supplier may hav independently verified information provided by certification in this paragraph. If the Company a	ed biphenyls and/or polybrominated dip of an applicable quantity limit, please ir ies that it gathered the information it pro- .Supplier acknowledges that Company e relied on informationprovided by othe y others, Supplier agrees that, at a minin and the Supplier enter into a written agre pource of the Supplier's liability and the	henyl ethers (each a " ndicate below which, i ovides in this form us will rely on this certifiers in completing this num, itssuppliers have eement with respect to Company's remedies	RoHS restricted substance") in exce if any, RoHS exemption you believe ing appropriate methods to ensure if ication in determining the complian form, and that Supplier may not have e provided certifications regarding the to the identified part, the terms and cc for issues that arise regarding inform	ce of its products with European Union membe	ove. If a homogeneous material within the part er level components, the declaration shall l correct to the best of its knowledge and belief, r state laws that implement the RoHS Directive. wever, in situations where Supplier has not tions are at least as comprehensive as the anty rights and/or remedies provided as part of						
RoHS Declaration * 1 - Item(s)	does not contain RoHS restricted substa	ances per the definitio	on above	Supplier Acceptance	* Accepted						
Exemption: If the declared item does not con applicable exemptions.	ntain RoHS restricted substances per	the definition above	except for defined RoHS exempti	ons, then select the corresponding response i	n the RoHS Declaration above and choose all						
Exemption List Version	EL-2011/534/EU										
Declaration Signature											
Instructions: Complete all of the required fin Requester) and click on Submit Form to have	elds on all pages of this form. Select the form returned to the Requester	he "Accepted" on th	e Supplier Acceptance drop-down	. This will display the signature area. Digital	lly sign the declaration (if required by the						
Supplier Digital Signature Ra	stislav Drska	Le									

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure	
Die	3.28	mg	Supplier	Silicon (Si)	7440-21-3		3.28	mg	
Die Attach	0.6	mg	Supplier	Epoxized Condensate Of Para- Hydrobenzaldehyde And Alkyl Phenol	129915-35-1		0.12	mg	
			Supplier	Silver (Ag)	7440-22-4		0.48	mg	
Lead Frame	17.25	mg	Supplier	Silver (Ag)	7440-22-4		0.345	mg	
			Supplier	Iron (Fe)	7439-89-6		0.3795	mg	
			Supplier	Copper (Cu)	7440-50-8		16.5255	mg	
Mold Compound-Black	22.31	mg		Epoxy Phenol Resin	proprietary data		2.3425	mg	
			Supplier	Fused Silica (SiO2)	60676-86-0		19.9674	mg	
Plating	2.2	mg	Supplier	Tin (Sn)	7440-31-5		2.2	mg	
Wire Bond - Cu	0.27	mg	Supplier	Copper (Cu)	7440-50-8		0.27	mg	

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 signa range of distribution unless otherwise noted)