ASSOCIATION CONNECTING	Material Composit © Copyright 2005. IPC, international and Pan-An	Bannockb	urn, Illinois. A	ll rights reserved utions.	under both	This docum level parts, t	ent is a declar the declaratio	ation of the n encompass	substances ses all lowe	s within the er level mat	manufacture erials for wh	er listed ite hich the ma	m. Note: i nufacture	f the item is an a r has engineering	ssembly with lower responsibility.	
1752-21.1					Form Type Distribute	*	Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Mater					ials and Mfg Information				
Supplier Informa	ation				· ·											
Company name*			Company unique ID			Unique ID Authority					Response Date*					
onsemi										2024-05-06						
Contact Name			Title - Contact			Phone - Contact*				Email - Contact*						
Product-Env-Stewards			Product Enviro Compliance				NA					Product-Env-Stewards@onsemi.com				
Authorized Representative*			Title - Representative			Phone - Representative*				Email - Representative*						
Product-Env-Stewards			Product Enviro Compliance			NA				Product-Env-Stewards@onsemi.com						
Requester	ester Item Number Mfr Item		n Number Mfr Item Name				Effective Da	te Version	n	Manufacturing Site CN1		W	eight*	UOM	Unit Type	
		G Regul		Ultra-Low IQ 150 mA CMOS LDO Regulator, High Ohmic State, Vout=3.6V, automotive		2024-05-06			2.			79	mg	Each		
Manufacturing P	Proccess Information	1														
Terminal Plating / Grid Array Material Te			erminal Base Alloy J-STD-020 MSI		Rating	Peak Pi	Peak Process Body Temperature		ire Max Ti	me at Peak '	k Temperature N		per of Reflow Cy	cles		
Matte Tin (Sn) - annealed CU Al			U Alloy	1			260 C 30			seconds 3						
Comments																
evel 1 - maximum tir	me at peak temperature d	luring sol	dering is 10-3	0 seconds												
or more information	n regarding material com	position]	please refer to	page 3												

RoHS Material Composition Declaration				Declaration Type *	Detailed
Directive 2015/863/EU amending RoHS Directive 2011/65/EU		nium (Cr6+), Polybro	ominated Biphenyls (PBB), Polybron	dmium and quantity limit of 0.1% by mass (100 minated Diphenyl Ethers (PBDE), and Bis(2-eth	
cadmium, hexavalentchromium, polybrominate contains a RoHS restricted substance inexcess encompass all such components. Supplier certif as of the date that Supplier completes this form Company acknowledges that Supplier may hav independently verified information provided by certification in this paragraph. If the Company a	ed biphenyls and/or polybrominated dip of an applicable quantity limit, please ir ies that it gathered the information it pro- .Supplier acknowledges that Company e relied on informationprovided by othe y others, Supplier agrees that, at a minin and the Supplier enter into a written agre pource of the Supplier's liability and the	henyl ethers (each a " ndicate below which, i ovides in this form us will rely on this certifiers in completing this num, itssuppliers have eement with respect to Company's remedies	RoHS restricted substance") in exce if any, RoHS exemption you believe ing appropriate methods to ensure if ication in determining the complian form, and that Supplier may not have e provided certifications regarding the to the identified part, the terms and co for issues that arise regarding inform	ce of its products with European Union membe	ove. If a homogeneous material within the part er level components, the declaration shall l correct to the best of its knowledge and belief, r state laws that implement the RoHS Directive. wever, in situations where Supplier has not tions are at least as comprehensive as the anty rights and/or remedies provided as part of
RoHS Declaration * 1 - Item(s)	does not contain RoHS restricted substa	on above	Supplier Acceptance	* Accepted	
Exemption: If the declared item does not con applicable exemptions.	ntain RoHS restricted substances per	the definition above	except for defined RoHS exempti	ons, then select the corresponding response i	n the RoHS Declaration above and choose all
Exemption List Version	EL-2011/534/EU				
Declaration Signature					
Instructions: Complete all of the required fin Requester) and click on Submit Form to have	elds on all pages of this form. Select the form returned to the Requester	he "Accepted" on th	e Supplier Acceptance drop-down	. This will display the signature area. Digital	lly sign the declaration (if required by the
Supplier Digital Signature Ra	stislav Drska	Le			

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

sigma range of distribution unless otherwise noted).										
Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure		
Die	0.12	mg	Supplier	Silicon (Si)	7440-21-3		0.12	mg		
Lead Frame	1.18	mg	В	Nickel (Ni)	7440-02-0		0.4283	mg		
			Supplier	Iron (Fe)	7439-89-6		0.5924	mg		
			Supplier	Copper (Cu)	7440-50-8		0.1593	mg		
Mold Compound-Black	1.4	mg	Supplier	Boron zinc hydroxide oxide	138265-88-0		0.042	mg		
			Supplier	Zinc Monoxide (ZnO)	1314-13-2		0.007	mg		
			Supplier	2,4,6-triamino-s-triazincompd.withs- triazine-triol	37640-57-6		0.042	mg		
			Supplier	Silica Amorphous (SiO2)	7631-86-9		1.12	mg		
			Supplier	Carbon Black (C)	1333-86-4		0.014	mg		
			Supplier	Ortho-Cresol Novolac Resin	29690-82-2		0.112	mg		
			Supplier	Phenolic Resin (Novolac)	9003-35-4		0.063	mg		
Plating	0.06	mg	Supplier	Tin (Sn)	7440-31-5		0.06	mg		
Wire Bond - Au	0.03	mg	Supplier	Gold (Au)	7440-57-5		0.03	mg		

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 signa range of distribution unless otherwise noted).