IPC ASSOCIATION COI	© Copyright 2005.	Material Composition Declaration © Copyright 2005. IPC, Bannockburn, Illinois. All rights reserved under both international and Pan-American copyright conventions.			der both	This document is a declaration of the substances within the manufacturer listed item. Note: if the item is an assembly with lowe level parts, the declaration encompasses all lower level materials for which the manufacturer has engineering responsibility.									
752-21.1		IPC Web Site for Information on IPC-1752 Standard Form Typ http://www.ipc.org/IPC-175x Distribute				* Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Materi					laterials ar	ials and Mfc Information			
upplier Ir	nformation									,		<u> </u>			
Company name* Compan			Company uni	mpany unique ID			Unique ID Authority					Response Date*			
nsemi											202	2024-05-16			
Contact Name	e	Title - Contact			I	Phone - Contact*				Em	Email - Contact*				
Product-Env	-Stewards	Product Enviro Compliance				NA				Pro	Product-Env-Stewards@onsemi.com				
uthorized R	Representative*	Title - Representative			I	Phone - Representative*				Em	Email - Representative*				
Product-Env	y-Stewards	Product Enviro Compliance				NA				Pro	Product-Env-Stewards@onsemi.com				
Re	equester Item Number	Mfr Item	Number	Mfr Item Name			Effective Date	e Vers	Version Manufacturing Site		te	Weight*	UOM	Unit Type	
		NCV890130MWTXG 2 MHz Switch		2 MHz Switcher	r		2024-05-16			24.73		mg	Each		
Ianufactu	uring Proccess Informa	ation						·		_					
Terminal Plating / Grid Array Material Terminal Base Alloy			Alloy J-S	STD-020 MSL	SL Rating Peak Process Body Temperature Max Time at Peak Temperature						perature Numl	er of Reflow Cy	cles		
Matte Tin (Sn) - annealed C		CU Alloy 1				<b>260</b> C		C	30	s	econds 3				
omments															
vel 1 - maxi	mum time at peak temperat	ture during sol	dering is 10-3	0 seconds											
or more info	ormation regarding materia	l composition	please refer to	page 3											

RoHS Material Composition Declaration			Declaration Type *	Detail	ed						
Directive 2015/863/EU amending RoHS Directive 2011/65/EU  RoHS Definition: Quantity limit of 0.01% by mass (100 PPM) in homogeneous material for Cadmium and quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury (Hg), Hexavalent Chromium (Cr6+), Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE), and Bis(2-ethylhexyl) phthalate (DBP), Dibutyl phthalate (DBP), Dibutyl phthalate (DBP).											
Please indicate whether any homogeneous material (as defined by the RoHS Directive, EU 2011/65/EU and implemented by the laws of the European Union member states) of the part identified on this form contains lead, mercury, cadmium, hexavalentchromium, polybrominated biphenyls and/or polybrominated diphenyl ethers (each a "RoHS restricted substance") in excess of the applicable quantity limit identified above. If a homogeneous material within the part contains a RoHS restricted substance inexcess of an applicable quantity limit, please indicate below which, if any, RoHS exemption you believe may apply. If the part is an assembly with lower level components, the declaration shall encompass all such components. Supplier certifies that it gathered the information it provides in this form using appropriate methods to ensure its accuracy and that such information is true and correct to the best of its knowledge and belief, as of the date that Supplier completes this form. Supplier acknowledges that Company will rely on this certification in determining the compliance of its products with European Union member state laws that implement the RoHS Directive. Company acknowledges that Supplier may have relied on information provided by others in completing this form, and that Supplier may not have independently verified such information. However, in situations where Supplier has not independently verified information provided by others, Supplier agrees that, at a minimum, its uppliers have provided certifications regarding their contributions to the part, and those certifications are at least as comprehensive as the certification in this paragraph. If the Company and the Supplier have provided as part of that agreement, will be the sole and exclusivesource of the Supplier's liability and the Company's remedies for issues that arise regarding information the Supplier provides in this form. In the absence of such written agreement, the warranty rights and/or remedies of Supplier's Standard Terms and Conditions of Sale appli											
RoHS Declaration * 1 - Item	(s) does not contain RoHS restricted substar	nces per the definition above	Supplier A	cceptance *	Accepted						
Exemption: If the declared item does not contain RoHS restricted substances per the definition above except for defined RoHS exemptions, then select the corresponding response in the RoHS Declaration above and choose all applicable exemptions.											
Exemption List Version	EL-2011/534/EU										
Declaration Signature											
		e "Accepted" on the Supplier Acceptance	drop-down. This will display the signature a	rea. Digitally sign t	the declaration (if required by the						

## **Homogeneous Material Composition Declaration for Electronic Products**

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).

Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Die	1.68	mg	Supplier	Silicon (Si)	7440-21-3		1.68	mg
Die Attach	0.34	mg	Supplier	Silver (Ag)	7440-22-4		0.255	mg
			Supplier	Epoxy resins	129915-35-1		0.085	mg
Lead Frame	8.6	mg	Supplier	Silver (Ag)	7440-22-4		0.0662	mg
			Supplier	Tin (Sn)	7440-31-5		0.0215	mg
			Supplier	Zinc (Zn)	7440-66-6		0.0189	mg
			Supplier	Chromium (Cr)	7440-47-3		0.0215	mg
			Supplier	Copper (Cu)	7440-50-8		8.4719	mg
Mold Compound-Black	13.61	mg		Epoxy resin	proprietary data		0.9527	mg
			Supplier	Phenolic Resin	Proprietary Data		0.9527	mg
			Supplier	Silica Amorphous (SiO2)	7631-86-9		2.0415	mg
			Supplier	Carbon Black (C)	1333-86-4		0.068	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		9.595	mg
Plating	0.33	mg	Supplier	Tin (Sn)	7440-31-5		0.33	mg
Wire Bond - Au	0.17	mg	Supplier	Gold (Au)	7440-57-5		0.17	mg