ASSOCIATION CONNECTING	Material Composit © Copyright 2005. IPC, international and Pan-Ar	Bannockb	urn, Illinois. A	ll rights reserved utions.	under both	This docum level parts, t	ent is a declarat he declaration e	ion of the su encompasse	ubstances v s all lower	within the manufacture level materials for v	urer listed i which the r	tem. Note: nanufacture	if the item is an as er has engineering	sembly with low responsibility.	
752-21.1					Form Type Distribute	*	* Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Materi					als and Mfg Information			
Supplier Informa	ation														
Company name*			Company unique ID				Unique ID Authority				Respon	Response Date*			
onsemi											2024-05	2024-05-20			
Contact Name			Title - Contact				Phone - Contact*				Email -	Email - Contact*			
Product-Env-Stewards			Product Enviro Compliance				NA				Produc	Product-Env-Stewards@onsemi.com			
Authorized Representative*			Title - Representative				Phone - Representative*				Email -	Email - Representative*			
Product-Env-Stewards			Product Enviro Compliance				NA				Produc	Product-Env-Stewards@onsemi.com			
Requester	Requester Item Number Mfr Item		n Number Mfr Item Name				Effective Date	e Version Manufacturing Site			Weight*	UOM	Unit Type		
		NRVB8H	NRVB8H100MFST1G 8.0 A, 100 V Scho		ottky Diode in S	e in SO-8FL 2024-05			N	MY1		113.069	mg	Each	
Ianufacturing P	Proccess Information	n													
Terminal Plating / Grid Array Material Termin			erminal Base A	ninal Base Alloy J-STD-020 MSL Ra		L Rating	Peak Process Body Temperature Max Time at Po			e Max Time at Peal	ak Temperature Number of Reflow Cycles				
Matte Tin (Sn) - annealed CU			CU Alloy	lloy 1			260 C 30		30	seconds 3					
omments															
vel 1 - maximum tir	me at peak temperature o	luring sol	dering is 10-30) seconds											
or more information	n regarding material con	position	please refer to	page 3											

RoHS Material Composition Declaration				Declaration Type *	Detailed				
Directive 2015/863/EU amending RoHS Directive 2011/65/EU		mium (Cr6+), Polybrominated Biphenyls (Pl		dmium and quantity limit of 0.1% by mass (10 minated Diphenyl Ethers (PBDE), and Bis(2-et					
cadmium, hexavalentchromium, polybromina contains a RoHS restricted substance inexces encompass all such components. Supplier cer as of the date that Supplier completes this for Company acknowledges that Supplier may h independently verified information provided certification in this paragraph. If the Company	ated biphenyls and/or polybrominated dip s of an applicable quantity limit, please in iffies that it gathered the information it pr m.Supplier acknowledges that Company ave relied on informationprovided by oth by others, Supplier agrees that, at a minir and the Supplier enter into a written agr esource of the Supplier's liability and the	henyl ethers (each a "RoHS restricted substa ndicate below which, if any, RoHS exemption ovides in this form using appropriate methoo will rely on this certification in determining ers in completing this form, and that Supplie num, itssuppliers have provided certification eement with respect to the identified part, the Company's remedies for issues that arise reg	nce") in exco n you believe ls to ensure i the compliar r may not ha s regarding t terms and co	e may apply. If the part is an assembly with low s accuracy and that such information is true an ce of its products with European Union member de independently verified such information. Ho neir contributions to the part, and those certifica	ove. If a homogeneous material within the part er level components, the declaration shall d correct to the best of its knowledge and belief, er state laws that implement the RoHS Directive. wever, in situations where Supplier has not ations are at least as comprehensive as the anty rights and/or remedies provided as part of				
RoHS Declaration * 4 - Item(s) does not contain RoHS restricted subst	ances per the definition above except for sele	ected exempt	ions Supplier Acceptance	* Accepted				
Exemption: 7a: Lead in high melting temperature type solders (i.e. lead based solder alloys containing 85% by weight or more lead).									
Exemption List Version	EL-2011/534/EU								
Declaration Signature									
Instructions: Complete all of the required fields on all pages of this form. Select the "Accepted" on the Supplier Acceptance drop-down. This will display the signature area. Digitally sign the declaration (if required by the Requester) and click on Submit Form to have the form returned to the Requester.									
Supplier Digital Signature	astislav Drska	Le							

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

sigma range of distribution unless	ouler wise noted).							
Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Clip	4.8	mg	Supplier	Zinc (Zn)	7440-66-6		0.0058	mg
			Supplier	Iron (Fe)	7439-89-6		0.1128	mg
			Supplier	Copper (Cu)	7440-50-8		4.68	mg
			Supplier	Phosphorus (P)	7723-14-0		0.0014	mg
Die	0.713	mg	Supplier	Silicon (Si)	7440-21-3		0.713	mg
Die Attach Solder	11.9	mg	Supplier	Silver (Ag)	7440-22-4		0.2975	mg
			А	Lead (Pb)	7439-92-1	7a	11.0075	mg
			Supplier	Tin (Sn)	7440-31-5		0.595	mg
Lead Frame	47.57	mg	Supplier	Silver (Ag)	7440-22-4		0.0285	mg
			Supplier	Iron (Fe)	7439-89-6		0.0476	mg
			Supplier	Copper (Cu)	7440-50-8		47.4796	mg
			Supplier	Phosphorus (P)	7723-14-0		0.0143	mg
Mold Compound-Black	47.136	mg		Epoxy resin	proprietary data		3.5352	mg
			Supplier	Phenolic Resin	Proprietary Data		1.1784	mg
			Supplier	Silica Amorphous (SiO2)	7631-86-9		3.5352	mg
			Supplier	Carbon Black (C)	1333-86-4		0.2357	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		38.6515	mg
Plating	0.95	mg	Supplier	Tin (Sn)	7440-31-5		0.95	mg

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).