ASDICIATION CONNECTING ELECTRONICS INDUSTRIES® INCLUSTRIES	. Bannockb	urn. Illinois. A	ll rights reserved untions.	under both	This docume level parts, t	ent is a declara	tion of the sencompass	substances es all low	within the er level ma	e manufacture terials for wh	er listed ite hich the ma	m. Note	: if the item is an a rer has engineering	assembly with low g responsibility.
				Form Type Distribute	*	Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Materials and Mfg I					g Inform	ation		
Supplier Information														
Company name* Comp			ompany unique ID			Unique ID Authority					Response Date*			
onsemi											2024-05-21			
ttact Name Title - Contact						Phone - Contact*					Email - Contact*			
Product-Env-Stewards Product Enviro			iro Compliance			NA				Product-Env-Stewards@onsemi.com				
Authorized Representative* Title - Represe			esentative			Phone - Representative*				Email - Representative*				
Product-Env-Stewards Product E			ct Enviro Compliance			NA				Product-Env-Stewards@onsemi.com				
Requester Item Number	Mfr Item Number		umber Mfr Item Name			Effective Dat	e Versior	ı	Manufacturing Site		W	eight*	UOM	Unit Type
	SZSMF0	SZSMF05CT1G MI SC88 Z/R PN		TA ARRAY TH	TA ARRAY TR 2				MY1		6.	2	mg	Each
Manufacturing Process Information	n													
Terminal Plating / Grid Array Mate	y Material Terminal Base Alloy J-S			J-STD-020 MSI	L Rating	Peak Process Body Temperature Max Time at Pea			'ime at Peak '	k Temperature Number of Reflow Cycles				
Matte Tin (Sn) - annealed CU Alloy			1		260		С	30		second	s 3			
omments														
vel 1 - maximum time at peak temperature	during sol	dering is 10-3	0 seconds											
or more information regarding material co	mposition	please refer to	page 3											

RoHS Material Composition Declaration				Declaration Type *	Detailed							
Directive 2015/863/EU amending RoHS Directive 2011/65/EU	(Pb), Mercury (Hg), Hexavalent Chromium (Cr6+), Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE), and Bis(2-ethylhexyl) phthalate (DEHP), Benzyl-butyl phthalate (BBP), Dibutyl phthalate (DBP), Dibutyl phthalate (DIBP).											
cadmium, hexavalentchromium, polybrominate contains a RoHS restricted substance inexcess encompass all such components. Supplier certif as of the date that Supplier completes this form Company acknowledges that Supplier may hav independently verified information provided by certification in this paragraph. If the Company a	ed biphenyls and/or polybrominated dip of an applicable quantity limit, please ir ies that it gathered the information it pro- .Supplier acknowledges that Company e relied on informationprovided by othe y others, Supplier agrees that, at a minin and the Supplier enter into a written agre pource of the Supplier's liability and the	henyl ethers (each a " ndicate below which, i ovides in this form us will rely on this certifiers in completing this num, itssuppliers have eement with respect to Company's remedies	RoHS restricted substance") in exce if any, RoHS exemption you believe ing appropriate methods to ensure if ication in determining the complian form, and that Supplier may not have e provided certifications regarding the to the identified part, the terms and cc for issues that arise regarding inform	ce of its products with European Union membe	ove. If a homogeneous material within the part er level components, the declaration shall l correct to the best of its knowledge and belief, r state laws that implement the RoHS Directive. wever, in situations where Supplier has not tions are at least as comprehensive as the anty rights and/or remedies provided as part of							
RoHS Declaration * 1 - Item(s)	does not contain RoHS restricted substa	ances per the definitio	on above	Supplier Acceptance	* Accepted							
Exemption: If the declared item does not con applicable exemptions.	ntain RoHS restricted substances per	the definition above	except for defined RoHS exempti	ons, then select the corresponding response i	n the RoHS Declaration above and choose all							
Exemption List Version	EL-2011/534/EU											
Declaration Signature												
Instructions: Complete all of the required fin Requester) and click on Submit Form to have	elds on all pages of this form. Select the form returned to the Requester	he "Accepted" on th	e Supplier Acceptance drop-down	. This will display the signature area. Digital	lly sign the declaration (if required by the							
Supplier Digital Signature Ra	stislav Drska	Le										

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

sigma range of distribution unless otherwise noted).										
Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure		
Die	0.19	mg	Supplier	Silicon (Si)	7440-21-3		0.19	mg		
Die Attach	0.12	mg	Supplier	Silver (Ag)	7440-22-4		0.09	mg		
			Supplier	Epoxy resins	129915-35-1		0.03	mg		
Lead Frame	1.92	mg	Supplier	Silver (Ag)	7440-22-4		0.0154	mg		
			Supplier	Zinc (Zn)	7440-66-6		0.0019	mg		
			Supplier	Iron (Fe)	7439-89-6		0.0499	mg		
			Supplier	Copper (Cu)	7440-50-8		1.8528	mg		
Mold Compound-Black	3.9	mg		Epoxy resin	proprietary data		0.195	mg		
			Supplier	Phenolic Resin	Proprietary Data		0.195	mg		
			Supplier	Ortho Cresol Novolac Resin	29690-82-2		0.078	mg		
			Supplier	Carbon Black (C)	1333-86-4		0.0195	mg		
			Supplier	Fused Silica (SiO2)	60676-86-0		3.4125	mg		
Plating	0.05	mg	Supplier	Tin (Sn)	7440-31-5		0.05	mg		
Wire Bond - Au	0.02	mg	Supplier	Gold (Au)	7440-57-5		0.02	mg		

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3