



## Product Overview

### 1SMC22A: Zener Transient Voltage Suppressor, 1500 Watt Peak Power

For complete documentation, see the data sheet

#### Product Description

The SMC series is designed to protect voltage sensitive components from high voltage, high energy transients. They have excellent clamping capability, high surge capability, low zener impedance and fast response time. The SMC series is supplied in ON Semiconductor's exclusive, cost-effective, highly reliable Surmetic® package and is ideally suited for use in communication systems, automotive, numerical controls, process controls, medical equipment, business machines, power supplies and many other industrial/consumer applications.

#### Features

- Standard Zener Breakdown Voltage Range - 6.8 to 91 V
- Stand-off Voltage Range - 5 to 78 V
- Peak Power - 1500 Watts @ 1 ms
- Maximum Clamp Voltage @ Peak Pulse Current
- Low Leakage < 5  $\mu$ A Above 10 V
- UL Recognition
- Maximum Temperature Coefficient Specified
- Available in Tape and Reel
- Response Time Typically < 1 ns
- CASE: Void-free, transfer-molded, thermosetting plastic

#### Part Electrical Specifications

Product	Compliance	Status	Dir	$V_{(BR)}$ Typ (V)	$P_{PK}$ Max (W)	$V_{RWM}$ Max (V)	$I_R$ Max (uA)	$V_C$ Max (V)	Package Type
1SMC22AT3G	AEC Qualified Pb-free Halide free	Active	Unidirectional	25.65	1500	22	5	35.5	SMC-2
SZ1SMC22AT3G	AEC Qualified PPAP Capable Pb-free Halide free	Active	Unidirectional	25.65	1500	22	5	35.5	SMC-2

For more information please contact your local sales support at [www.onsemi.com](http://www.onsemi.com)

Created on: 7/11/2015