



Product Overview

BC856BL: PNP Bipolar Transistor

For complete documentation, see the data sheet

Product Description

The PNP Bipolar Transistor is designed for use in linear and switching applications. The device is housed in the SOT-23 package, which is designed for lower power surface mount applications.

Features

- Pb-Free Packages are Available
- S and NSV Prefix for Automotive and Other Applications Requiring Unique Site and Control Change Requirements; AEC-Q101 Qualified and PPAP Capable

Part Electrical Specifications

Product	Compliance	Status	Polarity	I_C Continuous (A)	$V_{(BR)CEO}$ Min (V)	h_{FE} Min	h_{FE} Max	f_T Min (MHz)	P_{TM} Max (W)	Package Type
BC856BLT1G	AEC Qualified Pb-free Halide free	NEW	PNP	0.1	65	220	475	100	0.225	SOT-23-3
BC856BLT3G	AEC Qualified Pb-free Halide free	Active	PNP	0.1	65	220	475	100	0.225	SOT-23-3
SBC856BLT1G	AEC Qualified PPAP Capable Pb-free Halide free	Active	PNP	0.1	65	220	475	100	0.225	SOT-23-3
SBC856BLT3G	AEC Qualified PPAP Capable Pb-free Halide free	Active	PNP	0.1	65	220	475	100	0.225	SOT-23-3

For more information please contact your local sales support at www.onsemi.com

Created on: 7/11/2015