



## Product Overview

### MBRD620CT: Schottky Barrier Rectifier, 20 V, 6.0 A

For complete documentation, see the data sheet

#### Product Description

The Schottky Rectifier is designed for use in switching power supplies, inverters and as free wheeling diodes.

#### Features

- Extremely Fast Switching
- Extremely Low Forward Drop
- Platinum Barrier with Avalanche Guardrings

Mechanical Characteristics:

- Case: Epoxy, Molded
- Weight: 0.4 gram (approximately)
- Finish: All External Surfaces Corrosion Resistant and Terminal Leads are Readily Solderable
- Lead and Mounting Surface Temperature for Soldering Purposes: 260 °C Max. for 10 Seconds
- Shipped 75 units per plastic tube
- Available in 16 mm Tape and Reel, 2500 units per reel, by adding a "T4" suffix to the part number
- Marking: B620T, B630T, B640T, B650T, B660T

#### Part Electrical Specifications

Product	Compliance	Status	Configuration	$V_{RRM}$ Min (V)	$V_F$ Max (V)	$I_{RM}$ Max (uA)	$I_{O(rec)}$ Max (A)	$I_{FSM}$ Max (A)	$t_{rr}$ Max (ns)	$C_j$ Max (pF)	Package Type
MBRD620CTT4G	Pb-free Halide free	Active	Common Cathode	20	0.9	100	6	75			DPAK-3

For more information please contact your local sales support at [www.onsemi.com](http://www.onsemi.com)

Created on: 7/11/2015