



## Product Overview

### NSS12200L: Low $V_{CE(sat)}$ Transistor, PNP, 12 V, 4.0 A

For complete documentation, see the data sheet

#### Product Description

Low  $V_{CE(sat)}$  Bipolar Transistors are miniature surface mount devices featuring ultra low saturation voltage  $V_{CE(sat)}$  and high current gain capability. These are designed for use in low voltage, high speed switching applications where affordable efficient energy control is important.

#### Features

- High Current, Low  $V_{CE(sat)}$ , ESD Robust, High Current Gain, High Cut Off Frequency, Low Profile Package, Linear Gain (Beta)

#### Benefits

- Improved Circuit Efficiency, Decreased Battery Charge Time, Reduce component count, High Frequency Switching, Smaller Portable Product, No distortion

#### Applications

- Load Switching, Battery Charging, External Pass Transistor, DC/DC Converter, Complimentary Driver, Current Extension & Low Drop Out Regulation, Cathode Florescent Lamp drive, Peripheral Driver - LEDs, Motors, Relays

#### End Products

- Automotive

#### Part Electrical Specifications

Product	Compliance	Status	Polarity	$I_C$ Continuous (A)	$V_{BR}/V_{CEO}$ Min (V)	$V_{CE(sat)}$ Max (V)	$h_{FE}$ Min	$h_{FE}$ Max	$f_T$ Min (MHz)	$P_{TM}$ Max (W)	Package Type
NSS12200LT1G	AEC Qualified Pb-free Halide free	Active	PNP	2	12	0.09	250	-	100	0.71	SOT-23-3

For more information please contact your local sales support at [www.onsemi.com](http://www.onsemi.com)

Created on: 7/11/2015