



Product Overview

NTSV3080CTG: Schottky Power Rectifier, Dual, 30 A, 80 V

For complete documentation, see the data sheet

Product Description

The NTSV3080CTG is our new Dual 30A 80V Very Low Forward Voltage Trench-based Dual Schottky Rectifier. This new technology allows lower forward voltage drop without the high reverse leakage tradeoff experienced with planar schottky rectifiers. This platform also provides very stable switching characteristics over a wide temperature range and is an ideal output rectifier for switching power supplies including Notebook and Netbook Adapters, ATX and Flat Panel.

Features

- Fine Lithography Trenchbased Schottky Technology for Very Low Forward Voltage and Low Leakage
- Fast Switching with Exceptional Temperature Stability
- Low Power Loss and Lower Operating Temperature
- Higher Efficiency for Achieving Regulatory Compliance
- Low Thermal Resistance
- High Surge Capability
- These Devices are PbFree, Halogen Free/BFR Free and are RoHS Compliant

Applications

- Switching Power Supplies including Notebook / Netbook Adapters, ATX and Flat Panel Display
- High Frequency and DCDC Converters
- Freewheeling and ORing diodes
- Reverse Battery Protection
- Instrumentation

Part Electrical Specifications

Product	Compliance	Status	Configurat ion	V_{RRM} Min (V)	V_F Max (V)	I_{RM} Max (uA)	$I_{O(rec)}$ Max (A)	I_{FSM} Max (A)	t_r Max (ns)	C_j Max (pF)	Package Type
NTSV3080CTG	Pb-free Halide free	Active	Common Cathode	80	1.05	700	30	100			TO-220-3

For more information please contact your local sales support at www.onsemi.com

Created on: 7/11/2015