NTGS3441, NVGS3441

Power MOSFET

1 Amp, 20 Volts, P−Channel TSOP−6

ON Semiconductor®

http://onsemi.com

1 AMPERE
20 VOLTS
$R_{DS(on)}$ = 90 mΩ

Features

- Ultra Low $R_{DS(on)}$
- Higher Efficiency Extending Battery Life
- Miniature TSOP−6 Surface Mount Package
- NV Prefix for Automotive and Other Applications Requiring Unique Site and Control Change Requirements; AEC−Q101 Qualified and PPAP Capable
- These Devices are Pb−Free and are RoHS Compliant

Applications

- Power Management in Portable and Battery−Powered Products, i.e.: Cellular and Cordless Telephones, and PCMCIA Cards

P−Channel



MAXIMUM RATINGS (T_J = 25°C unless otherwise noted)

Rating	Symbol	Value	Unit
Drain−to−Source Voltage	V_{DSS}	−20	V
Gate−to−Source Voltage − Continuous	V_{GS}	±8.0	V
Thermal Resistance Junction−to−Ambient (Note 1) Total Power Dissipation @ T_A = 25°C Drain Current − Continuous @ T_A = 25°C − Pulsed Drain Current (T_p < 10 μS)	 $R_{\theta JA}$ P_d I_D I_{DM}	 244 0.5 −1.65 −10	 °C/W W A A
Thermal Resistance Junction−to−Ambient (Note 2) Total Power Dissipation @ T_A = 25°C Drain Current − Continuous @ T_A = 25°C − Pulsed Drain Current (T_p < 10 μS)	 $R_{\theta JA}$ P_d I_D I_{DM}	 128 1.0 −2.35 −14	 °C/W W A A
Thermal Resistance Junction−to−Ambient (Note 3) Total Power Dissipation @ T_A = 25°C Drain Current − Continuous @ T_A = 25°C − Pulsed Drain Current (T_p < 10 μS)	 $R_{\theta JA}$ P_d I_D I_{DM}	 62.5 2.0 −3.3 −20	 °C/W W A A
Operating and Storage Temperature Range	T_J, T_{stg}	−55 to 150	°C
Maximum Lead Temperature for Soldering Purposes for 10 Seconds	T_L	260	°C

Stresses exceeding Maximum Ratings may damage the device. Maximum Ratings are stress ratings only. Functional operation above the Recommended Operating Conditions is not implied. Extended exposure to stresses above the Recommended Operating Conditions may affect device reliability.

1. Minimum FR−4 or G−10 PCB, operating to steady state.
2. Mounted onto a 2″ square FR−4 board (1 in sq, 2 oz. Cu. 0.06″ thick single sided), operating to steady state.
3. Mounted onto a 2″ square FR−4 board (1 in sq, 2 oz. Cu. 0.06″ thick single sided), t < 5.0 seconds.

MARKING DIAGRAM & PIN ASSIGNMENT

TSOP−6
CASE 318G
STYLE 1



PT = Specific Device Code
M = Date Code*
▪ = Pb−Free Package

(Note: Microdot may be in either location)

*Date Code orientation may vary depending upon manufacturing location.

ORDERING INFORMATION

Device	Package	Shipping†
NTGS3441T1G	TSOP−6 (Pb−Free)	3000 / Tape & Reel
NVGS3441T1G	TSOP−6 (Pb−Free)	3000 / Tape& Reel

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

© Semiconductor Components Industries, LLC, 2012

October, 2012 − Rev. 6

Publication Order Number:
NTGS3441T1/D

ELECTRICAL CHARACTERISTICS (T_A = 25°C unless otherwise noted) (Notes 4 & 5)

Characteristic		Symbol	Min	Typ	Max	Unit
OFF CHARACTERISTICS						
Drain−Source Breakdown Voltage (V_{GS} = 0 Vdc, I_D = −10 μA)		$V_{(BR)DSS}$	−20	–	–	Vdc
Zero Gate Voltage Drain Current (V_{GS} = 0 Vdc, V_{DS} = −20 Vdc, T_J = 25°C) (V_{GS} = 0 Vdc, V_{DS} = −20 Vdc, T_J = 70°C)		I_{DSS}	– –	– –	−1.0 −5.0	μAdc
Gate−Body Leakage Current (V_{GS} = −8.0 Vdc, V_{DS} = 0 Vdc)		I_{GSS}	–	–	−100	nAdc
Gate−Body Leakage Current (V_{GS} = +8.0 Vdc, V_{DS} = 0 Vdc)		I_{GSS}	–	–	100	nAdc
ON CHARACTERISTICS						
Gate Threshold Voltage (V_{DS} = V_{GS}, I_D = −250 μAdc)		$V_{GS(th)}$	−0.45	−1.05	−1.50	Vdc
Static Drain−Source On−State Resistance (V_{GS} = −4.5 Vdc, I_D = −3.3 Adc) (V_{GS} = −2.5 Vdc, I_D = −2.9 Adc)		$R_{DS(on)}$	– –	0.069 0.117	0.090 0.135	Ω
Forward Transconductance (V_{DS} = −10 Vdc, I_D = −3.3 Adc)		g_{FS}	–	6.8	–	Mhos
DYNAMIC CHARACTERISTICS						
Input Capacitance	(V_{DS} = −5.0 Vdc, V_{GS} = 0 Vdc, f = 1.0 MHz)	C_{iss}	–	480	–	pF
Output Capacitance		C_{oss}	–	265	–	pF
Reverse Transfer Capacitance		C_{rss}	–	100	–	pF
SWITCHING CHARACTERISTICS						
Turn−On Delay Time	(V_{DD} = −20 Vdc, I_D = −1.6 Adc, V_{GS} = −4.5 Vdc, R_g = 6.0 Ω)	$t_{d(on)}$	–	13	25	ns
Rise Time		t_r	–	23.5	45	ns
Turn−Off Delay Time		$t_{d(off)}$	–	27	50	ns
Fall Time		t_f	–	24	45	ns
Total Gate Charge	(V_{DS} = −10 Vdc, V_{GS} = −4.5 Vdc, I_D = −3.3 Adc)	Q_{tot}	–	6.2	14	nC
Gate−Source Charge		Q_{gs}	–	1.3	–	nC
Gate−Drain Charge		Q_{gd}	–	2.5	–	nC
BODY−DRAIN DIODE RATINGS						
Diode Forward On−Voltage	(I_S = −1.6 Adc, V_{GS} = 0 Vdc)	V_{SD}	–	−0.88	−1.2	Vdc
Diode Forward On−Voltage	(I_S = −3.3 Adc, V_{GS} = 0 Vdc)	V_{SD}	–	−0.98	–	Vdc
Reverse Recovery Time	(I_S = −1.6 Adc, dI_S/dt = 100 A/μs)	t_{rr}	–	30	60	ns

4. Indicates Pulse Test: P.W. = 300 μsec max, Duty Cycle = 2%.
5. Handling precautions to protect against electrostatic discharge are mandatory.

TYPICAL ELECTRICAL CHARACTERISTICS



Figure 1. On−Region Characteristics



Figure 2. Transfer Characteristics



Figure 3. On−Resistance vs. Gate−to−Source Voltage



Figure 4. On−Resistance vs. Drain Current and Gate Voltage



Figure 5. On−Resistance Variation with Temperature



Figure 6. Drain−to−Source Leakage Current vs. Voltage

TYPICAL ELECTRICAL CHARACTERISTICS



Figure 7. Capacitance Variation



Figure 8. Gate−to−Source and Drain−to−Source Voltage vs. Total Charge



Figure 9. Gate Threshold Voltage Variation with Temperature



Figure 10. Diode Forward Voltage vs. Current

TYPICAL ELECTRICAL CHARACTERISTICS



Figure 11. Single Pulse Power



Figure 12. Normalized Thermal Transient Impedance, Junction−to−Ambient



TSOP−6 3.00x1.50x0.90, 0.95P
CASE 318G
ISSUE W

DATE 26 FEB 2024



TOP VIEW

NOTES:
1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 2018.
2. CONTROLLING DIMENSION: MILLIMETERS.
3. MAXIMUM LEAD THICKNESS INCLUDES LEAD FINISH. MINIMUM LEAD THICKNESS IS THE MINIMUM THICKNESS OF BASE MATERIAL.
4. DIMENSIONS D AND E1 DO NOT INCLUDE MOLD FLASH, PROTRUSIONS, OR GATE BURRS. MOLD FLASH, PROTRUSIONS, OR GATE BURRS SHALL NOT EXCEED 0.15 PER SIDE. DIMENSIONS D AND E1 ARE DETERMINED AT DATUM H.
5. PIN 1 INDICATOR MUST BE LOCATED IN THE INDICATED ZONE



DETAIL Z
SCALE 3:1



SIDE VIEW

MILLIMETERS			
DIM	MIN	NOM	MAX
A	0.90	1.00	1.10
A1	0.01	0.06	0.10
A2	0.80	0.90	1.00
b	0.25	0.38	0.50
c	0.10	0.18	0.26
D	2.90	3.00	3.10
E	2.50	2.75	3.00
E1	1.30	1.50	1.70
e	0.85	0.95	1.05
L	0.20	0.40	0.60
L2	0.25 BSC		
M	0°	---	10°



END VIEW



RECOMMENDED MOUNTING FOOTPRINT

*For additional information on our Pb-Free strategy and soldering details, please download th e ON Semiconductor Soldering and Mounting Techniques Reference manual, SOLDERRM/D.

DOCUMENT NUMBER:	**98ASB14888C**	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red.
DESCRIPTION:	**TSOP−6 3.00x1.50x0.90, 0.95P**	**PAGE 1 OF 2**

onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.

TSOP−6 3.00x1.50x0.90, 0.95P
CASE 318G
ISSUE W

DATE 26 FEB 2024

GENERIC MARKING DIAGRAM*



IC

XXX = Specific Device Code
A =Assembly Location
Y = Year
W = Work Week
▪ = Pb−Free Package



STANDARD

XXX = Specific Device Code
M = Date Code
▪ = Pb−Free Package

*This information is generic. Please refer to device data sheet for actual part marking. Pb−Free indicator, “G” or microdot “▪”, may or may not be present. Some products may not follow the Generic Marking.

STYLE 1:
PIN 1. DRAIN
2. DRAIN
3. GATE
4. SOURCE
5. DRAIN
6. DRAIN

STYLE 2:
PIN 1. EMITTER 2
2. BASE 1
3. COLLECTOR 1
4. EMITTER 1
5. BASE 2
6. COLLECTOR 2

STYLE 3:
PIN 1. ENABLE
2. N/C
3. R BOOST
4. Vz
5. V in
6. V out

STYLE 4:
PIN 1. N/C
2. V in
3. NOT USED
4. GROUND
5. ENABLE
6. LOAD

STYLE 5:
PIN 1. EMITTER 2
2. BASE 2
3. COLLECTOR 1
4. EMITTER 1
5. BASE 1
6. COLLECTOR 2

STYLE 6:
PIN 1. COLLECTOR
2. COLLECTOR
3. BASE
4. EMITTER
5. COLLECTOR
6. COLLECTOR

STYLE 7:
PIN 1. COLLECTOR
2. COLLECTOR
3. BASE
4. N/C
5. COLLECTOR
6. EMITTER

STYLE 8:
PIN 1. Vbus
2. D(in)
3. D(in)+
4. D(out)+
5. D(out)
6. GND

STYLE 9:
PIN 1. LOW VOLTAGE GATE
2. DRAIN
3. SOURCE
4. DRAIN
5. DRAIN
6. HIGH VOLTAGE GATE

STYLE 10:
PIN 1. D(OUT)+
2. GND
3. D(OUT)−
4. D(IN)−
5. VBUS
6. D(IN)+

STYLE 11:
PIN 1. SOURCE 1
2. DRAIN 2
3. DRAIN 2
4. SOURCE 2
5. GATE 1
6. DRAIN 1/GATE 2

STYLE 12:
PIN 1. I/O
2. GROUND
3. I/O
4. I/O
5. VCC
6. I/O

STYLE 13:
PIN 1. GATE 1
2. SOURCE 2
3. GATE 2
4. DRAIN 2
5. SOURCE 1
6. DRAIN 1

STYLE 14:
PIN 1. ANODE
2. SOURCE
3. GATE
4. CATHODE/DRAIN
5. CATHODE/DRAIN
6. CATHODE/DRAIN

STYLE 15:
PIN 1. ANODE
2. SOURCE
3. GATE
4. DRAIN
5. N/C
6. CATHODE

STYLE 16:
PIN 1. ANODE/CATHODE
2. BASE
3. EMITTER
4. COLLECTOR
5. ANODE
6. CATHODE

STYLE 17:
PIN 1. EMITTER
2. BASE
3. ANODE/CATHODE
4. ANODE
5. CATHODE
6. COLLECTOR

DOCUMENT NUMBER:	98ASB14888C	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped “CONTROLLED COPY” in red.
DESCRIPTION:	TSOP−6 3.00x1.50x0.90, 0.95P	PAGE 2 OF 2

onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.

onsemi, onsemi, and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as−is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

ADDITIONAL INFORMATION

TECHNICAL PUBLICATIONS:
Technical Library: www.onsemi.com/design/resources/technical−documentation
onsemi Website: www.onsemi.com

ONLINE SUPPORT: www.onsemi.com/support
For additional information, please contact your local Sales Representative at
www.onsemi.com/support/sales