# **PCRL75120SQF**

## Product Preview

# **1200 V Rectifier Die**

Low forward voltage rectifier die for free-wheeling applications. Ideal for use as a reverse diode in IGBT applications.

#### **Features**

- Low Vf
- Soft Fast Reverse Recovery Diode

## **Typical Applications**

- Solar Inverters
- UPS Systems

#### **MAXIMUM RATINGS**

Parameter	Symbol	Value	Unit
Peak Reverse Voltage, T <sub>J</sub> = 25°C	$V_{RRM}$	1200	V
Max Forward Conduction Current	IF	(Note 1)	Α
Operating Junction Temperature	$T_J$	-55 to +175	°C

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

1. Depending on thermal properties of assembly.

#### **MECHANICAL DATA**

Parameter	Symbol	Unit	
Die Size	6200 × 3300	μm <sup>2</sup>	
Die Thickness	121	μm	
Wafer Size	150	mm	
Total Pad Size (Anode)	5552 × 2652	μm <sup>2</sup>	
Top Pad metal	3.9 μm AlSi		
Back metal	2 μm AlTiNiAg		
Passivation	1.5 μm HR NIT		
Max possible chips per wafer	610		
Reject Ink dot size	25 mils		
Recommended storage environment: In original container, in dry nitrogen, or temperature of 18–28°C, 30–65% RH	Type: Sawn wafer on tape. Storage time: <3 months		

#### **ORDERING INFORMATION**

Device	Inking?	Shipping
PCRL75120SQF	Yes	Sawn Wafer on Tape



## ON Semiconductor®


www.onsemi.com

V<sub>RRM</sub> = 1200 V I<sub>F</sub> = Limited by T<sub>i(max)</sub>

#### **DIODE DIE**



#### **DIE OUTLINE**



This document contains information on a product under development. ON Semiconductor reserves the right to change or discontinue this product without notice.

onsemi, Onsemi, and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "onsemi" or its affiliates and/or subsidiaries in the United States and/or other countries. onsemi owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of onsemi's product/patent coverage may be accessed at <a href="www.onsemi.com/site/pdf/Patent-Marking.pdf">www.onsemi.com/site/pdf/Patent-Marking.pdf</a>. Onsemi reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as-is" and onsemi makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does onsemi assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using onsemi products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by onsemi. "Typical" parameters which may be provided in onsemi data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. onsemi does not convey any license under any of its intellectual property rights nor the rights of others. onsemi products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA class 3 medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase

#### ADDITIONAL INFORMATION

**TECHNICAL PUBLICATIONS:** 

 $\textbf{Technical Library:} \ \underline{www.onsemi.com/design/resources/technical-documentation}$ 

onsemi Website: www.onsemi.com

ONLINE SUPPORT: www.onsemi.com/support

For additional information, please contact your local Sales Representative at

www.onsemi.com/support/sales