

MICRODE AXIAL CASE 194-04

DATE 09 SEP 2003

NOTES:

CATHODE SYMBOL ON PACKAGE.
194-01 OBSOLETE, 194-04 NEW STANDARD.

	MILLIMETERS		INCHES	
DIM	MIN	MAX	MIN	MAX
Α	8.43	8.69	0.332	0.342
В	5.94	6.25	0.234	0.246
D	1.27	1.35	0.050	0.053
K	25.15	25.65	0.990	1.010

GENERIC MARKING DIAGRAM*



DEV = Specific Device Code = Assembly Location

ΥY = Year WW = Work Week

*This information is generic. Please refer to device data sheet for actual part marking.

DOCUMENT NUMBER:	98ASB42126B	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red.		
DESCRIPTION:	MICRODE AXIAL		PAGE 1 OF 1	

ON Semiconductor and at a trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. ON Semiconductor does not convey any license under its patent rights nor the rights of others.