

UQFN10 1.4x1.8, 0.4P

DATE 01 AUG 2007

NOTES:

- DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994.
 CONTROLLING DIMENSION: MILLIMETERS
- 2. COPTROLLING DIMENSION. MILLIMETERS
 3. DIMENSION 5 APPLIES TO PLATED TERMINAL
 AND IS MEASURED BETWEEN 0.25 AND 0.30 MM
 FROM TERMINAL
 4. COPLANARITY APPLIES TO THE EXPOSED PAD
 AS WELL AS THE TERMINALS.

	MILLIN	IETERS
DIM	MIN	MAX
Α	0.45	0.60
A1	0.00	0.05
A3	0.127	REF
b	0.15	0.25
D	1.40	BSC
E	1.80	BSC
е	0.40	BSC
L	0.30	0.50
L1	0.00	0.15
L3	0.40	0.60

GENERIC MARKING DIAGRAM*



XX = Specific Device Code

= Date Code Μ

= Pb-Free Package

(Note: Microdot may be in either location)

*This information is generic. Please refer to device data sheet for actual part marking. Pb-Free indicator, "G" or microdot " ■", may or may not be present.


MOUNTING FOOTPRINT

BOTTOM VIEW

10 X

Œ 0.05 С

0.10 C A B



DOCUMENT NUMBER:	98AON22493D	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red.	
DESCRIPTION:	10 PIN UQFN. 1.4 X 1.8. 0.4P		PAGE 1 OF 1

ON Semiconductor and un are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. ON Semiconductor does not convey any license under its patent rights nor the rights of others.