

\*For additional information on our Pb-Free strategy and soldering details, please download the onsemi Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

## DATE 18 DEC 2014

- DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994.
- ASME Y14.5M, 1994. CONTROLLING DIMENSION: MILLIMETERS. DIMENSION 6 APPLIES TO PLATED TERMINAL AND IS MEASURED BETWEEN 0.03 AND 0.07 FROM THE TERMINAL TIPS.
- COPLANARITY APPLIES TO THE EXPOSED PAD AS WELL AS THE TERMINALS.

	MILLIMETERS		
DIM	MIN	MAX	
Α		0.60	
A1	0.00	0.05	
A3	0.15 REF		
b	0.20	0.30	
D	1.00 BSC		
D2	0.38	0.58	
Е	1.00 BSC		
е	0.65 BSC		
L	0.20	0.30	
L2	0.27	0.37	

## GENERIC **MARKING DIAGRAM\***

XX M 0 1

XX = Specific Device Code

= Date Code

\*This information is generic. Please refer to device data sheet for actual part

Pb-Free indicator, "G" or microdot " .", may or may not be present.

DOCUMENT NUMBER:	98AON76666F	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red.	
DESCRIPTION:	UDFN4, 1.0X1.0, 0.65P		PAGE 1 OF 1

onsemi and ONSEMi. are trademarks of Semiconductor Components Industries, LLC dba onsemi or its subsidiaries in the United States and/or other countries. onsemi reserves the right to make changes without further notice to any products herein. onsemi makes no warranty, representation or guarantee regarding the suitability of its products herein. onsemi makes no warranty, representation or guarantee regarding the suitability of its products herein. special, consequential or incidental damages. onsemi does not convey any license under its patent rights nor the rights of others.