

CASE 567NN ISSUE O


DATE 29 MAR 2016

NOTES:

- NOTES: 1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994. 2. CONTROLLING DIMENSION: MILLIMETERS. 3. COPLANARITY APPLIES TO SPHERICAL CROWNS OF THE SOLDER BALLS. DATING THE OFFICIENCY OF ANE TO SPECIFED DY
- DATUM C, THE SEATING PLANE, IS DEFINED BY THE SPHERICAL CROWNS OF THE SOLDER 4. BALLS. DIMENSION b IS MEASURED AT THE MAXIMUM
- 5. SOLDER BALL DIAMETER PARALLEL TO DATUM C.

	MILLIMETERS		
DIM	MIN	MAX	
Α		0.33	
A1	0.03	0.13	
b	0.20	0.30	
D	1.55 BSC		
Е	1.53 BSC		
е	0.40 BSC		

RECOMMENDED SOLDERING FOOTPRINT*



*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

DOCUMENT NUMBER:	98AON10051G	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red.		
DESCRIPTION:	WLCSP8, 1.55X1.53		PAGE 1 OF 1	
ON Semiconductor and (III) are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. ON Semiconductor does not convey any license under its patent rights nor the rights of others.				

© Semiconductor Components Industries, LLC, 2019