	Material Comp © Copyright 2005. Il International and Par	PC, Bannockb	urn, Illinois. A	All rights reserved u ntions.	nder both	This docume level parts, t	ent is a declara he declaration	tion of encom	f the substances npasses all low	s within the er level mat	manufactur erials for wl	er listed it hich the m	tem. Note: i nanufacture	f the item is an as r has engineering	ssembly with low responsibility.
752-21.1	IPC Web Site for Information on IPC-1752 Standard Form Typ http://www.ipc.org/IPC-175x Distribute				* Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Mater					eous Materia	als and Mfg Information				
upplie	r Information														
Company name* Compan				mpany unique ID			Unique ID Authority					Response Date*			
nsemi												2025-06-08			
ontact N	lame		Title - Contact				Phone - Contact*					Email - Contact*			
Product-I	Env-Stewards		Product Enviro Compliance				NA				Product-Env-Stewards@onsemi.com				
uthorize	ed Representative*		Title - Representative				Phone - Representative*				Email - Representative*				
roduct-l	Env-Stewards		Product Enviro Compliance				NA				Product-Env-Stewards@onsemi.com				
	Requester Item Number Mfr Item N 1N5343BR		Number Mfr Item Name				Effective Dat	e Ve	e Version Manufacturing Site		ing Site	1	Weight*	UOM	Unit Type
			BRLG	RLG ZEN SUR40 REG 5W 7.5V TR			2025-06-08 CNP		CNP	P 607		507.0	mg	Each	
Ianufa	cturing Proccess Informa	tion													
	Terminal Plating / Grid Array Material		Terminal Base Alloy J-STD-020		-STD-020 MS	L Rating	Peak Process Body Temperat		ure Max Time at Peak Temp		Temperat	ure Numl	per of Reflow Cyc	cles	
Matte Tin (Sn) - annealed (CU Alloy NA			0 C		С	30		secon	ds 3				
omments	8														
or more	information regarding material	composition	please refer to	page 3											

RoHS Material Composition Declaration				Declaration Type *	Detailed						
Directive 2015/863/EU amending RoHS Directive 2011/65/EU	RoHS Definition: Quantity limit of 0.01% by mass (100 PPM) in homogeneous material for Cadmium and quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury (Hg), Hexavalent Chromium (Cr6+), Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE), and Bis(2-ethylhexyl) phthalate (DEHP), Benzyl-butyl phthalate (BBP), Dibutyl phthalate (DBP), Diisobutyl phthalate (DIBP).										
cadmium, hexavalentchromium, polybromina contains a RoHS restricted substance inexces encompass all such components. Supplier cer as of the date that Supplier completes this for Company acknowledges that Supplier may h independently verified information provided certification in this paragraph. If the Company	ated biphenyls and/or polybrominated dip s of an applicable quantity limit, please in iffies that it gathered the information it pr m.Supplier acknowledges that Company ave relied on informationprovided by oth by others, Supplier agrees that, at a minir and the Supplier enter into a written agr esource of the Supplier's liability and the	henyl ethers (each a "RoHS restricted substa ndicate below which, if any, RoHS exemption ovides in this form using appropriate methoo will rely on this certification in determining ers in completing this form, and that Supplie num, itssuppliers have provided certification eement with respect to the identified part, the Company's remedies for issues that arise reg	nce") in exco n you believe ls to ensure i the compliar r may not ha s regarding t terms and co	e may apply. If the part is an assembly with low s accuracy and that such information is true an ce of its products with European Union member de independently verified such information. Ho neir contributions to the part, and those certifica	ove. If a homogeneous material within the part er level components, the declaration shall d correct to the best of its knowledge and belief, er state laws that implement the RoHS Directive. wever, in situations where Supplier has not ations are at least as comprehensive as the anty rights and/or remedies provided as part of						
RoHS Declaration * 4 - Item(s) does not contain RoHS restricted subst	ances per the definition above except for sele	ected exempt	ions Supplier Acceptance	* Accepted						
Exemption: 7a: Lead in high melting temp	erature type solders (i.e. lead based sol	der alloys containing 85% by weight or m	ore lead).								
Exemption List Version	EL-2011/534/EU										
Declaration Signature											
Instructions: Complete all of the required Requester) and click on Submit Form to h			e drop-dowi	a. This will display the signature area. Digita	lly sign the declaration (if required by the						
Supplier Digital Signature	astislav Drska	Le									

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Die	4.5	mg	Supplier	Silicon (Si)	7440-21-3		4.5	mg
Die Attach Solder	21.29	mg	Supplier	Silver (Ag)	7440-22-4		0.5323	mg
			А	Lead (Pb)	7439-92-1	7a	19.6933	mg
			Supplier	Tin (Sn)	7440-31-5		1.0645	mg
Lead Frame	333.62	mg	В	Nickel (Ni)	7440-02-0		3.6698	mg
			Supplier	Copper (Cu)	7440-50-8		329.9502	mg
Mold Compound-Black	239.19	mg		Metal Hydroxide	proprietary data		11.9595	mg
			Supplier	Carbon Black (C)	1333-86-4		2.3919	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		179.3925	mg
			Supplier	Ortho-Cresol Novolac Resin	29690-82-2		23.919	mg
			Supplier	Phenolic Resin (Novolac)	9003-35-4		21.5271	mg
Plating	8.4	mg	Supplier	Tin (Sn)	7440-31-5		8.4	mg

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3