IPC ASSOCIATION CONNECT ELECTRONICS INDUSTR	© Copyright 2005. IPG	Material Composition Declaration © Copyright 2005. IPC, Bannockburn, Illinois. All rights reserved under both international and Pan-American copyright conventions.				This document is a declaration of the substances within the manufacturer listed item. Note: if the item is an assembly with low level parts, the declaration encompasses all lower level materials for which the manufacturer has engineering responsibility.									
752-21.1		IPC Web Site for Information on IPC-1752 Standard Form Typ http://www.ipc.org/IPC-175x Distribute				* Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Mater						als and Mfg	Informat	tion	
upplier Infor	mation														
Company name*			Company unique ID			τ	Unique ID Authority					Response Date*			
nsemi												2025-05-20			
Contact Name		Title - Contact			I	Phone - Contact*					Email - Contact*				
Product-Env-Stev	wards	Product Enviro Compliance			1	NA					Product-Env-Stewards@onsemi.com				
authorized Repre	sentative*	Title - Representative			I	Phone - Representative*				Email - Representative*					
Product-Env-Stewards			Product Enviro Compliance]	NA				Product-Env-Stewards@onsemi.com				
Reques	ster Item Number			tem Number Mfr Item Name			Effective Dat	e Versio	on 1	Manufacturing Site		W	eight*	UOM	Unit Type
				2-Input LP Logic Gate			2025-05-20		7	TH2		2.	035	mg	Each
Ianufacturing	g Proccess Informati	on						,							,
Termina	al Plating / Grid Array Material		Terminal Base Alloy		J-STD-020 MS	0-020 MSL Rating		Peak Process Body Temperature		Max Time at Peak Tempera		Temperatu	ture Number of Reflow Cycles		eles
Preciou Sn)	Precious metal (e.g. Ag,Au, NiPdAu) (no Sn)		CU Alloy		1		260		C	30	seco		3		
Comments						<u> </u>									
vel 1 - maximum	ı time at peak temperatur	e during so	ldering is 10-3	30 seconds											
or more informa	tion regarding material c	omposition	please refer to	p page 3											

RoHS Material Composition Declaration			Declaration Type *	Detail	ed						
Directive 2015/863/EU amending RoHS Directive 2011/65/EU RoHS Definition: Quantity limit of 0.01% by mass (100 PPM) in homogeneous material for Cadmium and quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury (Hg), Hexavalent Chromium (Cr6+), Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE), and Bis(2-ethylhexyl) phthalate (DEHP), Benzyl-butyl phthalate (BBP), Dibutyl phthalate (DBP), Diisobutyl phthalate (DIBP).											
Please indicate whether any homogeneous material (as defined by the RoHS Directive, EU 2011/65/EU and implemented by the laws of the European Union member states) of the part identified on this form contains lead, mercury, cadmium, hexavalentchromium, polybrominated biphenyls and/or polybrominated diphenyl ethers (each a "RoHS restricted substance") in excess of the applicable quantity limit identified above. If a homogeneous material within the part contains a RoHS restricted substance inexcess of an applicable quantity limit, please indicate below which, if any, RoHS exemption you believe may apply. If the part is an assembly with lower level components, the declaration shall encompass all such components. Supplier certifies that it gathered the information is true and correct to the best of its knowledge and belief, as of the date that Supplier completes this form. Supplier acknowledges that Company will rely on this certification in determining the compliance of its products with European Union member state laws that implement the RoHS Directive. Company acknowledges that Supplier may have relied on information provided by others in completing this form, and that Supplier may not have independently verified such information. However, in situations where Supplier has not independently verified information provided by others, Supplier agrees that, at a minimum, its suppliers have provided certifications regarding their contributions to the part, and those certifications are at least as comprehensive as the certification in this paragraph. If the Company and the Supplier is liability and the Company's remedies for issues that arise regarding information the Supplier provides in this form. In the absence of such written agreement, the warranty rights and/or remedies of Supplier's Standard Terms and Conditions of Sale applicable to such part shall apply.											
RoHS Declaration * 1 - Item	(s) does not contain RoHS restricted substar	nces per the definition above	Supplier A	cceptance *	Accepted						
Exemption: If the declared item does not contain RoHS restricted substances per the definition above except for defined RoHS exemptions, then select the corresponding response in the RoHS Declaration above and choose all applicable exemptions.											
Exemption List Version	EL-2011/534/EU										
Declaration Signature											
		e "Accepted" on the Supplier Acceptance	drop-down. This will display the signature a	rea. Digitally sign t	the declaration (if required by the						

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).

Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Die	0.055	mg	Supplier	Silicon (Si)	7440-21-3		0.055	mg
Die Attach	0.014	mg	Supplier	Phenolic Resin-2	54208-63-8		0.007	mg
			Supplier	Ortho Cresol Novolac Resin	29690-82-2		0.007	mg
Lead Frame	0.562	mg	Supplier	Zinc (Zn)	7440-66-6		0.001	mg
			Supplier	Iron (Fe)	7439-89-6		0.014	mg
			Supplier	Copper (Cu)	7440-50-8		0.547	mg
			Supplier	Phosphorus (P)	7723-14-0		-0	mg
Mold Compound-Black	1.34		Supplier	4,4'-Bis(2,3-epoxypropoxy)-3,3',5,5'-tetramethylbiphenyl	85954-11-6		0.268	mg
			Supplier	Carbon Black (C)	1333-86-4		0.013	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		0.992	mg
			Supplier	Phenolic Resin (Novolac)	9003-35-4		0.067	mg
Plating	0.026		Supplier	Palladium (Pd)	7440-05-3		0.002	mg
			В	Nickel (Ni)	7440-02-0		0.024	mg
			Supplier	Gold (Au)	7440-57-5		-0	mg
Wire Bond - Au	0.038	mg	Supplier	Gold (Au)	7440-57-5		0.038	mg