ASSOCIATION CONNECTING	Material Composit © Copyright 2005. IPC, international and Pan-An	Bannockb	ourn, Illinois. A	ll rights reserved u ntions.	nder both	This docume level parts, t	ent is a decla	aration of on encon	f the substance npasses all lo	es withi wer leve	n the manufactu l materials for w	rer listed i hich the r	item. No nanufac	ote: if the turer has	item is an asso engineering re	embly with lower sponsibility.
1752-21.1	IPC Web Site for Information on IPC-1752 Standard Form Typ http://www.ipc.org/IPC-175x Distribute				*	Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Mater					ials and M	als and Mfg Information				
Supplier Informa	ation															
Company name*	Company unique ID			Unique ID Authority					Respon	Response Date*						
onsemi										2024-05	2024-05-05					
Contact Name	Title - Contact]	Phone - Contact*					Email -	Email - Contact*					
Product-Env-Stewar	ds	Product Enviro Compliance				NA					Product-Env-Stewards@onsemi.com					
Authorized Represen	tative*	Title - Representative			Phone - Representative*					Email - Representative*						
Product-Env-Stewards			Product Enviro Compliance				NA					Produc	Product-Env-Stewards@onsemi.com			
Requester	Requester Item Number Mfr Item		Number Mfr Item Name				Effective D	ate Version Manufacturing Site			Weight	*	UOM	Unit Type		
	CAT34T C		S02VP2GT4	TEMP SENSOR	RY	2024-05-05	5		THB	ТНВ		14.87		mg	Each	
Manufacturing P	roccess Information	l					•			-		·				
Terminal P	Terminal Plating / Grid Array Material		erminal Base Alloy J-STD-		-STD-020 MS	L Rating	Peak P	Process Body Temperatu		ture M	ure Max Time at Peak Ter		emperature Number		f Reflow Cycle	s
Precious metal (e.g. Ag,Au, NiPdAu) (no Sn)			CU Alloy 1		L		260		С	30	30 8		seconds 3			
Comments																
evel 1 - maximum tin	ne at peak temperature d	luring sol	dering is 10-3	0 seconds												
for more information	n regarding material com	position	please refer to	page 3												

RoHS Material Composition Declaration				Declaration Type *	Detailed
Directive 2015/863/EU amending RoHS Directive 2011/65/EU		nium (Cr6+), Polybro	ominated Biphenyls (PBB), Polybron	dmium and quantity limit of 0.1% by mass (100 minated Diphenyl Ethers (PBDE), and Bis(2-eth	
cadmium, hexavalentchromium, polybrominate contains a RoHS restricted substance inexcess encompass all such components. Supplier certif as of the date that Supplier completes this form Company acknowledges that Supplier may hav independently verified information provided by certification in this paragraph. If the Company a	ed biphenyls and/or polybrominated dip of an applicable quantity limit, please ir ies that it gathered the information it pro- .Supplier acknowledges that Company e relied on informationprovided by othe v others, Supplier agrees that, at a minin and the Supplier enter into a written agre pource of the Supplier's liability and the	henyl ethers (each a " ndicate below which, i ovides in this form us will rely on this certifiers in completing this num, itssuppliers have eement with respect to Company's remedies	RoHS restricted substance") in exce if any, RoHS exemption you believe ing appropriate methods to ensure if ication in determining the complian form, and that Supplier may not have e provided certifications regarding the to the identified part, the terms and co for issues that arise regarding inform	ce of its products with European Union membe	ove. If a homogeneous material within the part er level components, the declaration shall l correct to the best of its knowledge and belief, r state laws that implement the RoHS Directive. wever, in situations where Supplier has not tions are at least as comprehensive as the anty rights and/or remedies provided as part of
RoHS Declaration * 1 - Item(s)	does not contain RoHS restricted substa	ances per the definitio	on above	Supplier Acceptance	* Accepted
Exemption: If the declared item does not con applicable exemptions.	ntain RoHS restricted substances per	the definition above	except for defined RoHS exempti	ons, then select the corresponding response i	n the RoHS Declaration above and choose all
Exemption List Version	EL-2011/534/EU				
Declaration Signature					
Instructions: Complete all of the required fin Requester) and click on Submit Form to have	elds on all pages of this form. Select the form returned to the Requester	he "Accepted" on th	e Supplier Acceptance drop-down	. This will display the signature area. Digital	lly sign the declaration (if required by the
Supplier Digital Signature Ra	stislav Drska	Le			

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Die	0.4	mg	Supplier	Silicon (Si)	7440-21-3		0.4	mg
Die Attach	0.1	mg		Epoxy resin	proprietary data		0.02	mg
			Supplier	Silver (Ag)	7440-22-4		0.08	mg
Lead Frame	6.18	mg	Supplier	Zinc (Zn)	7440-66-6		0.0074	mg
			Supplier	Iron (Fe)	7439-89-6		0.1452	mg
			Supplier	Copper (Cu)	7440-50-8		6.0255	mg
			Supplier	Phosphorus (P)	7723-14-0		0.0019	mg
Mold Compound-Black	7.94	mg		Epoxy resin	proprietary data		0.3732	mg
			Supplier	Silica Amorphous (SiO2)	7631-86-9		0.794	mg
			Supplier	Carbon Black (C)	1333-86-4		0.0079	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		6.3917	mg
			Supplier	Phenolic Resin (Novolac)	9003-35-4		0.3732	mg
Plating	0.12	mg	Supplier	Palladium (Pd)	7440-05-3		0.0075	mg
			В	Nickel (Ni)	7440-02-0		0.1113	mg
			Supplier	Gold (Au)	7440-57-5		0.0013	mg
Vire Bond - Au	0.13	mg	Supplier	Gold (Au)	7440-57-5		0.13	mg

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).