C	Aaterial Composit Copyright 2005. IPC, International and Pan-Am	Bannockbu	urn, Illinois. A	ll rights reserved untions.	under both	This docum evel parts, t	ent is a decla the declaration	aration of	of the substances mpasses all lowe	within the man er level materials	ufacturer s for whic	listed item. h the manu	Note: if facturer h	the item is an as	sembly with lower responsibility.	
					Form Type * Distribute						Materials	ials and Mfg Information				
Supplier Information	on															
Company name*			Company unique ID			Unique ID Authority					Response Date*					
onsemi										20	2025-05-14					
Contact Name			Title - Contact			Phone - Contact*				E	Email - Contact*					
Product-Env-Stewards			Product Enviro Compliance			NA				F	Product-Env-Stewards@onsemi.com					
Authorized Representative*			Title - Representative			Phone - Representative*				E	Email - Representative*					
Product-Env-Stewards			Product Enviro Compliance			NA				P	Product-Env-Stewards@onsemi.com					
Requester Ite	Requester Item Number Mfr Item		n Number Mfr Item Name				Effective D	ate V	rsion	Manufacturing Site		Weig	ght*	UOM	Unit Type	
		FAN54120UC420X 500mA Linear C		500mA USB Cor Linear Charger w	MA USB Compatible Single Cell Li-Ion ear Charger with 4.2V float voltage		2025-05-14	Ļ		РВВ		1.30	7134	mg	Each	
Manufacturing Pro	occess Information															
Terminal Plating / Grid Array Material Te			erminal Base Alloy J-STD-020 MSL		Rating	Peak Process Body Temperature		re Max Time at Peak Tempera		mperature	Numbe	r of Reflow Cyc	les			
SnAgCu CU Al			J Alloy 1			260 C 30			seconds 3							
Comments																
level 1 - maximum time	at peak temperature d	uring solo	dering is 10-3	0 seconds												
For more information re	egarding material com	position p	olease refer to	page 3												

RoHS Material Composition Declaration				Declaration Type *	Detailed							
Directive 2015/863/EU amending RoHS Directive 2011/65/EU	RoHS Definition: Quantity limit of 0.01% by mass (100 PPM) in homogeneous material for Cadmium and quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury (Hg), Hexavalent Chromium (Cr6+), Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE), and Bis(2-ethylhexyl) phthalate (DEHP), Benzyl-butyl phthalate (BBP), Dibutyl phthalate (DBP), Diisobutyl phthalate (DIBP).											
cadmium, hexavalentchromium, polybrominate contains a RoHS restricted substance inexcess encompass all such components. Supplier certif as of the date that Supplier completes this form Company acknowledges that Supplier may hav independently verified information provided by certification in this paragraph. If the Company a	ed biphenyls and/or polybrominated dip of an applicable quantity limit, please ir ies that it gathered the information it pro- .Supplier acknowledges that Company e relied on informationprovided by othe v others, Supplier agrees that, at a minin and the Supplier enter into a written agre pource of the Supplier's liability and the	henyl ethers (each a " ndicate below which, i ovides in this form us will rely on this certifiers in completing this num, itssuppliers have eement with respect to Company's remedies	RoHS restricted substance") in exce if any, RoHS exemption you believe ing appropriate methods to ensure if ication in determining the complian form, and that Supplier may not have e provided certifications regarding the to the identified part, the terms and cc for issues that arise regarding inform	ce of its products with European Union membe	ove. If a homogeneous material within the part er level components, the declaration shall l correct to the best of its knowledge and belief, r state laws that implement the RoHS Directive. wever, in situations where Supplier has not tions are at least as comprehensive as the anty rights and/or remedies provided as part of							
RoHS Declaration * 1 - Item(s)	does not contain RoHS restricted substa	ances per the definitio	on above	Supplier Acceptance	* Accepted							
Exemption: If the declared item does not con applicable exemptions.	ntain RoHS restricted substances per	the definition above	except for defined RoHS exempti	ons, then select the corresponding response i	n the RoHS Declaration above and choose all							
Exemption List Version	EL-2011/534/EU											
Declaration Signature												
Instructions: Complete all of the required fin Requester) and click on Submit Form to have	elds on all pages of this form. Select the form returned to the Requester	he "Accepted" on th	e Supplier Acceptance drop-down	. This will display the signature area. Digital	lly sign the declaration (if required by the							
Supplier Digital Signature Ra	stislav Drska	Le										

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Backside Protection Film	0.043928	mg		Epoxy resin	proprietary data		0.0092	mg
			Supplier	Carbon Black (C)	1333-86-4		0.0008	mg
			Supplier	Acrylic resins	Proprietary Data		0.0092	mg
			Supplier	Silica (SiO2)	14464-46-1		0.0247	mg
Die	0.850126	mg	Supplier	Silicon (Si)	7440-21-3		0.8501	mg
Protection coat	8.0E-6	mg		Polyimide	proprietary data		0	mg
Solder Ball	0.410608	mg	Supplier	Silver (Ag)	7440-22-4		0.0164	mg
			Supplier	Tin (Sn)	7440-31-5		0.3921	mg
			Supplier	Copper (Cu)	7440-50-8		0.0021	mg
Under Bump Metal	0.002464	mg	Supplier	Titanium (Ti)	7440-32-6		0.0003	mg
			Supplier	Copper (Cu)	7440-50-8		0.0022	mg

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 signa range of distribution unless otherwise noted)