PC Web Site for Information on IPC-1752 Standard http://www.ipc.org/IPC-175x	IPC ASSOCIATION ELECTRONICS	© Copyright 2005 IPC Rannockburn Illinois All rights reserved under both				This document is a declaration of the substances within the manufacturer listed item. Note: if the item is an assembly with low level parts, the declaration encompasses all lower level materials for which the manufacturer has engineering responsibility.										
Company name* Company unique ID Unique ID Authority Response Date* 2025-08-01 Contact Name Title - Contact Product Envistewards Authorized Representative* Product Envistewards	752-21.1	IPC Web Site for Information on IPC-1752 Standard Form Type					e *					s Materials	and Mfg Informat	on		
Insemi 2025-08-01 Contact Name Title - Contact Phone - Contact* Product-Env-Stewards Product Enviro Compliance NA Product-Env-Stewards@onsemi.com Authorized Representative* Product-Env-Stewards Product Enviro Compliance NA Product-Env-Stewards@onsemi.com Requester Item Number Mfr Item Name Effective Date Version Manufacturing Site Weight* UOM Unit FCP380N60 SF2 600V 380mOhm f TO220 2025-08-01 CPA 2030.181 mg Each Manufacturing Proccess Information Terminal Plating / Grid Array Material Terminal Base Alloy J-STD-020 MSL Rating Peak Process Body Temperature Max Time at Peak Temperature Number of Reflow Cycles	Supplier	Information														
Title - Contact Name Product Enviro Compliance NA Product-Env-Stewards NA Product-Env-Stewards NA Product-Env-Stewards NA Product-Env-Stewards Product-Env-Stewards Product-Env-Stewards Product-Env-Stewards Product-Env-Stewards Product-Env-Stewards NA Product-Env-Stewards Product-Env-Stewards NA Product-Env-Stewards NA Product-Env-Stewards@onsemi.com Product-Env-Stewards@onsemi.com Product-Env-Stewards@onsemi.com NA Product-Env-Stewards@onsemi.com NA Product-Env-Stewards@onsemi.com Product-Env-Stewards@onsemi.com Product-Env-Stewards@onsemi.com NA Product-Env-Stewards@onsemi.com NA Product-Env-Stewards@onsemi.com Product-Env-Stewards@onsemi.com Product-Env-Stewards@onsemi.com NA Product-Env-Stewards@onsemi.com Product-Env-Stewards@onsemi.com NA Product-Env-Stewards@onsemi.com Product-Env-Stewards@onsemi.com NA Na Namifacturing Site Na Namifacturing Site Na Namifacturing Site Na Na Namifacturing Site Na Namifacturing Namifacturing Site Na Namifacturing Namifacturing Site Na Namifacturing Namifacturing Site Na Namifacturing Namifacturing Namifacturing Site Na Namifacturing Namifacturing Namifacturing Site Na Namifacturing Namifacturin	ompany n	name*		Company ur	nique ID			Unique ID Authority				R	Response Date*			
Product-Env-Stewards Authorized Representative* Product-Env-Stewards Pro	nsemi											2	025-08-01			
Authorized Representative* Product-Env-Stewards Product Enviro Compliance Requester Item Number Mfr Item Number Mfr Item Number Mfr Item Name Effective Date Version Manufacturing Site Weight* UOM Unit FCP380N60 SF2 600V 380mOhm f TO220 2025-08-01 CPA 2030.181 mg Each Manufacturing Proccess Information Terminal Plating / Grid Array Material Terminal Base Alloy J-STD-020 MSL Rating Peak Process Body Temperature Max Time at Peak Temperature Number of Reflow Cycles	ontact Na	me		Title - Conta	ect			Phone - Contact*				E	Email - Contact*			
Product-Env-Stewards Requester Item Number Mfr Item Number Mfr Item Name Effective Date Version Manufacturing Site Weight* UOM Unit FCP380N60 SF2 600V 380mOhm f TO220 2025-08-01 CPA 2030.181 mg Each Manufacturing Proccess Information Terminal Plating / Grid Array Material Terminal Base Alloy J-STD-020 MSL Rating Peak Process Body Temperature Max Time at Peak Temperature Number of Reflow Cycles	Product-E	nv-Stewards		Product Env	iro Compliance			NA				I	Product-Env-Stewards@onsemi.com			
Requester Item Number Mfr Item Number Mfr Item Name Effective Date Version Manufacturing Site Weight* UOM Unit FCP380N60 SF2 600V 380mOhm f TO220 2025-08-01 CPA 2030.181 mg Each Manufacturing Proccess Information Terminal Plating / Grid Array Material Terminal Base Alloy J-STD-020 MSL Rating Peak Process Body Temperature Max Time at Peak Temperature Number of Reflow Cycles	Authorized Representative* Title - Representative						Phone - Representative*				E	Email - Representative*				
FCP380N60 SF2 600V 380mOhm f TO220 2025-08-01 CPA 2030.181 mg Each Ianufacturing Proccess Information Terminal Plating / Grid Array Material Terminal Base Alloy J-STD-020 MSL Rating Peak Process Body Temperature Max Time at Peak Temperature Number of Reflow Cycles	Product-Env-Stewards Product Enviro Compli				iro Compliance	iance NA				Produ			Product-Env-Stew	duct-Env-Stewards@onsemi.com		
Manufacturing Process Information Terminal Plating / Grid Array Material Terminal Base Alloy J-STD-020 MSL Rating Peak Process Body Temperature Max Time at Peak Temperature Number of Reflow Cycles		Requester Item Number	Mfr Iten	n Number	Mfr Item Name			Effective Date	Version	n N	Manufacturing	Site	Weight*	UOM	Unit Type	
Terminal Plating / Grid Array Material Terminal Base Alloy J-STD-020 MSL Rating Peak Process Body Temperature Max Time at Peak Temperature Number of Reflow Cycles			FCP380	N60	SF2 600V 380mOl	hm f TO220		2025-08-01		C	CPA		2030.181	mg	Each	
						GTD 000 M				-	la m			0D 0		
Matte Tin (Sn) - annealed CU Alloy NA 0 C 30 seconds 3					-		SL Rating				at Peak Te			cles		
omments	-	Matte Tin (Sn) - annealed		CU Alloy	N	A		[0		IC.	30		seconds 3			
	'or more ir	nformation regarding materia	al composition	nlease refer t	o nogo 2											

RoHS Material Composition Declaration			Declaration Type *	Detailed						
Directive 2015/863/EU amending RoHS Directive 2011/65/EU RoHS Definition: Quantity limit of 0.01% by mass (100 PPM) in homogeneous material for Cadmium and quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury (Hg), Hexavalent Chromium (Cr6+), Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE), and Bis(2-ethylhexyl) phthalate (DEHP), Benzyl-butyl phthalate (BBP), Dibutyl phthalate (DBP), Dissobutyl phthalate (DIBP).										
Please indicate whether any homogeneous material (as defined by the RoHS Directive, EU 2011/65/EU and implemented by the laws of the European Union member states) of the part identified on this form contains lead, mercury, cadmium, hexavalentchromium, polybrominated biphenyls and/or polybrominated diphenyl ethers (each a "RoHS restricted substance") in excess of the applicable quantity limit identified above. If a homogeneous material within the part contains a RoHS restricted substance inexcess of an applicable quantity limit, please indicate below which, if any, RoHS exemption you believe may apply. If the part is an assembly with lower level components, the tender of the date that such information it provides in this form using appropriate methods to ensure its accuracy and that such information is true and correct to the best of its knowledges that Company will rely on this certification in determining the compliance of its products with European Union member state laws that implement the RoHS Directive Company acknowledges that Supplier may have relied on information provided by others in completing this form, and that Supplier may not have independently verified such information. However, in situations where Supplier has not independently verified information provided by others, Supplier agrees that, at a minimum, its suppliers have provided certifications regarding their contributions to the part, and those certifications are at least as comprehensive as the certification in this paragraph. If the Company and the Supplier enter into a written agreement with respect to the identified part, the terms and conditions of that agreement, including any warranty rights and/or remedies of Supplier's Standard Terms and Conditions of Sale applicable to such part shall apply.										
RoHS Declaration * 4 - Item(s) does not contain RoHS restricted substance	es per the definition above except for selected exemp	otions Supplier Acceptance	* Accepted						
Exemption: 7a: Lead in high melting temperature type solders (i.e. lead based solder alloys containing 85% by weight or more lead).										
Exemption List Version	EL-2011/534/EU									
Declaration Signature										
Instructions: Complete all of the required fields on all pages of this form. Select the "Accepted" on the Supplier Acceptance drop-down. This will display the signature area. Digitally sign the declaration (if required by the Requester) and click on Submit Form to have the form returned to the Requester.										
Supplier Digital Signature Ra	astislav Drska	-6_								

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).

Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Die	2.81	mg	Supplier	Silicon (Si)	7440-21-3		2.81	mg
Die Attach Solder	1.111	mg	Supplier	Silver (Ag)	7440-22-4		0.0278	mg
			A	Lead (Pb)	7439-92-1	7a	1.0277	mg
			Supplier	Tin (Sn)	7440-31-5		0.0555	mg
Lead Frame	1492.12	mg	В	Nickel (Ni)	7440-02-0		0.1492	mg
			Supplier	Iron (Fe)	7439-89-6		1.4921	mg
			Supplier	Copper (Cu)	7440-50-8		1490.031	mg
			Supplier	Phosphorus (P)	7723-14-0		0.4476	mg
Mold Compound-Black	518.4	mg		Proprietary	proprietary data		25.92	mg
			Supplier	Carbon Black (C)	1333-86-4		2.592	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		386.208	mg
			Supplier	Ortho-Cresol Novolac Resin	29690-82-2		77.76	mg
			Supplier	Phenolic Resin (Novolac)	9003-35-4		25.92	mg
Plating	13.3	mg	Supplier	Tin (Sn)	7440-31-5		13.3	mg
Wire Bond - Al	2.44	mg	Supplier	Aluminum (Al)	7429-90-5		2.44	mg