ASSOCIATION CONNECTING	© Copyright 2005. IPC, international and Pan-Ar	Bannockb	urn, Illinois. A	ll rights reserved un tions.	nder both	This docume level parts, t	ent is a declarat he declaration	ion of the su encompasse	ubstances s all lower	within the manufactur level materials for w	er listed i hich the n	tem. Note: it nanufacturer	f the item is an as has engineering	sembly with lower responsibility.
1752-21.1	IPC Web Site for Information on IPC-1752 Standard Form Type http://www.ipc.org/IPC-175x Distribute				*	* Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Materi				als and Mfg Information				
Supplier Inform	ation													
Company name* Co			Company unique ID			Unique ID Authority				Response Date*				
onsemi											2025-06-07			
Contact Name 7			Title - Contact				Phone - Contact*				Email - Contact*			
Product-Env-Stewards			Product Enviro Compliance				NA				Product-Env-Stewards@onsemi.com			
Authorized Representative* T			Title - Representative			Phone - Representative*			Email - Representative*					
Product-Env-Stewards			Product Enviro Compliance				NA				Product-Env-Stewards@onsemi.com			
Requester	Requester Item Number Mfr Iten		n Number Mfr Item Name				Effective Date	Date Version Manufacturing Site			Weight*	UOM	Unit Type	
		FDD8444	FDD8444 FET 40V 5.2 mOh		nm DPAK		2025-06-07 CNJ		ŊJ	:	329.241	mg	Each	
Manufacturing I	Proccess Information	1												
Terminal Plating / Grid Array Material Terminal B			erminal Base A	Alloy J-STD-020 MSL Rating			Peak Process Body Temperature Max Time at Peak 7				Temperature Number of Reflow Cycles			
Matte Tin (Sn) - annealed CU Alloy			1			260		С	30	secon	ds 3			
Comments														
evel 1 - maximum ti	me at peak temperature o	luring sol	dering is 10-3	0 seconds										
For more informatio	on regarding material con	position]	please refer to	page 3										

RoHS Material Composition Declaration				Declaration Type *	Detailed						
Directive 2015/863/EU amending RoHS Directive 2011/65/EU	RoHS Definition: Quantity limit of 0.01% by mass (100 PPM) in homogeneous material for Cadmium and quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury (Hg), Hexavalent Chromium (Cr6+), Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE), and Bis(2-ethylhexyl) phthalate (DEHP), Benzyl-butyl phthalate (BBP), Dibutyl phthalate (DBP), Diisobutyl phthalate (DIBP).										
cadmium, hexavalentchromium, polybromina contains a RoHS restricted substance inexces encompass all such components. Supplier cer as of the date that Supplier completes this for Company acknowledges that Supplier may h independently verified information provided certification in this paragraph. If the Company	ated biphenyls and/or polybrominated dip s of an applicable quantity limit, please in ifies that it gathered the information it pr m.Supplier acknowledges that Company ave relied on informationprovided by oth by others, Supplier agrees that, at a minir and the Supplier enter into a written agr esource of the Supplier's liability and the	henyl ethers (each a "RoHS restricted substa ndicate below which, if any, RoHS exemption ovides in this form using appropriate methoo will rely on this certification in determining ers in completing this form, and that Supplie num, itssuppliers have provided certification eement with respect to the identified part, the Company's remedies for issues that arise reg	nce") in exco n you believe ls to ensure i the compliar r may not ha s regarding t terms and co	e may apply. If the part is an assembly with low s accuracy and that such information is true an ce of its products with European Union member de independently verified such information. Ho neir contributions to the part, and those certifica	ove. If a homogeneous material within the part er level components, the declaration shall d correct to the best of its knowledge and belief, er state laws that implement the RoHS Directive. wever, in situations where Supplier has not ations are at least as comprehensive as the anty rights and/or remedies provided as part of						
RoHS Declaration * 4 - Item(s) does not contain RoHS restricted subst	ances per the definition above except for sele	ected exempt	ions Supplier Acceptance	* Accepted						
Exemption: 7a: Lead in high melting temp	erature type solders (i.e. lead based sol	der alloys containing 85% by weight or m	ore lead).								
Exemption List Version	EL-2011/534/EU										
Declaration Signature											
Instructions: Complete all of the required Requester) and click on Submit Form to h			e drop-dowi	a. This will display the signature area. Digita	lly sign the declaration (if required by the						
Supplier Digital Signature	astislav Drska	Le									

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

sigma range of distribution unless otherwise noted).									
Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure	
Die	5.16	mg	Supplier	Silicon (Si)	7440-21-3		5.16	mg	
Die Attach Solder	5.026	mg	Supplier	Silver (Ag)	7440-22-4		0.1257	mg	
			А	Lead (Pb)	7439-92-1	7a	4.6491	mg	
			Supplier	Tin (Sn)	7440-31-5		0.2513	mg	
Lead Frame	167.854	mg	Supplier	Tin (Sn)	7440-31-5		0.168	mg	
			В	Nickel (Ni)	7440-02-0		0.168	mg	
			Supplier	Copper (Cu)	7440-50-8		167.518	mg	
Mold Compound-Black	149.268	mg		Epoxy resin	proprietary data		8.9561	mg	
			Supplier	Phenolic Resin	Proprietary Data		8.9561	mg	
			Supplier	Carbon Black (C)	1333-86-4		0.7463	mg	
			Supplier	Fused Silica (SiO2)	60676-86-0		126.8778	mg	
			Supplier	Silica Crystalline (SiO2)	14808-60-7		3.7317	mg	
Plating	1.092	mg	Supplier	Tin (Sn)	7440-31-5		1.092	mg	
Wire Bond - Al	0.841	mg	Supplier	Aluminum (Al)	7429-90-5		0.841	mg	

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 signa range of distribution unless otherwise noted).