ASSOCIATION CONNECTING	© Copyright 2005. IPC, international and Pan-Ar	Bannockb	urn, Illinois. A	ll rights reserved untions.	nder both	This docume level parts, t	ent is a declara	tion of the s encompass	substances es all lowe	within the manufacture level materials for w	urer listed which the	item. Note: i manufacturer	f the item is an as has engineering	ssembly with lower responsibility.	
1752-21.1	IPC Web Site for Information on IPC-1752 Standard Form Typ http://www.ipc.org/IPC-175x Distribute				e *	* Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Mater					ials and Mfg Information				
Supplier Inform	ation														
Company name*			Company unique ID			-	Unique ID Authority					Response Date*			
onsemi											2024-0	2024-04-25			
Contact Name			Title - Contact				Phone - Contact*				Email	Email - Contact*			
Product-Env-Stewards			Product Enviro Compliance				NA				Produ	Product-Env-Stewards@onsemi.com			
Authorized Representative*			Title - Representative				Phone - Representative*				Email	Email - Representative*			
Product-Env-Stewa	rds		Product Enviro Compliance				NA				Produ	Product-Env-Stewards@onsemi.com			
Requester	Requester Item Number Mfr Iten		n Number Mfr Item Name				Effective Dat	e Version	n i	Manufacturing Site		Weight*	UOM	Unit Type	
		FDG6316P SC8		SC88 12V/8V 270/650MO PCH DU		DU	2024-04-25			CN1		5.753	mg	Each	
Manufacturing I	Proccess Information	1													
Terminal Plating / Grid Array Material Termina			erminal Base A	Base Alloy J-STD-020 MSL		L Rating	Peak Process Body Temperature		re Max Time at Pea	me at Peak Temperat		er of Reflow Cy	cles		
Matte Tin (Sn) - annealed CU Alloy			U Alloy		l		260		C	30	seco	onds 3			
Comments															
evel 1 - maximum ti	me at peak temperature o	luring sol	dering is 10-3	0 seconds											
for more informatio	on regarding material con	position p	please refer to	page 3											

RoHS Material Composition Declaration				Declaration Type *	Detailed
Directive 2015/863/EU amending RoHS Directive 2011/65/EU		nium (Cr6+), Polybro	ominated Biphenyls (PBB), Polybron	dmium and quantity limit of 0.1% by mass (100 minated Diphenyl Ethers (PBDE), and Bis(2-eth	
cadmium, hexavalentchromium, polybrominate contains a RoHS restricted substance inexcess encompass all such components. Supplier certif as of the date that Supplier completes this form Company acknowledges that Supplier may hav independently verified information provided by certification in this paragraph. If the Company a	ed biphenyls and/or polybrominated dip of an applicable quantity limit, please ir ies that it gathered the information it pro- .Supplier acknowledges that Company e relied on informationprovided by othe y others, Supplier agrees that, at a minin and the Supplier enter into a written agre pource of the Supplier's liability and the	henyl ethers (each a " ndicate below which, i ovides in this form us will rely on this certifiers in completing this num, itssuppliers have eement with respect to Company's remedies	RoHS restricted substance") in exce if any, RoHS exemption you believe ing appropriate methods to ensure if ication in determining the complian form, and that Supplier may not have e provided certifications regarding the to the identified part, the terms and co for issues that arise regarding inform	ce of its products with European Union membe	ove. If a homogeneous material within the part er level components, the declaration shall l correct to the best of its knowledge and belief, r state laws that implement the RoHS Directive. wever, in situations where Supplier has not tions are at least as comprehensive as the anty rights and/or remedies provided as part of
RoHS Declaration * 1 - Item(s)	does not contain RoHS restricted substa	on above	Supplier Acceptance	* Accepted	
Exemption: If the declared item does not con applicable exemptions.	ntain RoHS restricted substances per	the definition above	except for defined RoHS exempti	ons, then select the corresponding response i	n the RoHS Declaration above and choose all
Exemption List Version	EL-2011/534/EU				
Declaration Signature					
Instructions: Complete all of the required fin Requester) and click on Submit Form to have	elds on all pages of this form. Select the form returned to the Requester	he "Accepted" on th	e Supplier Acceptance drop-down	. This will display the signature area. Digital	lly sign the declaration (if required by the
Supplier Digital Signature Ra	stislav Drska	Le			

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

sigma range of distribution unless otherwise noted).									
Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure	
Die	0.148	mg	Supplier	Silicon (Si)	7440-21-3		0.148	mg	
Lead Frame	2.087	mg	В	Nickel (Ni)	7440-02-0		0.7576	mg	
			Supplier	Iron (Fe)	7439-89-6		1.0477	mg	
			Supplier	Copper (Cu)	7440-50-8		0.2817	mg	
Mold Compound-Black	3.224	mg	Supplier	Boron zinc hydroxide oxide	138265-88-0		0.0967	mg	
			Supplier	Zinc Monoxide (ZnO)	1314-13-2		0.0161	mg	
			Supplier	2,4,6-triamino-s-triazincompd.withs- triazine-triol	37640-57-6		0.0967	mg	
			Supplier	Silica Amorphous (SiO2)	7631-86-9		2.5792	mg	
			Supplier	Carbon Black (C)	1333-86-4		0.0322	mg	
			Supplier	Ortho-Cresol Novolac Resin	29690-82-2		0.2579	mg	
			Supplier	Phenolic Resin (Novolac)	9003-35-4		0.1451	mg	
Plating	0.274	mg	Supplier	Tin (Sn)	7440-31-5		0.274	mg	
Wire Bond - Cu	0.02	mg	Supplier	Copper (Cu)	7440-50-8		0.02	mg	

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 signa range of distribution unless otherwise noted)