ASEOCIATION CONNECTING ELECTRONICS INDUSTRIES® International and	position De 5. IPC, Bannockt Pan-American co	claration ourn, Illinois. <i>A</i> opyright conve	All rights reserved u ntions.	nder both	This docume level parts, t	ent is a declaration entities of the declaration entities	on of the substar acompasses all 1	ces within the m ower level mater	anufacturer l ials for whicl	listed item. Note: h the manufacture	if the item is an a er has engineering	ssembly with low responsibility.	
	1 IPC Web Site for Information on IPC-1752 Standard Form Typ			Form Type Distribute	* Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Materi				us Materials	ials and Mfg Information			
upplier Information													
Company name* Com			Company unique ID			Unique ID Authority				Response Date*			
onsemi										2025-05-04			
Contact Name Title - Contact			ct	Phone - Contact*				E	Email - Contact*				
Product-Env-Stewards Pro			Product Enviro Compliance			NA				Product-Env-Stewards@onsemi.com			
Authorized Representative* Title - Rep			Representative I			Phone - Representative*			E	Email - Representative*			
Product-Env-Stewards			Product Enviro Compliance			NA				Product-Env-Stewards@onsemi.com			
Requester Item Number Mfr Iter		n Number Mfr Item Name				Effective Date	Version	Manufacturing Site		Weight*	UOM	Unit Type	
	FDP083	FDP083N15A-F102 FET 150V 8.3 m		Ohm TO220		2025-05-04		СРА		2040.181	mg	Each	
Ianufacturing Proccess Inform	nation												
Terminal Plating / Grid Array	Terminal Plating / Grid Array Material Terminal Base A		Alloy J	-STD-020 MSI	L Rating	Peak Process Body Temperature Max Time at Peak			e at Peak Tei	Temperature Number of Reflow Cycles			
Matte Tin (Sn) - annealed C		CU Alloy NA			0 C 30			seconds 3					
omments													
or more information regarding mater	ial composition	please refer to	page 3										

RoHS Material Composition Declaration				Declaration Type *	Detailed
Directive 2015/863/EU amending RoHS Directive 2011/65/EU		mium (Cr6+), Polybrominated Biphenyls (Pl		dmium and quantity limit of 0.1% by mass (10 minated Diphenyl Ethers (PBDE), and Bis(2-et	
cadmium, hexavalentchromium, polybromina contains a RoHS restricted substance inexces encompass all such components. Supplier cer as of the date that Supplier completes this for Company acknowledges that Supplier may h independently verified information provided certification in this paragraph. If the Company	ated biphenyls and/or polybrominated dip s of an applicable quantity limit, please in iffies that it gathered the information it pr m.Supplier acknowledges that Company ave relied on informationprovided by oth by others, Supplier agrees that, at a minir and the Supplier enter into a written agr esource of the Supplier's liability and the	henyl ethers (each a "RoHS restricted substa ndicate below which, if any, RoHS exemption ovides in this form using appropriate methoo will rely on this certification in determining ers in completing this form, and that Supplie num, itssuppliers have provided certification eement with respect to the identified part, the Company's remedies for issues that arise reg	nce") in exco n you believe ls to ensure i the compliar r may not ha s regarding t terms and co	e may apply. If the part is an assembly with low s accuracy and that such information is true an ce of its products with European Union member de independently verified such information. Ho neir contributions to the part, and those certifica	ove. If a homogeneous material within the part er level components, the declaration shall d correct to the best of its knowledge and belief, er state laws that implement the RoHS Directive. wever, in situations where Supplier has not ations are at least as comprehensive as the anty rights and/or remedies provided as part of
RoHS Declaration * 4 - Item(s) does not contain RoHS restricted subst	ances per the definition above except for sele	ected exempt	ions Supplier Acceptance	* Accepted
Exemption: 7a: Lead in high melting temp	erature type solders (i.e. lead based sol	der alloys containing 85% by weight or m	ore lead).		
Exemption List Version	EL-2011/534/EU				
Declaration Signature					
Instructions: Complete all of the required Requester) and click on Submit Form to h			e drop-dowi	a. This will display the signature area. Digita	lly sign the declaration (if required by the
Supplier Digital Signature	astislav Drska	Le			

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

sigma range of distribution unless otherwise noted).									
Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure	
Die	12.81	mg	Supplier	Silicon (Si)	7440-21-3		12.81	mg	
Die Attach Solder	1.111	mg	Supplier	Silver (Ag)	7440-22-4		0.0278	mg	
			А	Lead (Pb)	7439-92-1	7a	1.0277	mg	
			Supplier	Tin (Sn)	7440-31-5		0.0555	mg	
Lead Frame	1505.42	mg	Supplier	Tin (Sn)	7440-31-5		13.3	mg	
			В	Nickel (Ni)	7440-02-0		0.173	mg	
			Supplier	Iron (Fe)	7439-89-6		1.5	mg	
			Supplier	Copper (Cu)	7440-50-8		1489.9985	mg	
			Supplier	Phosphorus (P)	7723-14-0		0.4485	mg	
Mold Compound-Black	518.4	mg		Metal Hydroxide	proprietary data		18.144	mg	
			Supplier	Ortho Cresol Novolac Resin	29690-82-2		41.472	mg	
			Supplier	Carbon Black (C)	1333-86-4		2.592	mg	
			Supplier	Fused Silica (SiO2)	60676-86-0		414.72	mg	
			Supplier	Phenolic Resin (Novolac)	9003-35-4		41.472	mg	
Wire Bond - Al	2.44	mg	Supplier	Aluminum (Al)	7429-90-5		2.44	mg	

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).