	Material Comp © Copyright 2005. Il international and Par	PC, Bannockb	ourn, Illinois. A	All rights reserved u ntions.	nder both	This docume level parts, t	ent is a declarat he declaration e	ion of the encompass	substances ses all lowe	within the r er level mate	nanufacture rials for wh	er listed ite	m. Note: if nufacturer	the item is an as has engineering	ssembly with low responsibility.
752-21.1	IPC Web Site for Information on IPC-1752 Standard Form Type http://www.ipc.org/IPC-175x Distribute				* Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Materi					ous Materia	als and Mfg Information				
upplie	r Information														
Company name* Company				iny unique ID			Unique ID Authority					Response Date*			
nsemi												2024-04-30			
Contact N	ame		Title - Contact			]	Phone - Contact*				Email - Contact*				
Product-H	Env-Stewards		Product Enviro Compliance				NA					Product-Env-Stewards@onsemi.com			
uthorize	d Representative*		Title - Representative			]	Phone - Representative*				Email - Representative*				
roduct-I	Env-Stewards		Product Enviro Compliance				NA				Product-Env-Stewards@onsemi.com				
	Requester Item Number Mfr Iten		n Number Mfr Item Name				Effective Date	Version	n :	Manufacturing Site CPA		W	eight*	UOM	Unit Type
		FFSP2065B-F085 SiC Diode T		SiC Diode TO220	1220 650V		2024-04-30	)24-04-30				19	978.421	mg	Each
Ianufa	cturing Proccess Informa	tion													
	Terminal Plating / Grid Array Material		Ferminal Base Alloy J-STD-020 M		-STD-020 MS	L Rating	Peak Process Body Temperat		ure Max Time at Peak Temp		Temperatu	re Numbe	er of Reflow Cyc	cles	
Matte Tin (Sn) - annealed		C	CU Alloy NA			0 C		C	30		second	s 3			
omments															
or more	information regarding material	composition	please refer to	page 3											

RoHS Material Composition Declaration				Declaration Type *	Detailed				
Directive 2015/863/EU amending RoHS Directive 2011/65/EU		mium (Cr6+), Polybrominated Biphenyls (Pl		dmium and quantity limit of 0.1% by mass (10 minated Diphenyl Ethers (PBDE), and Bis(2-et					
cadmium, hexavalentchromium, polybromina contains a RoHS restricted substance inexces encompass all such components. Supplier cer as of the date that Supplier completes this for Company acknowledges that Supplier may h independently verified information provided certification in this paragraph. If the Company	ated biphenyls and/or polybrominated dip s of an applicable quantity limit, please in iffies that it gathered the information it pr m.Supplier acknowledges that Company ave relied on informationprovided by oth by others, Supplier agrees that, at a minir and the Supplier enter into a written agr esource of the Supplier's liability and the	henyl ethers (each a "RoHS restricted substa ndicate below which, if any, RoHS exemption ovides in this form using appropriate methoo will rely on this certification in determining ers in completing this form, and that Supplie num, itssuppliers have provided certification eement with respect to the identified part, the Company's remedies for issues that arise reg	nce") in exco n you believe ls to ensure i the compliar r may not ha s regarding t terms and co	e may apply. If the part is an assembly with low s accuracy and that such information is true an ce of its products with European Union member de independently verified such information. Ho neir contributions to the part, and those certifica	ove. If a homogeneous material within the part er level components, the declaration shall d correct to the best of its knowledge and belief, er state laws that implement the RoHS Directive. wever, in situations where Supplier has not ations are at least as comprehensive as the anty rights and/or remedies provided as part of				
RoHS Declaration * 4 - Item(	s) does not contain RoHS restricted subst	ances per the definition above except for sele	ected exempt	ions Supplier Acceptance	* Accepted				
Exemption: 7a: Lead in high melting temp	erature type solders (i.e. lead based sol	der alloys containing 85% by weight or m	ore lead).						
Exemption List Version	EL-2011/534/EU								
Declaration Signature									
Instructions: Complete all of the required fields on all pages of this form. Select the "Accepted" on the Supplier Acceptance drop-down. This will display the signature area. Digitally sign the declaration (if required by the Requester) and click on Submit Form to have the form returned to the Requester.									
Supplier Digital Signature	astislav Drska	Le							

## Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

sigma range of distribution unless	otherwise noted).							
Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Die	2.81	mg	Supplier	Silicon Carbide	409-21-2		2.81	mg
Die Attach Solder	1.111	mg	Supplier	Silver (Ag)	7440-22-4		0.0278	mg
			А	Lead (Pb)	7439-92-1	7a	1.0277	mg
			Supplier	Tin (Sn)	7440-31-5		0.0555	mg
Lead Frame	1444.76	mg	В	Nickel (Ni)	7440-02-0		1.0113	mg
			Supplier	Iron (Fe)	7439-89-6		1.4448	mg
			Supplier	Copper (Cu)	7440-50-8		1441.8705	mg
			Supplier	Phosphorus (P)	7723-14-0		0.4334	mg
Mold Compound-Black	518.4	mg		Proprietary	proprietary data		25.92	mg
			Supplier	Carbon Black (C)	1333-86-4		2.592	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		386.208	mg
			Supplier	Ortho-Cresol Novolac Resin	29690-82-2		77.76	mg
			Supplier	Phenolic Resin (Novolac)	9003-35-4		25.92	mg
Plating	8.9	mg	Supplier	Tin (Sn)	7440-31-5		8.9	mg
Wire Bond - Al	2.44	mg	Supplier	Aluminum (Al)	7429-90-5		2.44	mg

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 signa range of distribution unless otherwise noted).