ASSOCIATION CONNECTION	Material Composit © Copyright 2005. IPC, international and Pan-Ar	Bannockb	urn, Illinois. A	ll rights reserved u ntions.	nder both	This docume level parts, t	ent is a declara he declaration	ion of the s encompasse	ubstances es all lowe	within the manufacture within the manufacture with the materials for with the materials for with the manufacture w	urer listed which the	item. Note: if manufacturer	f the item is an as has engineering	ssembly with lower responsibility.	
1752-21.1					Form Type Distribute	* Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Materi					rials and N	als and Mfg Information			
Supplier Inform	nation														
Company name*			Company unique ID				Unique ID Authority				Respon	Response Date*			
onsemi											2024-0	2024-05-21			
Contact Name			Title - Contact				Phone - Contact*				Email	Email - Contact*			
Product-Env-Stewards			Product Enviro Compliance				NA				Produ	Product-Env-Stewards@onsemi.com			
Authorized Representative*			Title - Representative				Phone - Representative*			Email	Email - Representative*				
Product-Env-Stewards			Product Enviro Compliance				NA				Produ	Product-Env-Stewards@onsemi.com			
Request	Requester Item Number Mfr Iten		n Number Mfr Item Name				Effective Date	version	1	Manufacturing Site		Weight*	UOM	Unit Type	
		FOD8384V S		SO5 3A GD VDE			2024-05-21		I	PBB		197.151	mg	Each	
Manufacturing	Proccess Information	1													
Terminal Plating / Grid Array Material Ter			erminal Base Alloy J-STD-020 MSI		L Rating	Peak Process Body Temperature		re Max Time at Peal	k Tempera	ature Numb	er of Reflow Cy	cles			
Matte Tin (Sn) - annealed CU Alle			U Alloy	1			260 C 30			seco	seconds 3				
Comments															
evel 1 - maximum	time at peak temperature of	luring sol	dering is 10-3	0 seconds											
for more informat	ion regarding material con	position j	please refer to	page 3											

RoHS Material Composition Declaration				Declaration Type *	Detailed							
Directive 2015/863/EU amending RoHS Directive 2011/65/EU	(Pb), Mercury (Hg), Hexavalent Chror	oHS Definition: Quantity limit of 0.01% by mass (100 PPM) in homogeneous material for Cadmium and quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead b), Mercury (Hg), Hexavalent Chromium (Cr6+), Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE), and Bis(2-ethylhexyl) phthalate (DEHP), Benzyl-butyl athalate (BBP), Dibutyl phthalate (DBP), Diisobutyl phthalate (DIBP).										
cadmium, hexavalentchromium, polybrominate contains a RoHS restricted substance inexcess encompass all such components. Supplier certif as of the date that Supplier completes this form Company acknowledges that Supplier may hav independently verified information provided by certification in this paragraph. If the Company a	ed biphenyls and/or polybrominated dip of an applicable quantity limit, please ir ies that it gathered the information it pro- .Supplier acknowledges that Company e relied on informationprovided by othe v others, Supplier agrees that, at a minin and the Supplier enter into a written agre pource of the Supplier's liability and the	henyl ethers (each a " ndicate below which, i ovides in this form us will rely on this certifiers in completing this num, itssuppliers have eement with respect to Company's remedies	RoHS restricted substance") in exce if any, RoHS exemption you believe ing appropriate methods to ensure if ication in determining the complian form, and that Supplier may not have e provided certifications regarding the to the identified part, the terms and cc for issues that arise regarding inform	ce of its products with European Union membe	ove. If a homogeneous material within the part er level components, the declaration shall l correct to the best of its knowledge and belief, r state laws that implement the RoHS Directive. wever, in situations where Supplier has not tions are at least as comprehensive as the anty rights and/or remedies provided as part of							
RoHS Declaration * 1 - Item(s)	does not contain RoHS restricted substa	on above	Supplier Acceptance	* Accepted								
Exemption: If the declared item does not con applicable exemptions.	ntain RoHS restricted substances per	the definition above	except for defined RoHS exempti	ons, then select the corresponding response i	n the RoHS Declaration above and choose all							
Exemption List Version	EL-2011/534/EU											
Declaration Signature												
Instructions: Complete all of the required fin Requester) and click on Submit Form to have	elds on all pages of this form. Select the form returned to the Requester	he "Accepted" on th	e Supplier Acceptance drop-down	. This will display the signature area. Digital	lly sign the declaration (if required by the							
Supplier Digital Signature Ra	stislav Drska	Le										

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Coupling Gel	3.5	mg	Supplier	Dimethyl Siloxane	68083-19-2		3.5	mg
Die	1.131	mg	В	Gallium Arsenide (AsGa)	1303-00-0		0.071	mg
			Supplier	Silicon (Si)	7440-21-3		1.06	mg
Die Attach	0.223	mg	Supplier	Silver (Ag)	7440-22-4		0.1784	mg
			Supplier	Phenolic Resin-2	54208-63-8		0.0446	mg
Lead Frame	36.392	mg	Supplier	Silver (Ag)	7440-22-4		0.2	mg
			Supplier	Zinc (Zn)	7440-66-6		0.044	mg
			Supplier	Iron (Fe)	7439-89-6		0.837	mg
			Supplier	Copper (Cu)	7440-50-8		35.3	mg
			Supplier	Phosphorus (P)	7723-14-0		0.011	mg
Mold Compound-Black	153.98	mg	Supplier	Titanium Dioxide (TiO2)	13463-67-7		30.8	mg
			Supplier	2,6-dibromo-4-[1-(3-bromo-4- hydroxyphenyl)-1-methylethyl]phenol	6386-73-8		6.16	mg
			Supplier	Ortho Cresol Novolac Resin	29690-82-2		35.4	mg
			В	Antimony Trioxide (Sb2O3)	1309-64-4		4.62	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		77	mg
Plating	1.69	mg	Supplier	Tin (Sn)	7440-31-5		1.69	mg
Wire Bond - Au	0.235	mg	Supplier	Gold (Au)	7440-57-5		0.235	mg