IPC ASSOCIATION ELECTRONIC	© Copyright 2005.	Material Composition Declaration © Copyright 2005. IPC, Bannockburn, Illinois. All rights reserved under both international and Pan-American copyright conventions.			nder both le	This document is a declaration of the substances within the manufacturer listed item. Note: if the item is an assembly with lowe level parts, the declaration encompasses all lower level materials for which the manufacturer has engineering responsibility.									
752-21.1		IPC Web Site for Information on IPC-1752 Standard Form Typ http://www.ipc.org/IPC-175x Distribute					Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Materi				aterials and	ials and Mfg Information			
Supplie	r Information														
Company name*			Company un	ompany unique ID			Unique ID Authority				Respo	Response Date*			
nsemi										2024-0	2024-04-25				
Contact N	lame	Title - Contact			P	Phone - Contact*				Email	Email - Contact*				
Product-	Env-Stewards	Product Enviro Compliance			1	NA				Prod	Product-Env-Stewards@onsemi.com				
uthorize	ed Representative*	Title - Representative			P	Phone - Representative*			Email	Email - Representative*					
Product-	Env-Stewards	Product Enviro Compliance			1	NA				Prod	Product-Env-Stewards@onsemi.com				
	Requester Item Number Mfr Item		n Number Mfr Item Name				Effective Date	Version	rsion Manufacturing Site		e	Weight*	UOM	Unit Type	
		FODM217AR2 4SO TR T&		4SO TR T&R	T&R		2024-04-25 CP7		7 57.322		57.322	mg	Each		
Ianufa	acturing Process Inform												·	·	
	, ,		,		-STD-020 MSL I	Rating	Peak Process Body Temperatur		Max Time at I	Peak Temper	rature Numb	er of Reflow Cy	eles		
	Matte Tin (Sn) - annealed	(CU Alloy	1			260		C	30	sec	onds 3			
omments															
vel 1 - n	naximum time at peak tempera	ture during so	ldering is 10-3	30 seconds											
or more	information regarding materia	al composition	please refer to	o page 3											

RoHS Material Composition Declaration			Declaration Type *	Detail	led						
Directive 2015/863/EU amending RoHS Directive 2011/65/EU RoHS Definition: Quantity limit of 0.01% by mass (100 PPM) in homogeneous material for Cadmium and quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury (Hg), Hexavalent Chromium (Cr6+), Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE), and Bis(2-ethylhexyl) phthalate (DEHP), Benzyl-butyl phthalate (BBP), Dibutyl phthalate (DBP), Diisobutyl phthalate (DIBP).											
Please indicate whether any homogeneous material (as defined by the RoHS Directive, EU 2011/65/EU and implemented by the laws of the European Union member states) of the part identified on this form contains lead, mercury, cadmium, hexavalentchromium, polybrominated biphenyls and/or polybrominated diphenyl ethers (each a "RoHS restricted substance") in excess of the applicable quantity limit identified above. If a homogeneous material within the part contains a RoHS restricted substance inexcess of an applicable quantity limit, please indicate below which, if any, RoHS exemption you believe may apply. If the part is an assembly with lower level components, the declaration shall encompass all such components. Supplier certifies that it gathered the information it provides in this form using appropriate methods to ensure its accuracy and that such information is true and correct to the best of its knowledge and belief, as of the date that Supplier completes this form. Supplier acknowledges that Company will rely on this certification in determining the compliance of its products with European Union member state laws that implement the RoHS Directive. Company acknowledges that Supplier may have relied on informationprovided by others in completing this form, and that Supplier may not have independently verified such information. However, in situations where Supplier have provided certifications regarding their contributions to the part, and those certifications are at least as comprehensive as the certification in this paragraph. If the Company and the Supplier enter into a written agreement with respect to the identified part, the terms and conditions of that agreement, including any warranty rights and/or remedies of Supplier's Standard Terms and Conditions of Sale applicable to such part shall apply.											
RoHS Declaration * 1 - Item	(s) does not contain RoHS restricted substa	ances per the definition above	Supplier Ac	ceptance *	Accepted						
Exemption: If the declared item does not contain RoHS restricted substances per the definition above except for defined RoHS exemptions, then select the corresponding response in the RoHS Declaration above and choose all applicable exemptions.											
Exemption List Version	EL-2011/534/EU										
Declaration Signature											
Instructional Complete all of the required	fields on all neggs of this form. Calcut th		a duan dawn. This will display the signature on	a Digitally sign	the declaration (if recurined by the						
Instructions: Complete all of the required Requester) and click on Submit Form to			e drop-down. This will display the signature ar	ea. Digitally sign	the declaration (if required by the						

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).

Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Coupling Gel	2.0	mg	Supplier	Filler (SiO2)	68909-20-6		0.4	mg
			Supplier	Dimethyl Siloxane	68083-19-2		1.6	mg
Die	0.16	mg	В	Gallium Arsenide (AsGa)	1303-00-0		0.0518	mg
			Supplier	Silicon (Si)	7440-21-3		0.1051	mg
			Supplier	Aluminum (Al)	7429-90-5		0.0031	mg
Die Attach Epoxy	0.48	mg	Supplier	Silver (Ag)	7440-22-4		0.408	mg
			Supplier	Ortho Cresol Novolac Resin	29690-82-2		0.0312	mg
			Supplier	Silica Amorphous (SiO2)	7631-86-9		0.0096	mg
			Supplier	Phenolic Resin (Novolac)	9003-35-4		0.0312	mg
Lead Frame	21.956	mg	Supplier	Zinc (Zn)	7440-66-6		0.0263	mg
			Supplier	Iron (Fe)	7439-89-6		0.516	mg
			Supplier	Copper (Cu)	7440-50-8		21.4071	mg
			Supplier	Phosphorus (P)	7723-14-0		0.0066	mg
Mold Compound-Black	18.1	mg	Supplier	Ortho Cresol Novolac Resin	29690-82-2		2.353	mg
			Supplier	Carbon Black (C)	1333-86-4		0.181	mg
			Supplier	Aluminum Hydroxide (Al(OH)3)	21645-51-2		1.629	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		12.67	mg
			Supplier	Phenolic Resin (Novolac)	9003-35-4		1.267	mg
Mold Compound-White	14.126		Supplier	Ortho Cresol Novolac Resin	29690-82-2		2.8252	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		9.8882	mg
			Supplier	Phenolic Resin (Novolac)	9003-35-4		1.4126	mg
Plating	0.1	mg	Supplier	Tin (Sn)	7440-31-5		0.1	mg
Wire Bond - Au	0.4	mg	Supplier	Gold (Au)	7440-57-5		0.4	mg