Authorized Representative*  Title - Representative  Phone - Representative*  Email - Representative*			
Company name*  Company unique ID  Unique ID Authority  2025-05-21  Contact Name  Title - Contact  Phone - Contact*  Product-Env-Stewards  Authorized Representative*  Product-Env-Stewards  Product-En	rials and Mfg Information		
Semil   Contact Name   Title - Contact   Phone - Contact*   Email - Contact*   Product-Env-Stewards   Product Enviro Compliance   NA   Product-Env-Stewards@on uthorized Representative*   Product-Env-Stewards@on   Product-Env			
Contact Name  Title - Contact  Product-Env-Stewards  Product Enviro Compliance  Authorized Representative*  Product-Env-Stewards  Product-Env-Stewards  Product-Env-Stewards  Product-Enviro Compliance  Product-Env-Stewards  Product-Enviro Compliance  Requester Item Number  Mfr Item Number  Mfr Item Name  Effective Date  Version  Manufacturing Site  Weight*  UO  100  100  100  100  100  100  100	Response Date*		
Product-Env-Stewards Authorized Representative* Product-Env-Stewards Pro	2025-05-21		
Authorized Representative* Product-Env-Stewards Product Enviro Compliance Requester Item Number Mfr Item Number Mfr Item Name FODM217BV MSO TR  Phone - Representative* NA Product-Env-Stewards@on Manufacturing Site Weight* UO 2025-05-21 LITEONFG 57.322 mg	Email - Contact*		
Product-Env-Stewards  Requester Item Number  Mfr Item Number  Mfr Item Name  Effective Date  Version  Manufacturing Site  Weight*  UO  FODM217BV  4SO TR  2025-05-21  LITEONFG  57.322  mg	Product-Env-Stewards@onsemi.com		
Requester Item Number Mfr Item Number Mfr Item Name Effective Date Version Manufacturing Site Weight* UO FODM217BV 4SO TR 2025-05-21 LITEONFG 57.322 mg	Email - Representative*		
FODM217BV 4SO TR 2025-05-21 LITEONFG 57.322 mg	Product-Env-Stewards@onsemi.com		
	OM Unit Type		
Janufacturing Process Information	g Each		
	oflow Cycles		
	now Cycles		
water In (sn) - ameared CC Andy I 200 C 30 Seconds 3			
omments			
vel 1 - maximum time at peak temperature during soldering is 10-30 seconds or more information regarding material composition please refer to page 3			

RoHS Material Composition Declaration			Declaration Type *	Detail	ed			
Directive 2015/863/EU amending RoHS Directive 2011/65/EU		ium (Cr6+), Polybrominated Biphenyls (PB)	erial for Cadmium and quantity limit of 0.1% b B), Polybrominated Diphenyl Ethers (PBDE), a					
Please indicate whether any homogeneous material (as defined by the RoHS Directive, EU 2011/65/EU and implemented by the laws of the European Union member states) of the part identified on this form contains lead, mercury, cadmium, hexavalentchromium, polybrominated biphenyls and/or polybrominated diphenyl ethers (each a "RoHS restricted substance") in excess of the applicable quantity limit identified above. If a homogeneous material within the part contains a RoHS restricted substance inexcess of an applicable quantity limit, please indicate below which, if any, RoHS exemption you believe may apply. If the part is an assembly with lower level components, the declaration shall encompass all such components. Supplier certifies that it gathered the information it provides in this form using appropriate methods to ensure its accuracy and that such information is true and correct to the best of its knowledge and belief, as of the date that Supplier completes this form. Supplier acknowledges that Company will rely on this certification in determining the compliance of its products with European Union member state laws that implement the RoHS Directive. Company acknowledges that Supplier may have relied on information provided by others in completing this form, and that Supplier may not have independently verified such information. However, in situations where Supplier has not independently verified information provided by others, Supplier agrees that, at a minimum, its provided certifications regarding their contributions to the part, and those certifications are at least as comprehensive as the certification in this paragraph. If the Company and the Supplier near into a written agreement with respect to the identified part, the terms and conditions of that agreement, including any warranty rights and/or remedies provided as part of that agreement, will be the sole and exclusivesource of the Supplier's liability and the Company's remedies for issues that arise regarding information the Supplier provides in this for								
RoHS Declaration * 1 - Item	(s) does not contain RoHS restricted substar	nces per the definition above	Supplier A	cceptance *	Accepted			
Exemption: If the declared item does not applicable exemptions.	contain RoHS restricted substances per t	he definition above except for defined Rol	IS exemptions, then select the corresponding	response in the R	oHS Declaration above and choose all			
Exemption List Version	EL-2011/534/EU							
Declaration Signature								
		e "Accepted" on the Supplier Acceptance	drop-down. This will display the signature a	rea. Digitally sign t	the declaration (if required by the			

## **Homogeneous Material Composition Declaration for Electronic Products**

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).

Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Coupling Gel	2.0	mg	Supplier	Methylhydrogen Siloxane, Trimethylsiloxy-terminated	63148-57-2		0.1	mg
			Supplier	Filler (SiO2)	68909-20-6		0.3	mg
			Supplier	Dimethyl Siloxane	68083-19-2		1.6	mg
Die	0.16	mg	В	Gallium Arsenide (AsGa)	1303-00-0		0.0518	mg
			Supplier	Silicon (Si)	7440-21-3		0.1051	mg
			Supplier	Aluminum (Al)	7429-90-5		0.0031	mg
Die Attach Epoxy	0.48	mg		Epoxy resin	proprietary data		0.0432	mg
			Supplier	Silver (Ag)	7440-22-4		0.3936	mg
			Supplier	Silica Amorphous (SiO2)	7631-86-9		0.0144	mg
			Supplier	Formaldehyde Polymer	9003-36-5		0.0288	mg
Lead Frame	21.956	5 mg	Supplier	Zinc (Zn)	7440-66-6		0.0263	mg
			Supplier	Iron (Fe)	7439-89-6		0.516	mg
			Supplier	Copper (Cu)	7440-50-8		21.4071	mg
			Supplier	Phosphorus (P)	7723-14-0		0.0066	mg
Mold Compound-Black	18.1	mg	Supplier	Ortho Cresol Novolac Resin	29690-82-2		2.353	mg
			Supplier	Carbon Black (C)	1333-86-4		0.181	mg
			Supplier	Aluminum Hydroxide (Al(OH)3)	21645-51-2		1.629	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		12.67	mg
			Supplier	Phenolic Resin (Novolac)	9003-35-4		1.267	mg
Mold Compound-White	14.126	26 mg	Supplier	Ortho Cresol Novolac Resin	29690-82-2		2.8252	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		9.8882	mg
			Supplier	Phenolic Resin (Novolac)	9003-35-4		1.4126	mg
Plating	0.1	mg	Supplier	Tin (Sn)	7440-31-5		0.1	mg
Wire Bond - Au	0.4	mg	Supplier	Gold (Au)	7440-57-5		0.4	mg