IPC ASSOCIATION CONNECT ELECTRONICS INDUSTR	© Copyright 2005, IPC.	Material Composition Declaration © Copyright 2005. IPC, Bannockburn, Illinois. All rights reserved under both international and Pan-American copyright conventions.				This document is a declaration of the substances within the manufacturer listed item. Note: if the item is an assembly with low level parts, the declaration encompasses all lower level materials for which the manufacturer has engineering responsibility.									
752-21.1		IPC Web Site for Information on IPC-1752 Standard Form Typ http://www.ipc.org/IPC-175x Distribute										nd Mfg Iı	formatio	n	
Supplier Infor	mation						·								
Company name*			Company unique ID			ī	Unique ID Authority					Response Date*			
nsemi												2025-06-05			
Contact Name		Title - Contact]	Phone - Contact*					Email - Contact*				
Product-Env-Stev	wards	Product Enviro Compliance				NA				Pro	Product-Env-Stewards@onsemi.com				
uthorized Repres	sentative*	Title - Representative]	Phone - Representative*				Em	Email - Representative*				
Product-Env-Stewards			Product Enviro Compliance				NA				Pro	Product-Env-Stewards@onsemi.com			
Reques	ester Item Number Mfr Iten		m Number Mfr Item Name				Effective Dat	e Versio	Version Manufactur		Site	Wei	ght*	UOM	Unit Type
		FODM8801BV 4SO HI		4SO HI-T TR VI	SO HI-T TR VDE		2025-06-05	025-06-05 LITEONFG			74.267 mg		mg	Each	
Ianufacturing	g Proccess Informatio	n													
Termina	Plating / Grid Array Material		Terminal Base Alloy .		J-STD-020 M	SL Rating	Peak Process Body Temperature		re Max Time at Peak Temper		perature	ture Number of Reflow Cycles			
Precious metal (e.g. Ag,Au, NiPdAu) (no Sn)		u) (no	CU Alloy 1		1		245		С	30	S	econds	3		
comments															
vel 1 - maximum	time at peak temperature	during so	ldering is 10-3	30 seconds											
or more informa	tion regarding material co	nposition	please refer to	page 3											

RoHS Material Composition Declaration			Declaration Type *	Detail	ed						
Directive 2015/863/EU amending RoHS Directive 2011/65/EU RoHS Definition: Quantity limit of 0.01% by mass (100 PPM) in homogeneous material for Cadmium and quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury (Hg), Hexavalent Chromium (Cr6+), Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE), and Bis(2-ethylhexyl) phthalate (DEHP), Benzyl-butyl phthalate (BBP), Dibutyl phthalate (DBP), Diisobutyl phthalate (DIBP).											
cadmium, hexavalentchromium, polybromin contains a RoHS restricted substance inexce encompass all such components. Supplier cet as of the date that Supplier completes this Company acknowledges that Supplier may hindependently verified information provided certification in this paragraph. If the Compan	nated biphenyls and/or polybrominated diphess of an applicable quantity limit, please indriffes that it gathered the information it provom. Supplier acknowledges that Company wave relied on informationprovided by others of the supplier agrees that, at a minimusy and the Supplier enter into a written agree yesource of the Supplier's liability and the C	enyl ethers (each a "RoHS restricted substan licate below which, if any, RoHS exemption vides in this form using appropriate methods vill rely on this certification in determining the s in completing this form, and that Supplier um, itssuppliers have provided certifications ement with respect to the identified part, the tompany's remedies for issues that arise rega	s of the European Union member states) of the ce") in excess of the applicable quantity limit is you believe may apply. If the part is an assemb to ensure its accuracy and that such informatio e compliance of its products with European Ur may not have independently verified such infor regarding their contributions to the part, and the erms and conditions of that agreement, including information the Supplier provides in this	dentified above. If a ally with lower level in is true and correct tion member state la mation. However, in ose certifications are ag any warranty righ	homogeneous material within the part components, the declaration shall to the best of its knowledge and belief, was that implement the RoHS Directive. In situations where Supplier has not the at least as comprehensive as the lats and/or remedies provided as part of						
RoHS Declaration * 1 - Item	(s) does not contain RoHS restricted substar	nces per the definition above	Supplier A	cceptance *	Accepted						
Exemption: If the declared item does not contain RoHS restricted substances per the definition above except for defined RoHS exemptions, then select the corresponding response in the RoHS Declaration above and choose all applicable exemptions.											
Exemption List Version	EL-2011/534/EU										
Declaration Signature											
		e "Accepted" on the Supplier Acceptance	drop-down. This will display the signature a	rea. Digitally sign t	the declaration (if required by the						

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).

Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure	
Die	0.267	mg	В	Gallium Arsenide (AsGa)	1303-00-0		0.0864	mg	
			Supplier	Silicon (Si)	7440-21-3		0.1754	mg	
			Supplier	Aluminum (Al)	7429-90-5		0.0052	mg	
Die Attach	0.25	mg	Supplier	Silver (Ag)	7440-22-4		0.205	mg	
			Supplier	Phenolic Resin (Novolac)	9003-35-4		0.045	mg	
Lead Frame	24.951	mg	Supplier	Silver (Ag)	7440-22-4		1.28	mg	
			Supplier	Zinc (Zn)	7440-66-6		0.0449	mg	
			Supplier	Iron (Fe)	7439-89-6		0.6138	mg	
			Supplier	Copper (Cu)	7440-50-8		22.9774	mg	
			Supplier	Phosphorus (P)	7723-14-0		0.0349	mg	
Mold Compound-White	45.0	mg	Supplier	Titanium Dioxide (TiO2)	13463-67-7		11.25	mg	
			В	Brominated Bisphenol A Diglycidyl Ether	40039-93-8		1.35	mg	
			Supplier	Ortho Cresol Novolac Resin	29690-82-2		6.075	mg	
			В	Antimony Trioxide (Sb2O3)	1309-64-4		1.35	mg	
			Supplier	Fused Silica (SiO2)	60676-86-0		22.5	mg	
			Supplier	Phenolic Resin (Novolac)	9003-35-4		2.475	mg	
Plating	0.239	mg	Supplier	Palladium (Pd)	7440-05-3		0.0095	mg	
			В	Nickel (Ni)	7440-02-0		0.2238	mg	
			Supplier	Gold (Au)	7440-57-5		0.0057	mg	
Protective Coating	3.4	mg	Supplier	Poly(dimethylsiloxane), hydroxy terminated	70131-67-8		1.7	mg	
			Supplier	Ethylbenzene	100-41-4		0.34	mg	
			Supplier	Filler (SiO2)	68909-20-6		0.646	mg	
			Supplier	Misc.	Proprietary Data		0.034	mg	
			Supplier	Xylene	1330-20-7		0.68	mg	
Wire Bond - Au	0.16	mg	Supplier	Gold (Au)	7440-57-5		0.16	mg	