C	Material Composit © Copyright 2005. IPC, I nternational and Pan-An	Bannockb	urn, Illinois. A	Il rights reserved untions.	inder both	This docume level parts, th	ent is a declar he declaration	ration of n encom	f the substanc npasses all lov	es within wer level	the manufactu naterials for v	urer listed it which the m	em. No anufac	ote: if the turer has	e item is an as s engineering	sembly with low responsibility.
	IPC Web Site for Information on IPC-1752 Standard Form Typ http://www.ipc.org/IPC-175x Distribute				e *	* Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Mater					rials and M	ials and Mfg Information				
Supplier Informati	on															
Company name*			Company unique ID			Unique ID Authority					Respons	Response Date*				
onsemi										2024-04	2024-04-19					
Contact Name		Title - Contact]	Phone - Contact*					Email -	Email - Contact*				
Product-Env-Stewards			Product Enviro Compliance			NA					Produc	Product-Env-Stewards@onsemi.com				
Authorized Representative*			Title - Representative]	Phone - Representative*				Email -	Email - Representative*				
Product-Env-Stewards			Product Enviro Compliance				NA					Produc	Product-Env-Stewards@onsemi.com			
Requester Ite	Requester Item Number Mfr Iten FXL4T2		n Number Mfr Item Name 245BQX 4-Bit Translator Direct				Effective Da	ate Ve	Version Manufac		ufacturing Site		Weight	*	UOM	Unit Type
							2024-04-19		TH2		1	17.249 mg		mg	Each	
Manufacturing Pro	occess Information	l					1								1	1
Terminal Plating / Grid Array Material		d To	erminal Base Alloy J-STI		J-STD-020 MS	L Rating	Peak Pr	Process Body Temperature M		ture Max	e Max Time at Peak Tempera		ure N	lumber o	of Reflow Cyc	les
Precious metal (e.g. Ag,Au, NiPdAu) (no Sn)			U Alloy	lloy 1			260	260 C		30	30		ds 3			
Comments																
vel 1 - maximum time	at peak temperature d	uring sol	dering is 10-3	0 seconds												
or more information r	egarding material com	position p	olease refer to	page 3												

RoHS Material Composition Declaration				Declaration Type *	Detailed								
Directive 2015/863/EU amending RoHS Directive 2011/65/EU													
cadmium, hexavalentchromium, polybrominate contains a RoHS restricted substance inexcess encompass all such components. Supplier certif as of the date that Supplier completes this form Company acknowledges that Supplier may hav independently verified information provided by certification in this paragraph. If the Company a	ed biphenyls and/or polybrominated dip of an applicable quantity limit, please ir ies that it gathered the information it pro- .Supplier acknowledges that Company e relied on informationprovided by othe y others, Supplier agrees that, at a minin and the Supplier enter into a written agre pource of the Supplier's liability and the	henyl ethers (each a " ndicate below which, i ovides in this form us will rely on this certifiers in completing this num, itssuppliers have eement with respect to Company's remedies	RoHS restricted substance") in exce if any, RoHS exemption you believe ing appropriate methods to ensure if ication in determining the complian form, and that Supplier may not have e provided certifications regarding the to the identified part, the terms and cc for issues that arise regarding inform	ce of its products with European Union membe	ove. If a homogeneous material within the part er level components, the declaration shall l correct to the best of its knowledge and belief, r state laws that implement the RoHS Directive. wever, in situations where Supplier has not tions are at least as comprehensive as the anty rights and/or remedies provided as part of								
RoHS Declaration * 1 - Item(s)	does not contain RoHS restricted substa	ances per the definitio	on above	Supplier Acceptance	* Accepted								
Exemption: If the declared item does not con applicable exemptions.	ntain RoHS restricted substances per	the definition above	except for defined RoHS exempti	ons, then select the corresponding response i	n the RoHS Declaration above and choose all								
Exemption List Version	EL-2011/534/EU												
Declaration Signature													
Instructions: Complete all of the required fin Requester) and click on Submit Form to have	elds on all pages of this form. Select the form returned to the Requester	he "Accepted" on th	e Supplier Acceptance drop-down	. This will display the signature area. Digital	lly sign the declaration (if required by the								
Supplier Digital Signature Ra	stislav Drska	Le											

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Die	0.115	mg	Supplier	Silicon (Si)	7440-21-3		0.115	mg
Die Attach Epoxy	0.059	mg	Supplier	Poly(oxypropylene)diamine	9046-10-0		0.0018	mg
			Supplier	Miscellaneous	Trade Secret		0.003	mg
			Supplier	Silver (Ag)	7440-22-4		0.0502	mg
			Supplier	Phenolic Resin (Novolac)	9003-35-4		0.0041	mg
Lead Frame	6.461	mg	Supplier	Zinc (Zn)	7440-66-6		0.008	mg
			Supplier	Iron (Fe)	7439-89-6		0.152	mg
			Supplier	Copper (Cu)	7440-50-8		6.299	mg
			Supplier	Phosphorus (P)	7723-14-0		0.002	mg
Mold Compound-Black	10.2	mg	Supplier	Ortho Cresol Novolac Resin	29690-82-2		1.02	mg
			Supplier	Carbon Black (C)	1333-86-4		0.102	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		9.078	mg
Plating	0.066	mg	Supplier	Palladium (Pd)	7440-05-3		0.006	mg
			В	Nickel (Ni)	7440-02-0		0.059	mg
			Supplier	Gold (Au)	7440-57-5		0.001	mg
Wire Bond - Au	0.348	mg	Supplier	Gold (Au)	7440-57-5		0.348	mg

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).