ASSOCIATION CONNECTING ELECTRONICS INDUSTRIES®	Material Composit © Copyright 2005. IPC, 1 international and Pan-Am	Bannockb	urn, Illinois. A	ll rights reserved untions.	under both	This docum level parts,	ent is a declar the declaratio	ation of t n encomp	he substance basses all low	s within the r er level mate	nanufactur rials for wh	er listed it hich the m	em. Note: anufacture	if the item is an as er has engineering	ssembly with lower responsibility.
1752-21.1	IPC Web Site for Information on IPC-1752 Standard Form Typ http://www.ipc.org/IPC-175x Distribute				* Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Mater					ous Materia	ials and Mfg Information				
Supplier Informa	ation														
Company name*			Company unique ID			Unique ID Authority					Response Date*				
onsemi										2025-06-08					
Contact Name			Title - Contact			Phone - Contact*					Email - Contact*				
Product-Env-Stewards			Product Enviro Compliance			NA				Product-Env-Stewards@onsemi.com					
Authorized Representative*			Title - Representative			Phone - Representative*				Email - Representative*					
Product-Env-Stewards			Product Enviro Compliance			NA				Product-Env-Stewards@onsemi.com					
Requester	Requester Item Number Mfr Item		Number Mfr Item Name				Effective Da	te Ver	sion	Manufacturing Site		١	Weight*	UOM	Unit Type
		MAX809STRG A		ANA 2.93V MCROPROC RESET		2025-06-08			MY1		8	3.14	mg	Each	
Manufacturing P	roccess Information	1													
Terminal Plating / Grid Array Material Terminal			erminal Base A	Alloy	J-STD-020 MS	L Rating	Peak Pr	ocess Bo	dy Temperati	ure Max Tir	ne at Peak	Temperat	ure Num	ber of Reflow Cy	cles
Matte Tin (Sn) - annealed CU Alloy					1		260		С	30		secon	ds 3		
Comments															
level 1 - maximum tin	ne at peak temperature d	luring sol	dering is 10-3	0 seconds											
For more information	n regarding material com	position p	olease refer to	page 3											

RoHS Material Composition Declaration				Declaration Type *	Detailed				
Directive 2015/863/EU amending RoHS Directive 2011/65/EU		nium (Cr6+), Polybro	ominated Biphenyls (PBB), Polybron	dmium and quantity limit of 0.1% by mass (100 minated Diphenyl Ethers (PBDE), and Bis(2-eth					
cadmium, hexavalentchromium, polybrominate contains a RoHS restricted substance inexcess encompass all such components. Supplier certif as of the date that Supplier completes this form Company acknowledges that Supplier may hav independently verified information provided by certification in this paragraph. If the Company a	ed biphenyls and/or polybrominated dip of an applicable quantity limit, please ir ies that it gathered the information it pro- .Supplier acknowledges that Company e relied on informationprovided by othe y others, Supplier agrees that, at a minin and the Supplier enter into a written agre pource of the Supplier's liability and the	henyl ethers (each a " ndicate below which, i ovides in this form us will rely on this certifiers in completing this num, itssuppliers have eement with respect to Company's remedies	RoHS restricted substance") in exce if any, RoHS exemption you believe ing appropriate methods to ensure if ication in determining the complian form, and that Supplier may not have e provided certifications regarding the to the identified part, the terms and co for issues that arise regarding inform	ce of its products with European Union membe	ove. If a homogeneous material within the part er level components, the declaration shall l correct to the best of its knowledge and belief, r state laws that implement the RoHS Directive. wever, in situations where Supplier has not tions are at least as comprehensive as the anty rights and/or remedies provided as part of				
RoHS Declaration * 1 - Item(s)	does not contain RoHS restricted substa	ances per the definitio	on above	Supplier Acceptance	* Accepted				
Exemption: If the declared item does not con applicable exemptions.	ntain RoHS restricted substances per	the definition above	except for defined RoHS exempti	ons, then select the corresponding response i	n the RoHS Declaration above and choose all				
Exemption List Version	EL-2011/534/EU								
Declaration Signature									
Instructions: Complete all of the required fields on all pages of this form. Select the "Accepted" on the Supplier Acceptance drop-down. This will display the signature area. Digitally sign the declaration (if required by the Requester) and click on Submit Form to have the form returned to the Requester.									
Supplier Digital Signature Ra	stislav Drska	Le							

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

sigma range of distribution unless otherwise noted).									
Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure	
Die	0.16	mg	Supplier	Silicon (Si)	7440-21-3		0.16	mg	
Die Attach Epoxy	0.18	mg		Epoxy resin	proprietary data		0.117	mg	
			Supplier	Aluminum Trioxide (Al2O3)	1344-28-1		0.063	mg	
Lead Frame	2.75	mg	Supplier	Silver (Ag)	7440-22-4		0.4895	mg	
			Supplier	Zinc (Zn)	7440-66-6		0.0033	mg	
			Supplier	Iron (Fe)	7439-89-6		0.0646	mg	
			Supplier	Copper (Cu)	7440-50-8		2.1926	mg	
Mold Compound-Black	4.9	mg		Epoxy resin	proprietary data		0.245	mg	
			Supplier	Phenolic Resin	Proprietary Data		0.245	mg	
			Supplier	Ortho Cresol Novolac Resin	29690-82-2		0.098	mg	
			Supplier	Carbon Black (C)	1333-86-4		0.0245	mg	
			Supplier	Fused Silica (SiO2)	60676-86-0		4.2875	mg	
Plating	0.14	mg	Supplier	Tin (Sn)	7440-31-5		0.14	mg	
Wire Bond - Au	0.01	mg	Supplier	Gold (Au)	7440-57-5		0.01	mg	

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 signa range of distribution unless otherwise noted).