Material Composition Declaration © Copyright 2005. IPC, Bannockburn, Illinois. All rights reserved under both international and Pan-American copyright conventions.					This document is a declaration of the substances within the manufacturer listed item. Note: if the item is an assembly with lower level parts, the declaration encompasses all lower level materials for which the manufacturer has engineering responsibility.										
1752-21.1	IPC Web Site for Information on IPC 1752 Standard Form Type				* Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Mater					ous Materi	rials and Mfg Information				
Supplie	r Information														
Company name*				ompany unique ID			Unique ID Authority					Response Date*			
nsemi												2025-09-10			
Contact N	lame	Title - Contact				Phone - Contact*				Email - Contact*					
Product-l	Env-Stewards		Product Envi	Product Enviro Compliance			NA				Product-Env-Stewards@onsemi.com				
uthorize	ed Representative*	Title - Representative				Phone - Representative*				Email - Representative*					
Product-Env-Stewards			Product Enviro Compliance				NA				Product-Env-Stewards@onsemi.com				
	Requester Item Number Mfr Item		Number Mfr Item Name				Effective Date Version Manufacturing Site		ing Site	W	eight*	UOM	Unit Type		
		MC3316	MC33166TVG ANA DC-I		OC 3A SW I REG		2025-09-10		CNE			1960.42		mg	Each
Ianufa	cturing Proccess Informa	tion						,							
	Terminal Plating / Grid Array Material		Terminal Base Alloy J-STD		STD-020 MSI	L Rating	Peak Process Body Temperatur		ure Max Ti	me at Peak	Temperatu	re Numb	er of Reflow Cyc	eles	
	Matte Tin (Sn) - annealed		CU Alloy NA		A		0 C 30			seconds 3					
omments	3														
or more	information regarding material	composition	please refer to	page 3											

RoHS Material Composition Declaration			Declaration Type *	Detailed						
Directive 2015/863/EU amending RoHS Directive 2011/65/EU RoHS Definition: Quantity limit of 0.01% by mass (100 PPM) in homogeneous material for Cadmium and quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for Cadmium and quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury (Hg), Hexavalent Chromium (Cr6+), Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE), and Bis(2-ethylhexyl) phthalate (DEHP), Benzyl-butyl phthalate (BBP), Dibutyl phthalate (DBP), Diisobutyl phthalate (DIBP).										
Please indicate whether any homogeneous material (as defined by the RoHS Directive, EU 2011/65/EU and implemented by the laws of the European Union member states) of the part identified on this form contains lead, mercury, cadmium, hexavalentchromium, polybrominated biphenyls and/or polybrominated diphenyl ethers (each a "RoHS restricted substance") in excess of the applicable quantity limit identified above. If a homogeneous material within the part contains a RoHS restricted substance inexcess of an applicable quantity limit, please indicate below which, if any, RoHS exemption you believe may apply. If the part is an assembly with lower level components, the declaration shall encompass all such components. Supplier certifies that it gathered the information it provides in this form using appropriate methods to ensure its accuracy and that such information is true and correct to the best of its knowledges and belief, as of the date that Supplier completes this form. Supplier acknowledges that Company will rely on this certification in determining the compliance of its products with European Union member state laws that implement the RoHS Directive. Company acknowledges that Supplier may have relied on information provided by others in completing this form, and that Supplier may not have independently verified such information. However, in situations where Supplier has not independently verified information provided by others, Supplier agrees that, at a minimum, its paragraph. If the Company and the Supplier supplier have provided certifications regarding their contributions to the part, and those certifications are at least as comprehensive as the certification in this paragraph. If the Company and the Supplier enter into a written agreement with respect to the identified part, the terms and conditions of that agreement, including any warranty rights and/or remedies provided as part of that agreement, will be the sole and exclusivesource of the Supplier's Standard Terms and Conditions of Sale applicable to suc										
RoHS Declaration * 4 - Item(s) does not contain RoHS restricted substance	es per the definition above except for selected exemp	otions Supplier Acceptance	* Accepted						
Exemption: 7a: Lead in high melting temperature type solders (i.e. lead based solder alloys containing 85% by weight or more lead).										
Exemption List Version	EL-2011/534/EU									
Declaration Signature										
Instructions: Complete all of the required f Requester) and click on Submit Form to ha		'Accepted" on the Supplier Acceptance drop-dow	n. This will display the signature area. Digita	lly sign the declaration (if required by the						
Supplier Digital Signature Ra	astislav Drska	-6_								

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).

Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Die	3.55	mg	Supplier	Silicon (Si)	7440-21-3		3.55	mg
Die Attach	82.83	mg	A	Lead (Pb)	7439-92-1	7a	78.6885	mg
			Supplier	Tin (Sn)	7440-31-5		4.1415	mg
Lead Frame	1297.64	mg	Supplier	Copper (Cu)	7440-50-8		1297.64	mg
Mold Compound-Black	543.9	mg		Epoxy resin	proprietary data		38.073	mg
			Supplier	Phenolic Resin	Proprietary Data		38.073	mg
			Supplier	Silica Amorphous (SiO2)	7631-86-9		81.585	mg
			Supplier	Carbon Black (C)	1333-86-4		2.7195	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		383.4495	mg
Plating	31.13	mg	Supplier	Tin (Sn)	7440-31-5		31.13	mg
Wire Bond - Cu	1.37	mg	Supplier	Copper (Cu)	7440-50-8		1.37	mg