IPC ASSOCIATION ELECTRONIC		Material Composition Declaration © Copyright 2005. IPC, Bannockburn, Illinois. All rights reserved under be international and Pan-American copyright conventions.			nder both	This document is a declaration of the substances within the manufacturer listed item. Note: if the item is an assembly with lower level parts, the declaration encompasses all lower level materials for which the manufacturer has engineering responsibility.									
752-21.1					Form Type 'Distribute	* Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Mater					eous Materia	ials and Mfg Information			
Supplier	r Information						·								
Company name* Company				any unique ID			Unique ID Authority					Response Date*			
nsemi												2024-05-18			
Contact N	Jame		Title - Contact			]	Phone - Contact*				Email - Contact*				
Product-I	Env-Stewards		Product Enviro Compliance				NA				Product-Env-Stewards@onsemi.com				
uthorize	ed Representative*	Title - Representative			1	Phone - Representative*				Email - Representative*					
Product-I	Env-Stewards	Product Enviro Compliance				NA				Product-Env-Stewards@onsemi.com					
	Requester Item Number Mfr Ite		m Number Mfr Item Name				Effective Date Version Manufacturing Si		ring Site	V	Veight*	UOM	Unit Type		
		MC74HC1G02DTT1G LOG CMOS GATE NAN		E NAND 2INP	Т	2024-05-18		1	MY1		1	4.08	mg	Each	
Ianufa	cturing Proccess Inform	ation						•							
	Terminal Plating / Grid Array Material		Terminal Base Alloy J-STD-02		-STD-020 MSL	Rating	Peak Process Body Tempera		Temperatu	ture Max Time at Peak Tempera		Temperatu	ire Numb	er of Reflow Cyc	eles
Matte Tin (Sn) - annealed			CU Alloy 1				260 C 30				seconds 3				
omments	3														
vel 1 - m	aximum time at peak tempera	ture during sol	ldering is 10-3	0 seconds											
or more	information regarding materia	al composition	please refer to	page 3											

RoHS Material Composition Declaration			Declaration Type *	Detail	ed				
Directive 2015/863/EU amending RoHS Directive 2011/65/EU		ium (Cr6+), Polybrominated Biphenyls (PB)	erial for Cadmium and quantity limit of 0.1% b B), Polybrominated Diphenyl Ethers (PBDE), a						
cadmium, hexavalentchromium, polybromin contains a RoHS restricted substance inexce encompass all such components. Supplier cet as of the date that Supplier completes this Company acknowledges that Supplier may hindependently verified information provided certification in this paragraph. If the Compan	nated biphenyls and/or polybrominated diphess of an applicable quantity limit, please indriffes that it gathered the information it provom. Supplier acknowledges that Company wave relied on informationprovided by others of the supplier agrees that, at a minimusy and the Supplier enter into a written agree yesource of the Supplier's liability and the C	enyl ethers (each a "RoHS restricted substan licate below which, if any, RoHS exemption vides in this form using appropriate methods vill rely on this certification in determining the s in completing this form, and that Supplier um, itssuppliers have provided certifications ement with respect to the identified part, the tompany's remedies for issues that arise rega	s of the European Union member states) of the ce") in excess of the applicable quantity limit is you believe may apply. If the part is an assemb to ensure its accuracy and that such informatio e compliance of its products with European Ur may not have independently verified such infor regarding their contributions to the part, and the erms and conditions of that agreement, including information the Supplier provides in this	dentified above. If a ally with lower level in is true and correct tion member state la mation. However, in ose certifications are ag any warranty righ	homogeneous material within the part components, the declaration shall to the best of its knowledge and belief, was that implement the RoHS Directive. In situations where Supplier has not the at least as comprehensive as the lats and/or remedies provided as part of				
RoHS Declaration * 1 - Item	(s) does not contain RoHS restricted substar	nces per the definition above	Supplier A	cceptance *	Accepted				
Exemption: If the declared item does not contain RoHS restricted substances per the definition above except for defined RoHS exemptions, then select the corresponding response in the RoHS Declaration above and choose all applicable exemptions.									
Exemption List Version	EL-2011/534/EU								
Declaration Signature									
		e "Accepted" on the Supplier Acceptance	drop-down. This will display the signature a	rea. Digitally sign t	the declaration (if required by the				

## **Homogeneous Material Composition Declaration for Electronic Products**

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).

Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Die	0.42	mg	Supplier	Silicon (Si)	7440-21-3		0.42	mg
Die Attach	0.11	mg	Supplier	Silver (Ag)	7440-22-4		0.088	mg
			Supplier	Phenolic Resin-2	54208-63-8		0.022	mg
Lead Frame	5.78	mg	Supplier	Silver (Ag)	7440-22-4		0.0705	mg
			Supplier	Zinc (Zn)	7440-66-6		0.0069	mg
			Supplier	Iron (Fe)	7439-89-6		0.1358	mg
			Supplier	Copper (Cu)	7440-50-8		5.565	mg
			Supplier	Phosphorus (P)	7723-14-0		0.0017	mg
Mold Compound-Black	7.34	mg		Epoxy resin	proprietary data		0.367	mg
			Supplier	Phenolic Resin	Proprietary Data		0.367	mg
			Supplier	Ortho Cresol Novolac Resin	29690-82-2		0.1468	mg
			Supplier	Carbon Black (C)	1333-86-4		0.0367	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		6.4225	mg
Plating	0.39	mg	Supplier	Tin (Sn)	7440-31-5		0.39	mg
Wire Bond - Au	0.04	mg	Supplier	Gold (Au)	7440-57-5		0.04	mg