ABSOCIATION CONNECTING ELECTRONICS INDUSTRIES® International and Pan-An	Bannockburn, Illin	nois. All rights reserved u	inder both	This docume level parts, th	ent is a declaration e	ion of the su	ibstances v s all lower	within the manufactu level materials for w	rer listed it which the m	em. Note: anufacture	if the item is an as r has engineering	sembly with lowe responsibility.	
	IPC Web Site for Information on IPC-1752 Standard Form T http://www.ipc.org/IPC-175x Distrib			* Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Materia					ials and Mf	als and Mfg Information			
Supplier Information													
Company name*	ny unique ID	inique ID			Unique ID Authority				Response Date*				
semi									2025-06-06				
Contact Name	ame Title - Contact			1	Phone - Contact*				Email - Contact*				
Product-Env-Stewards	duct-Env-Stewards Product Enviro Compliance			NA					Product-Env-Stewards@onsemi.com				
uthorized Representative* Title - Representative				Phone - Representative*				Email - Representative*					
Product-Env-Stewards	t Enviro Compliance	viro Compliance			NA				Product-Env-Stewards@onsemi.com				
Requester Item Number	hber Mfr Item Number		nber Mfr Item Name		Effective Date	Version	Ν	Manufacturing Site		Veight*	UOM	Unit Type	
	MC74VHC1GT02 1G	74VHC1GT02DFT LOG CMOS GAT		E NOR SNGL			С	CN1		5.2	mg	Each	
Manufacturing Proccess Information	I												
Terminal Plating / Grid Array Materia	al Terminal Base Alloy		J-STD-020 MSL	Rating	Peak Proc	k Process Body Temperature Max Time at Peak		Temperature Number of Reflow Cycles		les			
Matte Tin (Sn) - annealed CU Alloy			1		260		С	30	second	is 3			
Comments													
evel 1 - maximum time at peak temperature d	uring soldering is	s 10-30 seconds											
or more information regarding material com	position please re	efer to page 3											

RoHS Material Composition Declaration				Declaration Type *	Detailed					
Directive 2015/863/EU amending RoHS Directive 2011/65/EU	RoHS Definition: Quantity limit of 0.01% by mass (100 PPM) in homogeneous material for Cadmium and quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury (Hg), Hexavalent Chromium (Cr6+), Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE), and Bis(2-ethylhexyl) phthalate (DEHP), Benzyl-butyl phthalate (BBP), Dibutyl phthalate (DBP), Diisobutyl phthalate (DIBP).									
cadmium, hexavalentchromium, polybrominate contains a RoHS restricted substance inexcess encompass all such components. Supplier certif as of the date that Supplier completes this form Company acknowledges that Supplier may hav independently verified information provided by certification in this paragraph. If the Company a	ed biphenyls and/or polybrominated dip of an applicable quantity limit, please ir ies that it gathered the information it pro- .Supplier acknowledges that Company e relied on informationprovided by othe y others, Supplier agrees that, at a minin and the Supplier enter into a written agre pource of the Supplier's liability and the	henyl ethers (each a " ndicate below which, i ovides in this form us will rely on this certifiers in completing this num, itssuppliers have eement with respect to Company's remedies	RoHS restricted substance") in exce if any, RoHS exemption you believe ing appropriate methods to ensure if ication in determining the complian form, and that Supplier may not have e provided certifications regarding the to the identified part, the terms and cc for issues that arise regarding inform	ce of its products with European Union membe	ove. If a homogeneous material within the part er level components, the declaration shall l correct to the best of its knowledge and belief, r state laws that implement the RoHS Directive. wever, in situations where Supplier has not tions are at least as comprehensive as the anty rights and/or remedies provided as part of					
RoHS Declaration * 1 - Item(s)	does not contain RoHS restricted substa	ances per the definitio	on above	Supplier Acceptance	* Accepted					
Exemption: If the declared item does not con applicable exemptions.	ntain RoHS restricted substances per	the definition above	except for defined RoHS exempti	ons, then select the corresponding response i	n the RoHS Declaration above and choose all					
Exemption List Version	EL-2011/534/EU									
Declaration Signature										
Instructions: Complete all of the required fin Requester) and click on Submit Form to have	elds on all pages of this form. Select the form returned to the Requester	he "Accepted" on th	e Supplier Acceptance drop-down	. This will display the signature area. Digital	lly sign the declaration (if required by the					
Supplier Digital Signature Ra	stislav Drska	Le								

## Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Die	0.19	mg	Supplier	Silicon (Si)	7440-21-3	Exempt	0.19	mg
Lead Frame	2.04	mg	В	Nickel (Ni)	7440-02-0		0.7813	mg
		-	Supplier	Iron (Fe)	7439-89-6		1.0792	mg
			Supplier	Copper (Cu)	7440-50-8		0.1795	mg
Mold Compound-Black	3.9	mg	Supplier	Boron zinc hydroxide oxide	138265-88-0		0.117	mg
			Supplier	Zinc Monoxide (ZnO)	1314-13-2		0.0195	mg
			Supplier	2,4,6-triamino-s-triazincompd.withs- triazine-triol	37640-57-6		0.117	mg
			Supplier	Silica Amorphous (SiO2)	7631-86-9		3.12	mg
			Supplier	Carbon Black (C)	1333-86-4		0.039	mg
			Supplier	Ortho-Cresol Novolac Resin	29690-82-2		0.312	mg
			Supplier	Phenolic Resin (Novolac)	9003-35-4		0.1755	mg
Plating	0.05	mg	Supplier	Tin (Sn)	7440-31-5		0.05	mg
Wire Bond - Cu	0.02	mg	Supplier	Copper (Cu)	7440-50-8		0.02	mg

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 signa range of distribution unless otherwise noted).