IPC ASSOCIATION CONI	© Copyright 2005.	Material Composition Declaration © Copyright 2005. IPC, Bannockburn, Illinois. All rights reserved under both international and Pan-American copyright conventions.			der both	This document is a declaration of the substances within the manufacturer listed item. Note: if the item is an assembly with lower level parts, the declaration encompasses all lower level materials for which the manufacturer has engineering responsibility.								
752-21.1		IPC Web Site for Information on IPC-1752 Standard Form Tyl http://www.ipc.org/IPC-175x Distribut								ials and Mfg Information				
upplier Inf	formation													
Company name*			Company unique ID			τ	Unique ID Authority				Response Date*			
nsemi											2024-09-20			
Contact Name		Title - Contact			F	Phone - Contact*				Email - Contact*				
Product-Env-S	Stewards		Product Enviro Compliance			1	NA				Product-Env-Stewards@onsemi.com			
uthorized Re	epresentative*	Title - Representative			F	Phone - Representative*				Email - Representative*				
Product-Env-S	Stewards		Product Enviro Compliance]	NA				Product-Env-Stewards@onsemi.com			
Rec	Requester Item Number		Mfr Item Number Mfr Item Name					Version	N	Manufacturing Site	We	ight*	UOM	Unit Type
		MC78M15CDTT5G ANA		ANA 500MA 15V VREG			2024-09-20		N	MY1).99	mg	Each
	ring Proccess Informa										·			
2		Terminal Base Alloy J-STD-020 MS		STD-020 MSL	Rating	Peak Process Body Temperate				Temperature	Numb	er of Reflow Cyc	eles	
Mat	tte Tin (Sn) - annealed		CU Alloy	1			260		C	30	seconds	3		
omments														
vel 1 - maxim	num time at peak temperat	ture during sol	dering is 10-3	30 seconds										
or more infor	rmation regarding materia	l composition	please refer to	page 3										

RoHS Material Composition Declaration			Declaration Type *	Detailed							
Directive 2015/863/EU amending RoHS Directive 2011/65/EU											
Please indicate whether any homogeneous material (as defined by the RoHS Directive, EU 2011/65/EU and implemented by the laws of the European Union member states) of the part identified on this form contains lead, mercury, cadmium, hexavalentchromium, polybrominated biphenyls and/or polybrominated diphenyl ethers (each a "RoHS restricted substance") in excess of the applicable quantity limit identified above. If a homogeneous material within the part contains a RoHS restricted substance inexcess of an applicable quantity limit, please indicate below which, if any, RoHS exemption you believe may apply. If the part is an assembly with lower level components, the declaration shall encompass all such components. Supplier certifies that it gathered the information it provides in this form using appropriate methods to ensure its accuracy and that such information is true and correct to the best of its knowledge and belief, as of the date that Supplier completes this form. Supplier acknowledges that Company will rely on this certification in determining the compliance of its products with European Union member state laws that implement the RoHS Directive. Company acknowledges that Supplier may have relied on information provided by others in completing this form, and that Supplier may not have independently verified such information. However, in situations where Supplier has not independently verified information provided by others, Supplier agrees that, at a minimum, its paragraph. If the Company and the Supplier enter into a written agreement with respect to the identified part, the terms and conditions of that agreement, including any warranty rights and/or remedies provided as part of that agreement, will be the sole and exclusivesource of the Supplier's Itability and the Company's remedies for issues that arise regarding information the Supplier provides in this form. In the absence of such written agreement, the warranty rights and/or remedies of Supplier's Standard Terms and Conditions of Sale applicable to suc											
RoHS Declaration * 4 - Item(s) does not contain RoHS restricted substance	es per the definition above except for selected exemp	otions Supplier Acceptance	* Accepted							
Exemption: 7a: Lead in high melting temperature type solders (i.e. lead based solder alloys containing 85% by weight or more lead).											
Exemption List Version	EL-2011/534/EU										
Declaration Signature											
Instructions: Complete all of the required fields on all pages of this form. Select the "Accepted" on the Supplier Acceptance drop-down. This will display the signature area. Digitally sign the declaration (if required by the Requester) and click on Submit Form to have the form returned to the Requester.											
Supplier Digital Signature Ra	astislav Drska	-6_									

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).

Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Die	0.2	mg	Supplier	Silicon (Si)	7440-21-3		0.2	mg
Die Attach	1.4	mg	A	Lead (Pb)	7439-92-1	7a	1.33	mg
			Supplier	Tin (Sn)	7440-31-5		0.07	mg
Lead Frame	214.64	mg	В	Nickel (Ni)	7440-02-0		0.4293	mg
			Supplier	Copper (Cu)	7440-50-8		214.2107	mg
Mold Compound-Black	129.65	mg		Phenolic Resin	proprietary data		10.372	mg
			Supplier	Ortho Cresol Novolac Resin	29690-82-2		10.372	mg
			Supplier	Carbon Black (C)	1333-86-4		0.6482	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		108.2577	mg
Plating	3.73	mg	Supplier	Tin (Sn)	7440-31-5		3.73	mg
Wire Bond - Cu	1.37	mg	Supplier	Copper (Cu)	7440-50-8		1.37	mg