consemi Contact Name Title - Contact Phone - Contact* Product-Env-Stewards Product Enviro Compliance Authorized Representative* Title - Representative Phone - Representative*	Response Date* 2025-08-03 Email - Contact* Product-Env-Stew	vards@onsemi.	com	
Company name* Company unique ID Unique ID Authority R Contact Name Title - Contact Phone - Contact* E Product-Env-Stewards Product Enviro Compliance NA Itle - Representative* Title - Representative Phone - Representative* E Product-Env-Stewards Product Enviro Compliance NA I	2025-08-03 Email - Contact* Product-Env-Stew		com	
nsemi Title - Contact Product-Env-Stewards Product Enviro Compliance Uthorized Representative* Title - Representative Product-Env-Stewards Product Enviro Compliance NA Interpresentative Product-Env-Stewards Product Enviro Compliance NA Interpresentative Product-Env-Stewards Product Enviro Compliance NA Interpresentative	2025-08-03 Email - Contact* Product-Env-Stew		com	
Title - Contact Product-Env-Stewards Product Enviro Compliance NA I tuthorized Representative* Title - Representative Product-Env-Stewards Product-Enviro Compliance NA I Title - Representative Phone - Representative* E Product-Env-Stewards Product Enviro Compliance NA I	Email - Contact* Product-Env-Stew		com	
Product-Env-Stewards Product Enviro Compliance NA I I Title - Representative* Phone - Representative* Enviro Compliance NA I Product-Env-Stewards Product Enviro Compliance NA I	Product-Env-Stew		com	
Authorized Representative* Title - Representative Product-Env-Stewards Product Enviro Compliance NA I			com	
Product-Env-Stewards Product Enviro Compliance NA I	Zmail Danuas 4-			
	Email - Representative*			
Requester Item Number Mfr Item Number Mfr Item Name Effective Date Version Manufacturing Site	Product-Env-Stewards@onsemi.com			
	Weight*	UOM	Unit Type	
MOC3011SR2VM 6PW RP TRIAC T&R VDE 2025-08-03 LITEONFG	464.903	mg	Each	
Innufacturing Process Information Terminal Plating / Grid Array Material Terminal Base Alloy J-STD-020 MSL Rating Peak Process Body Temperature Max Time at Peak Temperature Max Time at Peak Temperature Peak Process Body Temperature Peak Proce	omporatura Numb	ber of Reflow C	valos	
Terminal Plating / Grid Array Material Terminal Base Alloy J-STD-020 MSL Rating Peak Process Body Temperature Max Time at Peak Tempe		ber of Reflow C	ycies	
	seconds 3			
omments				
vel 1 - maximum time at peak temperature during soldering is 10-30 seconds or more information regarding material composition please refer to page 3				

RoHS Material Composition Declaration			Declaration Type *	Detail	ed				
Directive 2015/863/EU amending RoHS Directive 2011/65/EU RoHS Definition: Quantity limit of 0.01% by mass (100 PPM) in homogeneous material for Cadmium and quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury (Hg), Hexavalent Chromium (Cr6+), Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE), and Bis(2-ethylhexyl) phthalate (DEHP), Benzyl-butyl phthalate (BBP), Dibutyl phthalate (DBP), Diisobutyl phthalate (DIBP).									
Please indicate whether any homogeneous material (as defined by the RoHS Directive, EU 2011/65/EU and implemented by the laws of the European Union member states) of the part identified on this form contains lead, mercury, cadmium, hexavalentchromium, polybrominated biphenyls and/or polybrominated diphenyl ethers (each a "RoHS restricted substance") in excess of the applicable quantity limit identified above. If a homogeneous material within the part contains a RoHS restricted substance inexcess of an applicable quantity limit, please indicate below which, if any, RoHS exemption you believe may apply. If the part is an assembly with lower level components, the declaration shall encompass all such components. Supplier certifies that it gathered the information it provides in this form using appropriate methods to ensure its accuracy and that such information is true and correct to the best of its knowledge and belief, as of the date that Supplier completes this form. Supplier acknowledges that Company will rely on this certification in determining the compliance of its products with European Union member state laws that implement the RoHS Directive. Company acknowledges that Supplier may have relied on informationprovided by others in completing this form, and that Supplier may not have independently verified such information. However, in situations where Supplier has not independently verified information provided by others, Supplier agrees that, at a minimum, its uppliers have provided certifications regarding their contributions to the part, and those certifications are at least as comprehensive as the certification in this paragraph. If the Company and the Supplier near into a written agreement with respect to the identified part, the terms and conditions of that agreement, including any warranty rights and/or remedies provided as part of that agreement, will be the sole and exclusivesource of the Supplier's Standard Terms and Conditions of Sale applicable to such part shall apply.									
RoHS Declaration * 1 - Item	(s) does not contain RoHS restricted substar	nces per the definition above	Supplier A	cceptance *	Accepted				
Exemption: If the declared item does not contain RoHS restricted substances per the definition above except for defined RoHS exemptions, then select the corresponding response in the RoHS Declaration above and choose all applicable exemptions.									
Exemption List Version	EL-2011/534/EU								
Declaration Signature									
		e "Accepted" on the Supplier Acceptance	drop-down. This will display the signature a	rea. Digitally sign t	the declaration (if required by the				

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).

Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Coupling Gel	0.4	mg	Supplier	Dimethyl Cyclosiloxanes	69430-24-6		0.04	mg
			Supplier	Trimethoxy(methyl)silane (C4H12O3Si)	1185-55-3		0.36	mg
Die	5.13	mg	Supplier	Silicon (Si)	7440-21-3		5.13	mg
Die Attach	0.3	mg	Supplier	Silver (Ag)	7440-22-4		0.225	mg
			Supplier	Phenolic Resin-2	54208-63-8		0.075	mg
Lead Frame 1	101.703	mg	Supplier	Silver (Ag)	7440-22-4		0.407	mg
			Supplier	Zinc (Zn)	7440-66-6		0.203	mg
			Supplier	Iron (Fe)	7439-89-6		2.64	mg
			Supplier	Copper (Cu)	7440-50-8		98.3	mg
			Supplier	Phosphorus (P)	7723-14-0		0.153	mg
Mold Compound-White	327.22		Supplier	Titanium Dioxide (TiO2)	13463-67-7		81.805	mg
			В	Brominated Bisphenol A Diglycidyl Ether	40039-93-8		9.8166	mg
			Supplier	Ortho Cresol Novolac Resin	29690-82-2		44.1747	mg
			В	Antimony Trioxide (Sb2O3)	1309-64-4		9.8166	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		163.61	mg
			Supplier	Phenolic Resin (Novolac)	9003-35-4		17.9971	mg
Plating	28.5	mg	Supplier	Tin (Sn)	7440-31-5		28.5	mg
Wire Bond - Au	1.65	mg	Supplier	Gold (Au)	7440-57-5		1.65	mg