IPC  ASSOCIATION CONI	© Copyright 2005.	Material Composition Declaration © Copyright 2005. IPC, Bannockburn, Illinois. All rights reserved under both international and Pan-American copyright conventions.			der both	This document is a declaration of the substances within the manufacturer listed item. Note: if the item is an assembly with lower level parts, the declaration encompasses all lower level materials for which the manufacturer has engineering responsibility.									
752-21.1		IPC Web Site for Information on IPC-1752 Standard  http://www.ipc.org/IPC-175x  Form Typ Distribute				* Declaration Class * Class 6 - RoHS Yes/No. Homogeneous Materi					erials and l	ials and Mfg Information			
upplier Inf	formation														
Company name*			Company unique ID			Ţ	Unique ID Authority				Respo	Response Date*			
nsemi											2025-0	2025-06-03			
Contact Name	<b>.</b>	Title - Contact			I	Phone - Contact*				Email	Email - Contact*				
Product-Env-S	Stewards		Product Enviro Compliance				NA				Produ	Product-Env-Stewards@onsemi.com			
uthorized Re	epresentative*	Title - Representative			I	Phone - Representative*				Email	Email - Representative*				
Product-Env-S	Stewards		Product Enviro Compliance				NA				Produ	Product-Env-Stewards@onsemi.com			
Rec	quester Item Number	Mfr Item	Number	Mfr Item Name			Effective Date	e Versio	on	Manufacturing Site		Weight*	UOM	Unit Type	
		MUN214	40T1G	SS SC59 BR XSTR	R NPN 50V		2025-06-03					11.03	mg	Each	
Ianufactur	ring Proccess Informa	ation												·	
Terminal Plating / Grid Array Material T			Ferminal Base Alloy J-STD-020 MSL		Rating	Peak Process Body Temperature		re Max Time at Pe	ak Temper	ature Num	ber of Reflow Cyc	eles			
Matte Tin (Sn) - annealed			CU Alloy 1			260		C	30	seco	onds 3				
omments															
vel 1 - maxim	num time at peak temperat	ture during sol	dering is 10-3	30 seconds											
or more infor	rmation regarding materia	l composition	please refer t	o page 3											

RoHS Material Composition Declaration			Declaration Type *	Detail	led					
Directive 2015/863/EU amending RoHS Directive 2011/65/EU  RoHS Definition: Quantity limit of 0.01% by mass (100 PPM) in homogeneous material for Cadmium and quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury (Hg), Hexavalent Chromium (Cr6+), Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE), and Bis(2-ethylhexyl) phthalate (DEHP), Benzyl-butyl phthalate (BBP), Dibutyl phthalate (DBP), Diisobutyl phthalate (DIBP).										
Please indicate whether any homogeneous material (as defined by the RoHS Directive, EU 2011/65/EU and implemented by the laws of the European Union member states) of the part identified on this form contains lead, mercury, cadmium, hexavalentchromium, polybrominated biphenyls and/or polybrominated diphenyl ethers (each a "RoHS restricted substance") in excess of the applicable quantity limit identified above. If a homogeneous material within the part contains a RoHS restricted substance inexcess of an applicable quantity limit, please indicate below which, if any, RoHS exemption you believe may apply. If the part is an assembly with lower level components, the declaration shall encompass all such components. Supplier certifies that it gathered the information it provides in this form using appropriate methods to ensure its accuracy and that such information is true and correct to the best of its knowledge and belief, as of the date that Supplier completes this form. Supplier acknowledges that Company will rely on this certification in determining the compliance of its products with European Union member state laws that implement the RoHS Directive. Company acknowledges that Supplier may have relied on information provided by others in completing this form, and that Supplier may not have independently verified such information. However, in situations where Supplier have provided certifications regarding their contributions to the part, and those certifications are at least as comprehensive as the certification in this paragraph. If the Company and the Supplier enter into a written agreement with respect to the identified part, the terms and conditions of that agreement, including any warranty rights and/or remedies provided as part of that agreement, will be the sole and exclusivesource of the Supplier's Itability and the Company's remedies for issues that arise regarding information the Supplier provides in this form. In the absence of such written agreement, the warranty rights and/or remedies of Supplier's St										
RoHS Declaration * 1 - Item	(s) does not contain RoHS restricted substa	ances per the definition above	Supplier Ac	ceptance *	Accepted					
Exemption: If the declared item does not contain RoHS restricted substances per the definition above except for defined RoHS exemptions, then select the corresponding response in the RoHS Declaration above and choose all applicable exemptions.										
Exemption List Version	EL-2011/534/EU									
Declaration Signature										
Instructional Complete all of the required	fields on all neggs of this form. Calcut th		a duan dawn. This will display the signature on	a Digitally sign	the declaration (if recruired by the					
Instructions: Complete all of the required Requester) and click on Submit Form to			e drop-down. This will display the signature ar	ea. Digitally sign	the declaration (if required by the					

## **Homogeneous Material Composition Declaration for Electronic Products**

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).

Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Die	0.22	mg	Supplier	Silicon (Si)	7440-21-3		0.22	mg
Lead Frame	3.06		В	Nickel (Ni)	7440-02-0		1.2393	mg
			Supplier	Iron (Fe)	7439-89-6		1.6983	mg
			Supplier	Copper (Cu)	7440-50-8		0.1224	mg
Mold Compound-Black	7.13		Supplier	Ortho Cresol Novolac Resin	29690-82-2		0.713	mg
			Supplier	Carbon Black (C)	1333-86-4		0.0356	mg
			Supplier	Aluminum Hydroxide (Al(OH)3)	21645-51-2		1.0338	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		4.6345	mg
			Supplier	Phenolic Resin (Novolac)	9003-35-4		0.713	mg
Plating	0.52	mg	Supplier	Tin (Sn)	7440-31-5		0.52	mg
Wire Bond - Cu	0.1	mg	Supplier	Copper (Cu)	7440-50-8		0.1	mg