ASSOCIATION CONNECT	© Copyright 2005, IPC	Material Composition Declaration © Copyright 2005. IPC, Bannockburn, Illinois. All rights reserved under both international and Pan-American copyright conventions.				This document is a declaration of the substances within the manufacturer listed item. Note: if the item is an assembly with low level parts, the declaration encompasses all lower level materials for which the manufacturer has engineering responsibility.									
752-21.1		IPC Web Site for Information on IPC-1752 Standard Form Typ http://www.ipc.org/IPC-175x Distribute				* Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Mater						als and Mf	g Informa	ation	
Supplier Infor	rmation														
Company name*			Company unique ID			τ	Unique ID Authority					Response Date*			
nsemi												2025-06-08			
Contact Name		Title - Contact			I	Phone - Contact*					Email - Contact*				
Product-Env-Ste	wards	Product Enviro Compliance				NA					Product-Env-Stewards@onsemi.com				
authorized Repre	esentative*	Title - Representative			I	Phone - Representative*				Email - Representative*					
Product-Env-Ste	wards	Product Enviro Compliance				NA				Product-Env-Stewards@onsemi.com					
Reque	ester Item Number	r Item Number Mfr Iter		Item Number Mfr Item Name			Effective Dat	e Versio	Version Manufacturing Site		W	eight*	UOM	Unit Type	
		N24C64UD7		UDTG 64Kb I2C SER EEPROM			2025-06-08		7	ТНВ		1	.479	mg	Each
Ianufacturin	g Proccess Information	on												1	
Termin	al Plating / Grid Array Material		Terminal Base Alloy		J-STD-020 MS	SL Rating	Peak Process Body Temperature		e Max Time	ne at Peak Tempera		re Num	nber of Reflow Cyc	eles	
Precious metal (e.g. Ag,Au, NiPdAu) (no Sn)			CU Alloy 1		1		260		C 3			second	s 3		
Comments															
vel 1 - maximun	n time at peak temperatur	e during so	ldering is 10-3	30 seconds											
or more informa	ation regarding material co	mposition	please refer to	o page 3											

RoHS Material Composition Declaration			Declaration Type *	Detail	ed						
Directive 2015/863/EU amending RoHS Directive 2011/65/EU RoHS Definition: Quantity limit of 0.01% by mass (100 PPM) in homogeneous material for Cadmium and quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury (Hg), Hexavalent Chromium (Cr6+), Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE), and Bis(2-ethylhexyl) phthalate (DEHP), Benzyl-butyl phthalate (BBP), Dibutyl phthalate (DBP), Diisobutyl phthalate (DIBP).											
Please indicate whether any homogeneous material (as defined by the RoHS Directive, EU 2011/65/EU and implemented by the laws of the European Union member states) of the part identified on this form contains lead, mercury, cadmium, hexavalentchromium, polybrominated biphenyls and/or polybrominated diphenyl ethers (each a "RoHS restricted substance") in excess of the applicable quantity limit identified above. If a homogeneous material within the part contains a RoHS restricted substance inexcess of an applicable quantity limit, please indicate below which, if any, RoHS exemption you believe may apply. If the part is an assembly with lower level components, the declaration shall encompass all such components. Supplier certifies that it gathered the information it provides in this form using appropriate methods to ensure its accuracy and that such information is true and correct to the best of its knowledges and belief, as of the date that Supplier completes this form. Supplier acknowledges that Company will rely on this certification in determining the compliance of its products with European Union member state laws that implement the RoHS Directive. Company acknowledges that Supplier may have relied on information provided by others in completing this form, and that Supplier may not have independently verified such information. However, in situations where Supplier has not independently verified information provided by others, Supplier agrees that, at a minimum, its paragraph. If the Company and the Supplier shall apply the interest of the identified part, the terms and conditions of that agreement, including any warranty rights and/or remedies provided as part of that agreement, will be the sole and exclusivesource of the Supplier's liability and the Company's remedies for issues that arise regarding information the Supplier provides in this form. In the absence of such written agreement, the warranty rights and/or remedies of Supplier's Standard Terms and Conditions of Sale applicable to such part shall apply											
RoHS Declaration * 1 - Item	(s) does not contain RoHS restricted substar	nces per the definition above	Supplier A	cceptance *	Accepted						
Exemption: If the declared item does not contain RoHS restricted substances per the definition above except for defined RoHS exemptions, then select the corresponding response in the RoHS Declaration above and choose all applicable exemptions.											
Exemption List Version	EL-2011/534/EU										
Declaration Signature											
		e "Accepted" on the Supplier Acceptance	drop-down. This will display the signature a	rea. Digitally sign t	the declaration (if required by the						

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).

Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Die	0.15	mg	Supplier	Silicon (Si)	7440-21-3		0.15	mg
Die Attach Tape	0.019	mg	Supplier	Oxirane, (chloromethyl)-, homopolymer	24969-06-0		0.0029	mg
			Supplier	2-Propenoic acid, 2-methyl-, polymer with butyl 2-propenoate and methyl 2-methyl-2-propenoate	25035-69-2		0.0029	mg
			Supplier	Proprietary	Proprietary Data		0.0019	mg
			Supplier	Silica Amorphous (SiO2)	7631-86-9		0.0085	mg
			Supplier	Phenolic Resin (Novolac)	9003-35-4		0.0029	mg
Lead Frame	4.7	mg	Supplier	Zinc (Zn)	7440-66-6		0.0056	mg
			Supplier	Iron (Fe)	7439-89-6		0.1104	mg
			Supplier	Copper (Cu)	7440-50-8		4.5825	mg
			Supplier	Phosphorus (P)	7723-14-0		0.0014	mg
Mold Compound-Black	6.5	mg		Epoxy resin	proprietary data		0.325	mg
			Supplier	Phenolic Resin	Proprietary Data		0.13	mg
			Supplier	Ortho Cresol Novolac Resin	29690-82-2		0.1625	mg
			Supplier	Carbon Black (C)	1333-86-4		0.0325	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		5.85	mg
Plating	0.09	mg	Supplier	Palladium (Pd)	7440-05-3		0.0022	mg
			В	Nickel (Ni)	7440-02-0		0.0792	mg
			Supplier	Gold (Au)	7440-57-5		0.0086	mg
Wire Bond - Au	0.02	mg	Supplier	Gold (Au)	7440-57-5		0.02	mg