ASSOCIATION CONNECTED INDUST	© Copyright 2005. IPC	Material Composition Declaration © Copyright 2005. IPC, Bannockburn, Illinois. All rights reserved under both international and Pan-American copyright conventions.				This document is a declaration of the substances within the manufacturer listed item. Note: if the item is an assembly with lowelevel parts, the declaration encompasses all lower level materials for which the manufacturer has engineering responsibility.									
752-21.1		IPC Web Site for Information on IPC-1752 Standard Form Thttp://www.ipc.org/IPC-175x Distrib													
upplier Info	rmation														
Company name* Company uniqu			rique ID t			Unique ID Authority					Response Date*				
nsemi											2024-04-	2024-04-19			
Contact Name Title - Contact				- Contact			Phone - Contact*				Email - 0	Email - Contact*			
Product-Env-Ste	ewards	Product Enviro Compliance			N.	NA				Product	Product-Env-Stewards@onsemi.com				
authorized Repro	esentative*	Title - Representative			Ph	Phone - Representative*				Email - 1	Email - Representative*				
Product-Env-Ste	ewards	Product Enviro Compliance			N.	NA				Product	Product-Env-Stewards@onsemi.com				
Reque	ester Item Number Mfr Item		Number	Mfr Item Name		Effective Da		Version	Ma	Manufacturing Site		Veight*	UOM	Unit Type	
		NCD57200DR2		2G High Voltage, Low and Isolated High Side Gate Driver		Side 20	2024-04-19 PH1		80.44 mg		Each				
Ianufacturin	ng Proccess Informatio	n													
Termin	Terminal Plating / Grid Array Material		Terminal Base Alloy J		J-STD-020 MSL Ratio	020 MSL Rating		Peak Process Body Temperature		Max Time at Pea	k Temperati	ire Num	e Number of Reflow Cycles		
Precious metal (e.g. Ag,Au, NiPdAu) (no Sn)			CU Alloy 1		1		260			seco		seconds 3			
Comments															
vel 1 - maximun	n time at peak temperature	during so	ldering is 10-3	30 seconds											
	ation regarding material co														

RoHS Material Composition Declaration			Declaration Type *	Detail	ed						
Directive 2015/863/EU amending RoHS Directive 2011/65/EU RoHS Definition: Quantity limit of 0.01% by mass (100 PPM) in homogeneous material for Cadmium and quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury (Hg), Hexavalent Chromium (Cr6+), Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE), and Bis(2-ethylhexyl) phthalate (DEHP), Benzyl-butyl phthalate (BBP), Dibutyl phthalate (DBP), Diisobutyl phthalate (DIBP).											
Please indicate whether any homogeneous material (as defined by the RoHS Directive, EU 2011/65/EU and implemented by the laws of the European Union member states) of the part identified on this form contains lead, mercury, cadmium, hexavalentchromium, polybrominated biphenyls and/or polybrominated diphenyl ethers (each a "RoHS restricted substance") in excess of the applicable quantity limit identified above. If a homogeneous material within the part contains a RoHS restricted substance inexcess of an applicable quantity limit, please indicate below which, if any, RoHS exemption you believe may apply. If the part is an assembly with lower level components, the declaration shall encompass all such components. Supplier certifies that it gathered the information it provides in this form using appropriate methods to ensure its accuracy and that such information is true and correct to the best of its knowledge and belief, as of the date that Supplier completes this form. Supplier acknowledges that Company will rely on this certification in determining the compliance of its products with European Union member state laws that implement the RoHS Directive. Company acknowledges that Supplier may have relied on informationprovided by others in completing this form, and that Supplier may not have independently verified such information. However, in situations where Supplier has not independently verified information provided by others, Supplier agrees that, at a minimum, its provided certifications regarding their contributions to the part, and those certifications are at least as comprehensive as the certification in this paragraph. If the Company and the Supplier enter into a written agreement with respect to the identified part, the terms and conditions of that agreement, including any warranty rights and/or remedies provided as part of that agreement, will be the sole and exclusivesource of the Supplier's liability and the Company's remedies for issues that arise regarding information the Supplier provides in this for											
RoHS Declaration * 1 - Item	(s) does not contain RoHS restricted substar	nces per the definition above	Supplier A	cceptance *	Accepted						
Exemption: If the declared item does not contain RoHS restricted substances per the definition above except for defined RoHS exemptions, then select the corresponding response in the RoHS Declaration above and choose all applicable exemptions.											
Exemption List Version	EL-2011/534/EU										
Declaration Signature											
		e "Accepted" on the Supplier Acceptance	drop-down. This will display the signature a	rea. Digitally sign t	the declaration (if required by the						

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).

Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Die	2.04	mg	Supplier	Silicon (Si)	7440-21-3		2.04	mg
Die Attach	0.65	mg	Supplier	Silver (Ag)	7440-22-4		0.5525	mg
			Supplier	Ortho Cresol Novolac Resin	29690-82-2		0.0975	mg
Lead Frame	29.12	mg	Supplier	Zinc (Zn)	7440-66-6		0.0349	mg
			Supplier	Iron (Fe)	7439-89-6		0.6989	mg
I			Supplier	Copper (Cu)	7440-50-8		28.3629	mg
			Supplier	Phosphorus (P)	7723-14-0		0.0233	mg
Mold Compound-Black	48.06	mg		Epoxy resin	proprietary data		3.6045	mg
			Supplier	Phenolic Resin	Proprietary Data		1.2015	mg
			Supplier	Silica Amorphous (SiO2)	7631-86-9		3.6045	mg
			Supplier	Carbon Black (C)	1333-86-4		0.2403	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		39.4092	mg
Plating	0.3	mg	Supplier	Palladium (Pd)	7440-05-3		0.021	mg
			В	Nickel (Ni)	7440-02-0		0.273	mg
			Supplier	Gold (Au)	7440-57-5		0.006	mg
Wire Bond - Au	0.27	mg	Supplier	Gold (Au)	7440-57-5		0.27	mg